

SYSTEM AND METHOD IN A DATA TABLE FOR CREATING RECURSIVE SCALABLE TEMPLATE INSTANCES

Technical Field of the invention

The present invention relates to the field of information processing by digital computers, more particularly to a method and system, in a data table, preferably an electronic spreadsheet, for creating recursive scalable template instances.

Background art

One essential value of electronic spreadsheets is to organize data into columns and rows, while automating tedious calculations. A typical, common, and valuable example of such a set of data organized into columns and rows is a range of cells. Even if a range of cells receives a formal and strict definition within electronic spreadsheet environments, it is flexible enough so that information can be included in either a single range of cells or in a set of several ranges of cells. Ranges of cells therefore are quite useful objects. A range of cell can be defined and processed as a whole entity. For example it can be copied from one place to another place within the spreadsheet or from one spreadsheet file to another spreadsheet file. Ranges of cells are widely used in applications developed in the field of electronic spreadsheets. Most often, the ranges of cells are arranged according to some kind of structure, thus becoming structured ranges of cells. The contents of each cell is defined within an element, where an element is defined as a row of a structured range of cells, and then the same kind of element is repeated a certain number of times, to store/process a variable number of information pieces. Most of the time, several instances of similar structured ranges of cells are used. In the current context where no other tool is really available, instances of such similar structured ranges of cells are frequently created through cut/copy and paste operations. In order to keep a high level of intellectual control over growing quantities of information, human being needs to organize or structure this information. The hierarchical model is often used, because allowing nested structures. A typical and well known example of such a hierarchical structure is the directory tree of computer Operating Systems, such as DOS (Disk Operating System) or Microsoft Windows. The root directory may contain files and/or a number of directories, which may themselves contain files and/or a number of directories, which may themselves contain files and/or a number of directories, etc. Recursivity help structure the information and maintain intellectual control over it. This need for recursivity applies as well, in spreadsheet environment to structured ranges of cells. When several instances of structured ranges of cells are defined and used in an electronic spreadsheet file, they are often themselves structured according to a specific superstructure arrangement or "array of structured ranges of cells" which can be duplicated between different electronic spreadsheet files or even within a single electronic spreadsheet file. Within such an array of structured ranges of cells, it is common to find several structured ranges of cells which follow the same intermediate superstructure, and also some other structured ranges of cells following other intermediate superstructures. The array of structured ranges of cells may then be viewed as a set of aggregated intermediate superstructures of structured ranges of cells. In the current context of conventional electronic spreadsheets, instances of such arrays of structured ranges of cells are frequently created through cut/copy and paste operations.

Creating a new instance of a structured range of cells is complex and lengthy, particularly because a conventional range of cells shows strong limitations :

- (i) structure information (such as number of columns, number of rows), format information (such as font style, color or border), and contents information (such as formulas or raw - or informative - data) are mixed,
 - (ii) the size of the range of cell is fixed at a given instant.
- Therefore, when a spreadsheet user wants to create another range of cells with an identical structure, he/she needs to perform successively several operations. He/she needs to :
1. copy-paste an existing structured range of cells,

2. distinguish between areas containing raw - or informative - data and areas containing generic content such as formulas,
3. empty the copied structured range of cells of the copied raw data while trying to keep the structure, format and generic contents,
- 5 4. adjust the size of the structured copied range of cells to his new needs.
5. eventually, fill the raw data area with default values, in order to ease subsequent data entry.

Furthermore, before copying and pasting a structured range of cells, the user must prepare the place for the copied structured range of cells, with the risk of overwriting, and therefore
 10 losing the preexisting information at the destination location. This chain of operations rapidly becomes tedious, lengthy and prone to error, especially when manipulated structured ranges of cells increase in size and complexity.

When recursivity is involved, creating a new instance of an array of structured ranges of cells is even more complex and lengthy, particularly because an array of structured
 15 range of cells involves a twofold level of structure:

- At the lower level a set of multiple, and even different, instances of structured ranges of cells must be created. As previously mentioned, this operation is itself complex, lengthy and prone to error due to the limitations of conventional ranges of cells.
- At the higher level, the creation of an instance of an array of structured range of cells
 20 would require that the spreadsheet user carry on several operations:
 1. Identify an existing instance of an array of structured ranges of cells, used as a reference for creating the new instance.
 2. Prepare the place, at the destination location, to hold the new instance, at the risk of possibly overwriting, and then losing, any pre-existing information.
 - 25 3. Copy-Paste the reference instance of the array of structured range of cells onto the destination location.
 4. Adjust the structure of the newly created instance of an array of structured ranges of cells to his/her new needs, by either deleting or introducing within the array one or several intermediate superstructures of instances of structured ranges of cells.
 - 30 5. Clean the content of each instance of structured ranges of cells comprised within the array.
 6. Eventually fill each instance of structured ranges of cells with the relevant default values.

US Patent 5,033,009 entitled "System for generating worksheet files for electronic
 35 spreadsheets" Steven J. Dubnoff, March 3rd, 1989, is an interesting document of prior art. This invention develops the concepts of pattern data and variable data that may be integrated to generate a worksheet file through a worksheet file generator. However, this invention shows many limitations preventing it from solving the set of issues presented here above and, in particular :

- 40 • It aims at producing a new output spreadsheet from a set of two input files, while there is a need, within a user application environment, to create and manipulate new entities within an existing electronic spreadsheet file, that the user is familiar with.
- It contains no mechanism allowing the direct update of the output spreadsheet, other than the regular spreadsheet tool.
- 45 • It contains no capability to manipulate within the same spreadsheet file, a variable number of different structures and a variable number of instances of each of those structure. The granularity is limited to the spreadsheet file, while the required granularity is that of a structured range of cells.
- The so called "file format specification" really mixes structure information (such as
 50 number and relative position of columns and rows), presentation information (such as font, color, background, etc.), contents information (such as formulas, etc.).

Summary of the invention

As defined in independent claims, the present invention is directed to a method, system and program, in a multidimensional electronic data table comprising a plurality of data, preferably a multidimensional electronic spreadsheet comprising a plurality of cells, for
 5 creating one or plurality of recursive scalable template instances; a recursive scalable template instance comprising a variable number of contiguous recursive element instances ordered and aligned along a first data table dimension and structured according to a recursive scalable template; a recursive element instance being defined as comprising one
 10 or a plurality of scalable template instances; a scalable template instance comprising a variable number of elements structured according to a scalable template; an element being defined as a range of data; a range of data comprising one or a plurality of data; a recursive scalable template comprising a recursive element comprising one or a plurality of scalable templates. The method comprises for each recursive scalable template instance to create, the steps of:

- 15 • Selecting a recursive scalable template;
- Defining a location for creating a recursive scalable template instance;
- Creating at the defined location one or a plurality of contiguous recursive element instances ordered and aligned along a first data table dimension; each recursive element instance having a variable size along said first data table dimension and a same
 20 size along a second data table dimension;
- Structuring each recursive element instance according to the recursive element defined for the recursive scalable template;
- Aligning each scalable template instance of each recursive element instance along said first data table dimension;
- 25 • Aligning within each recursive element instance, each scalable template instance along said second data table dimension.

Further embodiments of the invention are provided in the appended dependent claims.

Acronyms

The following acronyms will be used for more conciseness:

- 30 • **EF** stands for Element Format
- **EP** stands for Element Profile
- **MEF** stands for Meta-element Format
- **MEP** stands for Meta-element Profile
- **RE** stands for Recursive Element
- 35 • **RME** stands for Recursive Meta-Element
- **RST** stands for Recursive Scalable Template
- **RSTI** stands for Recursive Scalable Template Instance
- **ST** stands for Scalable Template
- **STI** stands for Scalable Template Interface

Brief description of the drawings

- 40 • Figure **1A** is a schematic view of a computer system in which the present invention may be embodied.
- Figure **1B** is a schematic view of a software system including an operating system, an application software, and a user interface for carrying out the present invention.
- 45 • Figure **2** shows a preferred spreadsheet user interface, according to the preferred embodiment of the present invention, for managing RST's.
- Figure **3** shows a preferred spreadsheet user interface, according to the preferred embodiment of the present invention, for editing EF's.
- Figure **4** shows a preferred spreadsheet user interface, according to the preferred embodiment of the present invention, for editing EP's.
- 50 • Figure **5** shows a preferred spreadsheet user interface, according to the preferred embodiment of the present invention, for editing ST's.
- Figure **6** shows a preferred spreadsheet user interface, according to the preferred embodiment of the present invention, for editing RST's.

- Figures **7A**, **7B**, **7C**, **7D**, and **7E** respectively illustrate the structure of the EF Table (EFT), of the EP Table (EPT), of the ST Table (STT), of a ST Descriptor Table (STDT), of the STI Table (STIT), according to the preferred embodiment of the present invention.
- 5 • Figure **7F** gives a graphical illustration of the relationships established between the tables EFT, EPT, STT, STDT, STIT, RET, RSTT, RSTDT, RSTIT and RSTIDT according to the preferred embodiment of the present invention.
- Figure **8** is a flow chart illustrating a preferred method for managing RST objects according to a preferred embodiment of the present invention.
- 10 • Figure **9** is a flow chart illustrating a preferred method for editing EF's and MEF's according to a preferred embodiment of the present invention.
- Figure **10** is a flow chart illustrating a preferred method for editing EP's and MEP's according to a preferred embodiment of the present invention.
- Figures **11** is a flow chart illustrating a preferred method for editing a ST according to a preferred embodiment of the present invention.
- 15 • Figures **12** is a flow chart illustrating a preferred method for editing a RST according to a preferred embodiment of the present invention.
- Figure **13A** shows a preferred spreadsheet user interface, according to the preferred embodiment of the present invention, for creating STI's.
- 20 • Figure **13B** illustrates the ST instantiation, according to a preferred embodiment of the present invention.
- Figure **14A** is a flow chart illustrating a preferred method for instantiating a ST according to a preferred embodiment of the present invention.
- Figure **14B** is a flow chart illustrating a preferred method for creating a STI according to a preferred embodiment of the present invention.
- 25 • Figure **15A** illustrates the logical structure of a RSTI, according to the preferred embodiment of the present invention.
- Figure **15B** illustrates the logical structure of a RST, according to the preferred embodiment of the present invention.
- 30 • Figures **16A** and **16B** constitute a flow chart illustrating a preferred method for creating RSTI's according to a preferred embodiment of the present invention.
- Figures **17A**, **17B**, **17C**, **17D**, **17E** and **17F** respectively illustrate the structure of the RE Table (RET), of the RST Table (RSTT), of the RST Manager Table (RSTMT), of a RST Descriptor Table (RSTDT), of the RSTI Table (RSTIT), and of a RSTI Descriptor Table (RSTIDT).
- 35 • Figure **18A** shows a preferred spreadsheet user interface, according to the preferred embodiment of the present invention, for creating RSTI's.
- Figure **18B** shows a preferred spreadsheet user interface, according to the preferred embodiment of the present invention, for editing RE's.
- 40 • Figure **18C** is a flow chart illustrating a preferred method for editing RE's in RST's according to a preferred embodiment of the present invention.
- Figure **19A** is a flow chart illustrating a preferred method for computing the number of rows comprised in a STI according to a preferred embodiment of the present invention.
- 45 • Figure **19B** is a flow chart illustrating a preferred method for computing the number of columns comprised in a STI according to a preferred embodiment of the present invention.

Detailed description of the preferred embodiment

SYSTEM HARDWARE : As shown in FIG. 1A, the present invention may be embodied on a computer system **100** comprising a central processor **101**, a main memory **102**, an input/output controller **103**, a keyboard **104**, a pointing device **105** (e.g., mouse, track ball, pen device, or the like), a display device **106**, and a mass storage **107** (e.g., hard disk). Additional input/output devices, such as a printing device **108**, may be included in the system **100** as desired. As illustrated, the various components of the system **100**

communicate through a system bus 110 or similar architecture. In a preferred embodiment, the computer system 100 includes an IBM-compatible personal computer, which is available from several vendors (including International Business Machine - IBM Corporation of Armonk, N.Y.). As illustrated in FIG. 1B, a computer software system 150 is provided for directing the operation of the computer system 100. Software system 150, which is stored in system memory 102 and on disk memory 107, includes a kernel or operating system 151 and a shell or interface 153. One or more application programs, such as application software 152, may be "loaded" (i.e., transferred from storage 107 into memory 102) for execution by the system 100. The system 100 receives user commands and data through user interface 153; these inputs may then be acted upon by the system 100 in accordance with instructions from operating module 151 and/or application module 152. The interface 153, which is preferably a graphical user interface (GUI), also serves to display results, whereupon the user may supply additional inputs or terminate the session. In a preferred embodiment, operating system 151 and interface 153 are Microsoft Win95, available from Microsoft Corporation of Redmond, Wash. Application module 152, on the other hand, includes a spreadsheet notebook of the present invention as described in further detail herein below.

INTERFACE : The following descriptions will focus on the presently preferred embodiments of the present invention implementing the user interfaces described in international patent application PCT/EP 02/09483 (IBM's reference FR9 2001 0029) entitled "System and method in an electronic spreadsheet for exporting-importing the content of input cells from a scalable template instance to another" by Aureglia et al.

RECURSIVE SCALABLE TEMPLATE MANAGEMENT

A. Introduction

25 The concept of scalable templates (ST's)

Conventional electronic spreadsheets include built-in means allowing the spreadsheet users to easily organize data into columns and rows, while automating tedious calculations. This set of organized data can be included in either a single range of cells or in a set of several ranges of cells. The range of cells is a quite useful, and widely used object in an electronic spreadsheet environment. It can be defined and processed as a whole entity. According to the invention described in international patent application PCT/EP 02/09483 (IBM's reference FR9 2001 0029), systems and methods are available to allow an electronic spreadsheet user to:

- Define a structure, for a range of cells, including :
 - (i) an optional header part made of one or more meta-elements ;
 - (ii) a mandatory body part made of one or more elements ;
 - (iii) an optional footer part made of one or more meta-elements.

The structure of **each** meta-element of the header part may be defined in terms of attributes by a MEF, and in terms of contents by a MEP.

The structure of **all** elements of the body part, may be defined in terms of attributes by an EF, and in terms of contents by an EP.

The structure of **each** meta-element of the footer part may be defined in terms of attributes by a MEF, and in terms of contents by a MEP.

This structure is called a ST. In summary, the ST defines a structure by specifying the number of fields, by referring to a couple of EF and EP that defines all body elements, and, optionally, by referring to one or several couples of MEF and MEP that define each meta-element of the header part or the footer part.

- Manage ST's and underneath defined objects, known as EF's, EP's, MEF's and MEP's.
- Create, or update EF's, MEF's.
- Create, or update EP's, MEP's.
- Create, or update a ST.
- Create a STI abiding by a defined ST.
- Insert one or a plurality of elements within a STI.
- Remove one or a plurality of elements from a STI.

The above set of functions is supported by a set of tools :

- the "**RST Manager**" method, or **RSTM** method for short;
- the "**EF Editor**" method, or **EFE** method for short;
- the "**EP Editor**" method, or **EPE** method for short;
- 5 • the "**ST Editor**" method, or **STE** method for short;
- the "**ST Instanciator**" method, or **STI** method for short;

The concept of Recursive Scalable Templates (RST's)

Having introduced the concept of ST's and of STI's, the concept of RST's and RSTI's becomes easier to capture. Indeed a RST can be seen as a two level structure. The highest
 10 level is logically equivalent to the structure of a ST, as a set of structured RE and RME's which can be logically mapped to element and meta-elements. The recursive nature of a RST appears at the lower structural level, because the RE and RME's are objects which themselves comprise STI's (instead of conventional spreadsheet cells, as it is the case for
 15 elements and meta-elements). In other words, a RST is a tiered structure of ST's. When a RST is instanciated, the same similarities can be articulated to describe the structure of the resulting RSTI. At a higher level, a RSTI presents a structure logically equivalent to the structure of a STI, but constituted by container ranges instead of individual cells. Within
 20 each container range, a lower level structure is present in the form of STI's. As a result a RSTI can be seen as a STI itself containing STI's in lieu of conventional cells. Such an object was therefore first introduced under the name of "an array of structured ranges of cells". Referring now to FIG 15A and 15B, a simple example of such a RST and RSTI will be used to illustrate the present application. By referring first to FIG 15B, the RST 2051
 25 named "**RST_customer**" defines the structure followed by a Network Services Provider to record all the various data corresponding to a customer receiving networking services. This RST is organized around a structure comprising:

- A header part 2052 where the customer data (such as company name, address, business, contract schedule, etc.) are recorded according to the structure of a ST named "**ST_cust_data**", where the customer contact points (such as CEO, CIO, CFO, managers, etc.) are recorded according to the structure of a ST named "**ST_contacts**",
 30 where the contracted service level agreements are recorded according to the structure of a ST named "**ST_SLA**", and where the customer support team (such as the transition manager, the delivery manager, the solution manager, etc.) is recorded according to the structure of a ST named "**ST_support_team**".
- A body part 2053 where is recorded, for each customer resource receiving services from the service provider, the information required to manage this resource (such as location, IP address, configuration file, etc.) according to the structure of a ST named "**ST_res_info**", and where is recorded the current problem log for the same resource
 35 according to the structure of a ST named "**ST_pb_log**".
- A footer part 2054 where is recorded the billing status for this customer, according to the structure of a ST named "**ST_billing**", and where are recorded the problem statistics for the customer managed resources, according to the structure of a ST named "**ST_stats**".
 40

By referring then to FIG 15B, the RSTI 2001 follows the structure of the RST 2051 "**RST_customer**". Indeed it is also organized around a structure comprising a header part 2002, a body part 2003, and a footer part 2004. The header part 2002 contains four STI's
 45 which are themselves organized according to the structure of the RST header part 2052, and which abide by the structures of the ST's "**ST_cust_data**", "**ST_contacts**", "**ST_SLA**", and "**ST_support_team**". The body part 2003 is constituted by three different records 2010, 2009, and 2008, each of them organised according to the structure of the RST body part 2053, that is comprising two STI's which abide by the structures of the ST's "**ST_res_info**",
 50 and "**ST_cpb_log**". Finally the footer part 2004 contains two STI's which are themselves organized according to the structure of the RST footer part 2054, and which abide by the structures of the ST's "**ST_billing**", and "**ST_stats**". Most often also, several instances of similar recursively structured ranges of cells are used. Within the logic of our example, as described above and illustrated in FIG 15A, a similar recursively structured range of cells is

created for each customer in a new sheet. In the current context of electronic spreadsheet environment, where no other tool is really available, instances of such similar recursively structured ranges of cells are frequently created through cut/copy and paste operations. We have already described the limitations of conventional tools for creating STI's. The creation of a RSTI is even more difficult and prone to errors due to the twofold structure of a RSTI. Indeed the additional difficulty appearing when manipulating such recursive objects is to determine the structural level at which should occur a given operation (such as copy-pasting a recursive object, identifying areas containing row data or structure specific data within a recursive object, adjusting the size of a recursive object, emptying some fields within a recursive object, correcting any error resulting from the previous operations applied to a recursive object, and filling default values in some fields within a recursive object). Furthermore, before the copy-paste operation, on the recursively structured range of cells, takes place, the user must prepare the place for the copied recursively structured range of cells, at the destination location, with the risk, if this is not done, of overwriting, and therefore loosing the preexisting information at this location. The chain of operations described above rapidly becomes tedious, lengthy and prone to error, mainly because the size and complexity of recursively structured ranges of cells are quickly reaching the limits of human beings, when using conventional tools. In a preferred embodiment of the present invention, a user-friendly solution to these problems is proposed by allowing the electronic spreadsheet user to:

- Define a superstructure, for a range of cells, including :
 - (i) an optional header part made of one or more RME's ;
 - (ii) a mandatory body part made of one RE's ;
 - (iii) an optional footer part made of one or more RME's.

The structure of **each** RME of the header part is defined as an ordered collection of superstructure fields, each corresponding to a ST. The structure of **all** RE's of the body part, is defined as an ordered collection of superstructure fields, each corresponding to a ST. The structure of **each** RME of the footer part is defined as an ordered collection of superstructure fields, each corresponding to a ST. This superstructure is called a RST.

In summary, the RST defines a superstructure by specifying the number of fields, by referring to a RE that defines the body part, and, optionally, by referring to one or several RME's that define the header part and/or the footer part.

- Manage RST's and underneath defined objects, known as RE's and RME's.
- Create, or update RE's.
- Create, or update RME's.
- Create, or update a RST.
- Create a RSTI abiding by a defined RST.

The above set of functions is supported by a set of tools :

- the "**RST Manager**" method, or **RSTM** method for short;
- the "**RE Editor**" method, or **REE** method for short;
- the "**RST Editor**" method, or **RSTE** method for short;
- the "**RST Instanciator**" method, or **RSTI** method for short.

This set of functions is defined in much further details, in the following sections. In our example, a RST is developed to define the generic structure of the "NSP Customer Repository" and thus to facilitate the creation of several instances of said "NSP Customer Repository". Now referring to FIG 15B, the RST defining the structure of "NSP Customer Repository" :

- (i) Specifies the number of superstructure fields, 2 (two) in our exemple.
- (ii) Defines the header part of "NSP Customer Repository", through the following steps :
 - Defining the structure of a first ST "**ST_cust_data**", and of a second ST "**ST_contacts**".
 - Defining the structure of a first RME comprising the two previous ST's.

- Defining the structure of a third ST "ST_SLA", and of a fourth ST "ST_support_team".
- Defining the structure of a second RME 2057 comprising the two previous ST's.
- 5 (iii) Defines the body part 2053 of "NSP Customer Repository", through the following steps :
 - Defining the structure of a fifth ST "ST_res_info", and of a sixth ST "ST_pb_log".
 - Defining the structure of a RE 2056 comprising the two previous ST's.
- (iv) Defines the footer part 2054 of "NSP Customer Repository", through the following steps :
 - 10 • Defining the structure of a first ST "ST_billing", and of a second ST "ST_stats".
 - Defining the structure of a RME 2055 comprising the two previous ST's.

From the above RST 2051, one or several RSTI's, such as the one illustrated in FIG 15A, can be created, at very limited cost to the user and thus avoiding the many risks for error.

B. Concepts and Vocabulary

- 15 The purpose of this section is to formalize both some concepts (with associated objects) and some vocabulary defined within the scope of the present invention. In the following descriptions, it is assumed that spreadsheets are in two dimensions (2D), so that tables and structures can be described in a 2D environment. Moreover it is assumed that tables are organized vertically, so that the table headings are on the top of the table instead of being
- 20 on its left. This allows to significantly clarify the description of the various original concepts, objects, and methods which are part of the present invention, but this does not limit in any way the scope of the invention. In other words, the underneath description can be generalized to environment with either 2D tables organized horizontally or with 3D tables, without departing from the spirit of the present invention.

25 B1. Preliminary Definitions

Structured Range of Cells : a structured range of cells is a range of cells that abides by some kind of structure organizing the data into rows and columns. Columns define fields aimed at containing the same kind of information on each row. Rows define records (or elements).

Table : the word table can be used to designate a structured range of cells.

- 30 **Field** : a field is a labeled column in a database or table that contains the same kind of information for each record (or element). For example, a customer table may contain fields labeled Name, Address and Tel #.

By extension, in a given record (or element), a given field refers to the cell located at the intersection of the record (or element) and the given field (labeled column).

- 35 The above definitions are for a 2D environment where columns define fields and rows define records. They can be transposed in a 2D environment where rows define fields and columns define record. They can also be transposed in a 3D environment, where, for example, sheets define records.

- IN/OUT Cell**: a cell is specified as "IN" cell when assumed to be used for recording user provided information. A cell is specified as "OUT" cell when assumed to be used for
- 40 producing information (generally obtained through formulas whose arguments refer directly or indirectly to "IN" cells).

B2. Object Definitions

The following objects are defined to help the understanding of the invention.

- Element Format** : an EF is a spreadsheet object defining the structure of an element within
- 45 a 2 dimensions or a 3 dimensions range of cells, in terms of format attribute :
- Background attributes (color, pattern, etc...),
 - Alignment attributes (horizontal, vertical, text wrapping, alignment across columns, etc...)
 - Font attributes (size, color, etc...)
 - Line attributes (type, color, etc...)
 - 50 • Protection of the field
 - and any other conventional format attribute.

Meta-Element Format : a MEF is a spreadsheet object defining the structure of a meta-element within a 2 dimensions or a 3 dimensions range of cells, in terms of format attribute :

- Background attributes (color, pattern, etc...),
 - 5 • Alignment attributes (horizontal, vertical, text wrapping, cell merging, etc...)
 - Font attributes (size, color, etc...)
 - Line attributes (type, color, etc...)
 - Protection of the field
 - and any other conventional format attribute.
- 10 **Element Profile** : an EP is a spreadsheet object defining the structure of an element within a 2 dimensions or a 3 dimensions range of cells, in terms of content and destination :
- formulas for fields to be computed from data comprised in other fields of the same element, or in other fields of another element or meta-element of the same STI, or even in other fields outside the STI.
 - 15 • field default values to be assigned at element creation time.
 - destination of the cells (data entry for "IN" cells or data produced for "OUT" cells).

Meta-Element Profile : a MEP is a spreadsheet object defining the structure of a meta-element within a 2 dimensions or a 3 dimensions range, in terms of content and destination :

- 20 • formulas for cells to be computed from data comprised in other cells of the same element, or in other cells of another element or meta-element of the same STI, or even in other cells outside the STI.
 - cell default values to be assigned at meta-element creation time.
 - destination of the cells (data entry for "IN" cells or data produced for "OUT" cells)
- 25 **Scalable Template** (also referred to as "Template" or "ST") : A ST is a spreadsheet object defining the structure of a 2 dimensions or a 3 dimensions range of cells, in terms of {element + meta-elements} layout. The word "scalable" refers to the capability of the ST of defining a given structure for variable size (e.g. ranging from a minimum value to a maximum value) range of cells. The ST defines a structure by :
- 30 • specifying the number of fields,
 - by referring to a couple of EF and/or EP that defines each body element, and,
 - optionally, by referring to one or several couples of MEF's and/or MEP's.

In a 2 dimensions environment, such MEF's / MEP's are either located above the EF / EP, constituting the ST "header" part, or located below the EF / EP, constituting the ST "footer" part. Either the ST "header" part or the ST "footer" part, or both of them may be empty.

- 35 When the element and meta-element references are only constituted by EP's and MEP's, then the ST only carries contents information and can thus be named **Scalable Profiled Template**. When the element and meta-element references are only constituted by EF's and MEF's, then the ST only carries format information and can thus be named **Scalable Formatted Template**. When the element and meta-element references are constituted by any combination of both EP's and EF's, then the ST carries both profile and format information and can thus be named **Scalable Profiled & Formatted Template**.

Scalable Template Instance (also referred to as "Instance" or "scalable instance" or "STI")

- 45 : A STI is a spreadsheet object abiding by the structure of a defined ST : a scalable formatted template, or a scalable profiled template, or a scalable profiled & formatted template. An STI may be viewed as a heir object of a ST. It contains a variable number of elements (at least one) containing information, in each field, corresponding to the parent structure, and constituting the "body" part, plus optionally one or several meta-elements, as defined by the ST, and constituting the "header" part and the "footer" part of the STI.

- 50 **Element** : An element is a spreadsheet object belonging to a STI, and made of elementary fields abiding either by an EF, or by an EP, or by a couple (EF, EP) found in the parent structure (respectively scalable formatted template, or scalable profiled template, or scalable profiled & formatted template). Without loosing any generality, it is assumed that an element

always abides by a couple (EF, EP), where either the EF or the EP can be reduced to a void object.

Meta-Element : A meta-element is a spreadsheet object belonging to an STI, and made of elementary cells abiding either by a MEF, or by a MEP, or by a couple (MEF, MEP). Without losing any generality, it is assumed that a meta-element always abides by a couple (MEF, MEP), where either the MEF or the MEP can be reduced to a void object.

Recursive Element : A RE is a spreadsheet object belonging to a RST, constituting the body part of the RST, and made of elementary fields used to record the names of ST's. A RE has a structure similar to the structure of an element, but instead of being instantiated as a range of cells, is instantiated as a range of STI's.

Example : The RE of the RST 2051, as illustrated in FIG 15B, corresponds to the structure 2056, constituting the body part 2053 of this RST, and made of two fields which respectively contain the name of the ST's "ST_res_info" and "ST_pb_log".

Recursive Meta-element : A RME is a spreadsheet object belonging to a RST, belonging to the header and/or footer part of the RST, and made of elementary fields used to record the names of ST's. A RME has a structure similar to the structure of a meta-element, but instead of being instantiated as a range of cells, is instantiated as a range of STI's.

Example : A RME of the RST 2051, as illustrated in FIG 15B, corresponds to the structure 2058, belonging to the header part 2052 of this RST, and made of two fields which respectively contain the name of the ST's "ST_cust_data" and "ST_contacts".

Recursive Scalable Template (also referred to as "Recursive Template" or "RST"): A RST is a spreadsheet object defining the superstructure of a 2 dimensions or a 3 dimensions range of cells, in terms of {RE + RME's} layout. The word "scalable" refers to the capability of the RST of defining a given superstructure for variable size (e.g. ranging from a minimum value to a maximum value) range of cells. The RST defines a superstructure by :

- specifying the number of fields,
- by referring to a RE that defines the body part of the RST, and,
- optionally, by referring to one or several RME's.

In a 2 dimensions environment, such RME's are either located above the RE, constituting the RST "header" part, or located below the RE, constituting the RST "footer" part. Either the RST "header" part or the RST "footer" part, or both of them may be empty.

Example : A RST 2051 is illustrated in FIG 15B. It is constituted by a header part 2052, a body part 2053 and a footer part 2054. The header part comprises two RME's 2058 and 2057, both with two fields, and which respectively contain the name of the ST's "ST_cust_data", "ST_contacts" and "ST_SLA", "ST_support_team". The body part comprises one RE 2056 with two fields which respectively contains the name of the ST's "ST_res_info", "ST_pb_log". The footer part comprises one RME 2055 with two fields which respectively contains the name of the ST's "ST_billing", "ST_stats".

Recursive Scalable Template Instance (also referred to as "Recursive Instance" or "RSTI") : A RSTI is a spreadsheet object abiding by the structure of a defined RST. A RSTI may be viewed as a heir object of a RST. It contains a variable number of container rows (at least one) containing one or a plurality of STI's, corresponding to the parent RE structure, and constituting the "body" part, plus optionally one or several other container rows containing one or a plurality of STI's, corresponding to the parent RME's structure, and constituting the "header" part and the "footer" part of the RSTI.

Example : A RSTI 2001 is illustrated in FIG 15A. This RSTI abides by the RST 2051 as illustrated in FIG 15B. It is constituted by a header part 2002, a body part 2003 and a footer part 2004. The header part comprises two container rows 2012 and 2011. The body part comprises three container rows 2010, 2009 and 2008. The footer part comprises one container row 2007. Each container row contains two container ranges, such as the container range 2014 which can be seen as the intersection of the top container row 2012 and of the right container column 2005. Each container range contains a STI which abides

by the structure of the ST defined as part of the RE or RME member of the RST 2051. For instance the STI 2034 comprised within the container range intersection of the container row 2010 and of the container column 2005 abides by the structure of the ST named "ST_pb_log", as defined in the RME 2056 of the RST 2051, and is itself constituted by a header part 2015, a body part 2016 and a footer part 2017.

Container rows : a container row is a spreadsheet object belonging to a RSTI, and corresponding to the range of cells containing the STI's which are structured according to the definition of a RE or of a RME part of the RST that the RSTI abides by. The number of rows of a container row is equal to the number of rows of the highest STI it contains. A container row can also be referred to as a recursive element instance. A container row can be seen within a RSTI as equivalent to an element within a STI.

Example : The container row 2012 is illustrated in FIG 15A, and corresponds to the range of cells comprising the STI's 2032 and 2013 which are defined within the RSTI 2001. The number of rows of this container row is equal to the number of rows of the STI 2032 which is higher than the STI 2013.

Container columns : a container column is a spreadsheet object belonging to a RSTI, and corresponding to the range of cells containing the STI's which occupy the same superstructure position within the container rows of the RSTI. The number of columns of a container column is equal to the number of columns of the widest STI it contains.

Example : The container column 2006 is illustrated in FIG 15A, and corresponds to the range of cells comprising the STI's occupying the leftmost position within the RSTI 2001. The number of columns of this container column is equal to the number of columns of the STI 2030 which is the widest STI on the left side of the RSTI 2001.

Container ranges : a container range is a spreadsheet object belonging to a RSTI, and corresponding to the intersection of a container row and of a container column. Each container range contains a single STI which occupies the top and leftmost corner. A container range within a RSTI can be seen as equivalent to a single cell within a STI.

Example : The container range 2014 is illustrated in FIG 15A, and corresponds to the intersection of the container row 2012 and of the container column 2005, both belonging to the RSTI 2001. This container range 2014 contains the STI 2013.

B3. Notations

The following notation : $\prod_{i \in \mathcal{S}} a_i$ corresponds to the multiplication of the terms a_i , the index i belonging to the set \mathcal{S} . The following notation : $\text{LCM}(\{a_i\}_{i \in \mathcal{S}})$ corresponds to the Least Common Multiplier of the terms a_i , the index i belonging to the set \mathcal{S} . If \mathcal{S} is constituted by a single element a , then $\text{LCM}(\{a_i\}_{i \in \mathcal{S}})$ is equal to a . The following notation : $a \bmod b$ corresponds to the remainder of the division of a by b .

C. Tables used for managing RST objects

As introduced in the previous section, the preferred embodiment of the present invention relies on different types of objects for managing RST's. These objects are recorded in different repositories, so that they can be accessed and updated by the different methods which are part of the preferred embodiment of the present invention. Such repositories are referred to as tables:

- the **EF Table** or **EFT** for short,
- the **EP Table** or **EPT** for short,
- the **ST Table** or **STT** for short,
- The **ST Descriptor Table** or **STDT** for short.
- The **ST Instanciator Table** or **STIT** for short.
- The **RE Table** or **RET** for short.
- The **RST Table** or **RSTT** for short.
- The **RST Manager Table** or **RSTMT** for short.
- The **RST Descriptor Table** or **RSTDT** for short.
- The **RSTI Table** or **RSTIT** for short.
- The **RSTI Descriptor Table** or **RSTIDT** for short.

The **EFT**, **EPT**, **STT**, **STDT**, **STIT**, **RET**, **RSTT**, **RSTDT**, **RSTIT**, and **RSTIDT** tables are saved as part of the spreadsheet disk file on the mass storage **107**, whereas the **RSTMT** table is temporarily saved on the main memory **102**.

C1. EF Table

- 5 Referring now to FIG. 7A, the **EFT** Table **700** corresponds to a logical simple structure made of several records **701**, each of them corresponding to an EF or to a MEF, according to the present invention. Each record includes six fields:
- The "Name" **702** field is used for recording a character string which uniquely identifies the EF or the MEF described by the current record **701**.
 - 10 ◦ The "Last Change Date" **703** field is used for recording the date of the last update of the EF or the MEF described by the current record **701**.
 - The "Description Ptr" **704** field is a reference pointing to the memory location where is recorded an illustrative range of cells depicting the EF or MEF described by the current record **701**. This memory location can either be on the Mass storage **107**, or on the main memory **102**, or on other conventional memory repository means, without departing from the spirit of the present invention.
 - 15 ◦ The "Row #" **705** field is used for recording the number of rows present in the EF or in the MEF described by the current record **701**. This field is relevant for 3D ST's where element or MEF's correspond to 2D structures. In the preferred embodiment of the present invention where 2D ST's are assumed, this field is always filled with the value 1.
 - 20 ◦ The "Column #" **706** field is used for recording the number of columns present in the EF or in the MEF described by the current record **701**.
 - The "Type" **707** field is used for recording different attributes associated to the EF or to the MEF described by the current record **701**: this is the "META" attribute **708** specifying if the current record **701** describes an EF or a MEF (with respective values "NO" and "YES"), and the "REFERENCED" attribute **709** specifying through dedicated subfields (**709a**, **709b**, **709c**, **709d** and **709e**) the relationships with other objects. These subfields are described as part of the description of the "REFERENCED" attribute **2240**. Conventional techniques can be used for encoding these different attributes in this "Type" field, such as executing bit-wise XOR operations with predefined bit patterns, but any other conventional means could be used instead without departing from the spirit of the invention.
 - 25
 - 30

C2. EP Table

- 35 Referring now to FIG. 7B, the **EPT** Table **710** corresponds to a logical simple structure made of several records **711**, each of them corresponding to an EP or to a MEP, according to the present invention. Each record includes six fields:
- The "Name" **712** field is used for recording a character string which uniquely identifies the EP or the MEP described by the current record **711**.
 - The "Last Change Date" **713** field is used for recording the date of the last update of the EP or the MEP described by the current record **711**.
 - 40 ◦ The "Description Ptr" **714** field is a reference pointing to the memory location where an illustrative range of cells depicting the EP or MEP described by the current record **711** is recorded. This memory location can either be on the Mass storage **107**, or on the main memory **102**, or on other conventional memory repository means, without departing from the spirit of the present invention.
 - 45 ◦ The "Row #" **715** field is used for recording the number of rows present in the EP or in the MEP described by the current record **711**. This field is relevant for 3D ST's where element or MEP's correspond to 2D structures. In the preferred embodiment of the present invention where 2D ST's are assumed, this field is always filled with the value 1.
 - 50 ◦ The "Column #" **716** field is used for recording the number of columns present in the EP or in the MEP described by the current record **711**.
 - The "Type" **717** field is used for recording different attributes associated to the EP or to the MEP described by the current record **711**: this is the "META" attribute **718** specifying if

the current record **701** describes an EP or a MEP (with respective values "NO" and "YES"), and the "REFERENCED" attribute **719** specifying through dedicated subfields (**719a**, **719b**, **719c**, **719d** and **719e**) the relationships with other objects. These subfields are described as part of the description of the "REFERENCED" attribute **2240**. Conventional techniques can be used for encoding these different attributes in this "Type" field, such as executing bit-wise XOR operations with predefined bit patterns, but any other conventional means could be used instead without departing from the spirit of the invention.

C3. ST Table

Referring now to FIG. 7C, the **STT** Table **720** corresponds to a logical simple structure made of several records **721**, each of them corresponding to a ST, according to the present invention. Each record includes six fields:

- The "Name" **722** field is used for recording a character string which uniquely identifies the ST described by the current record **721**.
- The "Last Change Date" **723** field is used for recording the date of the last update of the ST described by the current record **721**.
- The "Description Ptr" **724** field is a reference pointing to the memory location where a description of the ST described by the current record **721** is recorded. This memory location can either be on the mass storage **107**, or on the main memory **102**, or on other conventional memory repository means, without departing from the spirit of the present invention. This description is structured according to the **STDT** table **760** illustrated in FIG 7D, that is as an ordered list of couples of names, each couple being made by the name of an element or MEP and by the name of an element or MEP.
- The "Min Element #" **725** field is used to record the minimum number of elements found in each STI abiding by the ST described by the current record **721**.
- The "Max Element #" **726** field is used to record the maximum number of elements found in each STI abiding by the ST described by the current record **721**.
- The "Type" **727** field is used for recording different attributes associated to the ST described by the current record **721**: this is the "META" attribute **728** which always take the value "NO", and the "REFERENCED" attribute **729** specifying through dedicated subfields (**729a**, **729b**, **729c**, **729d** and **729e**) the relationships with other objects. These subfields are described as part of the description of the "REFERENCED" attribute **2240**. Conventional techniques can be used for encoding these different attributes in this "Type" field, such as executing bit-wise XOR operations with predefined bit patterns, but any other conventional means could be used instead without departing from the spirit of the invention.

C4. ST Descriptor Table

Referring now to FIG. 7D, the **STDT** Table **760** corresponds to a logical simple structure made of several couples of element or MEP **765** and of element or MEP **764**. This structure is organized into three sub-sets:

- The optional ST "Header" part **767**, made of a variable number (possibly null) of couples like the top couple **761**. Each of these couples is constituted by a MEP (column **765**) and by a MEP (column **764**).
- The mandatory "Body" part **762** made of a single couple constituted by an EF (column **765**) and by an EP (column **764**).
- The optional ST "Footer" part **766**, made of a variable number (possibly null) of couples like the bottom couple **763**. Each of these couples is constituted by a MEP (column **765**) and by a MEP (column **764**).

C5. ST Instanciator Table

Referring now to FIG. 7E, the **STIT** Table **750** corresponds to a logical simple structure made of several records **751**, each of them corresponding to a STI, according to the preferred embodiment of the present invention. Each record includes six fields:

- The "Address" **752** field is used for locating the STI described by the current record **751**: its value corresponds to the conventional character string used to record the address of any range of cells.
- The "ST" **753** field is used for recording the name of the ST abided by the STI described by the current record **751**.
- The "Element #" **754** field is used for recording the number of elements within the STI described by the current record **751**.
- The "Critical" **755** field is used for recording if the STI described by the current record **751** is considered as critical. Its content can take the values "YES" or "NO".
- The "Header Size" **756** field is used for recording the number of meta-elements constituting the Header part of the STI described by the current record **751**.
- The "Footer Size" **757** field is used for recording the number of meta-elements constituting the Footer part of the STI described by the current record **751**.

C6. RE Table

- Referring now to FIG. 17A, the **RET** Table **2210** corresponds to a logical simple structure made of several records **2211**, each of them corresponding to a RE or to a RME, according to the present invention. Each record includes six fields:
- The "Name" **2212** field is used for recording a character string which uniquely identifies the RE or the RME described by the current record **2211**.
 - The "Last Change Date" **2213** field is used for recording the date of the last update of the RE or of the RME described by the current record **2211**.
 - The "Description Ptr" **2214** field is a reference pointing to the memory location where is recorded an illustrative range of cells depicting the RE or the RME described by the current record **2211**. This memory location can either be on the Mass storage **107**, or on the main memory **102**, or on other conventional memory repository means, without departing from the spirit of the present invention.
 - The "Row #" **2215** field is used for recording the number of rows present in the RE or in the RME described by the current record **2211**. This field is relevant for 3D RST's where RE's or RME's correspond to 2D structures. In the preferred embodiment of the present invention where 2D RST's are assumed, this field is always filled with the value 1.
 - The "Column #" **2216** field is used for recording the number of columns present in the RE or in the RME described by the current record **2211**.
 - The "Type" **2217** field is used for recording different attributes associated to the RE or to the RME described by the current record **2211**: this is the "META" attribute **2218** specifying if the current record **2211** describes a RE or a RME (with respective values "No" and "Yes"), and the "REFERENCED" attribute **2219** specifying through dedicated subfields (**2219a**, **2219b**, **2219c**, **2219d** and **2219e**) the relationships with other objects. These subfields are described as part of the description of the "REFERENCED" attribute **2240**. Conventional techniques can be used for encoding these different attributes in this "Type" field, such as executing bit-wise XOR operations with predefined bit patterns, but any other conventional means could be used instead without departing from the spirit of the invention.

C7. RST Table

- Referring now to FIG. 17B, the **RSTT** Table **2220** corresponds to a logical simple structure made of several records **2221**, each of them corresponding to a RST, according to the present invention. Each record includes six fields:
- The "Name" **2222** field is used for recording a character string which uniquely identifies the RST described by the current record **2221**.
 - The "Last Change Date" **2223** field is used for recording the date of the last update of the RST described by the current record **2221**.
 - The "Description Ptr" **2224** field is a reference pointing to the memory location where a description of the RST described by the current record **2221** is recorded. This memory location can either be on the mass storage **107**, or on the main memory **102**, or on other

conventional memory repository means, without departing from the spirit of the present invention. This description is structured according to the RSTDT table 2250 illustrated in FIG 17D, that is as an ordered list of RME or RE names.

- The "*Min Element #*" 2225 field is used for recording the minimum number of RE's found in every RSTI abiding by the RST described by the current record 2221.
- The "*Max Element #*" 2226 field is used for recording the maximum number of RE's found in every RSTI abiding by the RST described by the current record 2221.
- The "*Type*" 2227 field is used for recording different attributes associated to the RST described by the current record 2221: this is the "META" attribute 2228 which always take the value "NO", and the "REFERENCED" attribute 2229 specifying through dedicated subfields (2229a, 2229b, 2229c, 2229d and 2229e) the relationships with other objects. These subfields are described as part of the description of the "REFERENCED" attribute 2240. Conventional techniques can be used for encoding these different attributes in this "Type" field, such as executing bit-wise XOR operations with predefined bit patterns, but any other conventional means could be used instead without departing from the spirit of the invention.

C8. RST Manager Table .

Referring now to FIG. 17C, the *RSTMT* Table 2230 corresponds to a logical simple structure made of several records 2231, each of them corresponding to an object managed by the RST manager, according to the preferred embodiment of the present invention. Each record includes seven fields:

- The "*Name*" 2232 field is used for recording a character string which uniquely identifies the object described by the current record 2231.
- The "*Last Change Date*" 2233 field is used for recording the date of the last update of the object described by the current record 2231.
- The "*Description Ptr*" 2234 field is a reference pointing to the memory location where is recorded a description of the object described by the current record 2231. This memory location can either be on the Mass storage 107, or on the main memory 102, or on other conventional memory repository means, without departing from the spirit of the present invention.
- The "*Info Field 1*" 2235 field is used for recording a first piece of information associated to the object described by the current record 2231.
- The "*Info Field 2*" 2236 field is used for recording a second piece of information associated to the object described by the current record 2231.
- The "*Type*" 2237 field is used for recording different attributes associated to the object described by the current record 2231, such as:
 - the attribute "META" 2239 previously described for the similar "Type" fields 707, 717, 727, 777, 2217, and 2227, and also two other attributes:
 - the attribute "REFERENCED" 2240 which is constituted by 5 (five) subfields, according to the FIG 17C illustrating an example of RSTMT table 2230:
 - The "OWN REFERENCE" (or OR for short) subfield 2240a. This subfield is a unique prime number assigned when the object described by the record 2231 is created. This prime number is released only when the object described by the record 2231 is deleted.
 - The "FILIAION REFERENCE" (or FR for short) subfield 2240b. This subfield is evaluated according to the following formula, where the \mathcal{F} set corresponds to the set of objects constituting the object described by the record 2231:

$$FR = \prod_{i \in \mathcal{F}} OR_i \times LCM(\{FR_i\}_{i \in \mathcal{F}})$$

The above formula allows to dynamically link the object described by the record 2231 with the objects constituting it, because any change in the value of one of the factors OR_i or FR_i will be automatically reflected into FR. If the \mathcal{F} set is empty (for instance when the object described by the record 2231 is an EP, or a MEP, or an EF, or a MEF), then the FR subfield defaults to the value 1 (one).

- The "INSTANCE REFERENCE" (or IR for short) subfield **2240c**. This subfield is initiated to the value 1 (one) when the object described by the record **2231** is created. Afterwards this subfield is multiplied by 2 (two) each time a new instance abiding by this object is created, and is divided by 2 (two) each time an existing instance abiding by this object is deleted.

- The "REFERENCED OBJECT" (or RO for short) subfield **2240d**. This subfield is a Boolean variable specifying if the object described by the record **2231** participates to the definition of another object. For instance an EF, or a MEF, or an EP, or a MEP can participate to the definition of a ST. Similarly a ST can participate to the definition of a RE which can itself participate to the definition of a RST. This subfield is evaluated according to the following formula, where the \mathcal{P} set corresponds to the set of objects the type of which follows the type of the object described by the record **2231, in the hierarchy of RST objects:**

$$RO = \text{"YES"} \text{ if } \text{LCM}(\{FR_i\}_{i \in \mathcal{P}}) \bmod OR = 0;$$

$$RO = \text{"NO"} \text{ otherwise.}$$

The above formula allows to dynamically link the object described by the record **2231** with the objects belonging to the \mathcal{P} set, because any change in the value of one of the factors FR_i will be automatically reflected into RO. If the object described by the record **2231** is an EF, or a MEF, or an EP, or a MEP, then the \mathcal{P} set corresponds to the set of ST's. If the object described by the record **2231** is a ST, then the \mathcal{P} set corresponds to the set of RE's. If the object described by the record **2231** is a RE, then the \mathcal{P} set corresponds to the set of RST's. If the object described by the record **2231** is a RST, then the \mathcal{P} set is empty (the top of the hierarchy being reached), so that the RO subfield defaults to the value "NO".

- The "SELECTED CHILDREN" (or SC for short) subfield **2240e**. This subfield is a Boolean variable specifying if the object described by the record **2231** participates to the definition of a selected object. This subfield is evaluated according to the following formula, where the \mathcal{S} set corresponds to the set of selected objects (having the "SELECTED" attribute **2242** equal to the value "YES"):

$$SC = \text{"YES"} \text{ if } \text{LCM}(\{FR_i\}_{i \in \mathcal{S}}) \bmod OR = 0 \text{ \#OR\# object } \in \mathcal{S};$$

$$SC = \text{"NO"} \text{ otherwise.}$$

The above formula allows to dynamically link the object described by the record **2231** with the selected objects (belonging to the \mathcal{S} set), because any change in the value of one of the factors FR_i or in the \mathcal{S} set will be automatically reflected into SC.

The other "REFERENCED" attributes **709**, **719**, **729**, **780**, **2219**, and **2229**, as defined within the tables EFT **700**, EPT **710**, STT **720**, RSTEIT **770**, RET **2210**, and RSTT **2220**, are based on the same set of five subfields.

- the "SELECTED" attribute **2242** reflecting whether the associated object has been or not selected by the spreadsheet user within the RST Manager Dialog Box **2300**, (with respective values "YES" and "NO"), and also
- the "NATURE" attribute **2241** reflecting whether the object is a (M)EF, or a (M)EP, or a ST, or a R(M)E, or a RST (with respective values "FORMAT", or "PROFILE" or "TEMPLATE" or "RECELEMENT" or "RECTEMPLATE").

Conventional techniques can be used for encoding these different attributes in this "Type" field **2237**, such as executing bit-wise XOR operations with predefined bit patterns, but any other conventional means could be used instead without departing from the spirit of the invention.

- The "Index" **2238** field is used for sorting the **RSTMT** table, as performed by the **RST Manager** method.

C9. RST Descriptor Table

Referring now to FIG. 17D, the **RSTDT** Table 2250 corresponds to a logical simple structure made of several names of RE's or RME's 2254. This structure is organized into three sub-sets:

- The optional RST "*Header*" part 2256, made of a variable number (possibly null) of RME names like the top name 2251.
- The mandatory "*Body*" part 2252 made of a single RE name.
- The optional RST "*Footer*" part 2255, made of a variable number (possibly null) of RME names like the bottom name 2253.

C10. RSTI Table

10 Referring now to FIG. 17E, the **RSTIT** Table 2260 corresponds to a logical simple structure made of several records 2261, each of them corresponding to a RSTI, according to the preferred embodiment of the present invention. Each record includes six fields:

- The "*Address*" 2262 field is used for locating the RSTI described by the current record 2261: its value corresponds to the conventional character string used to record the address of any range of cells.
- The "*ST*" 2263 field is used for recording the name of the RST abided by the RSTI described by the current record 2261.
- The "*Element #*" 2264 field is used for recording the number of RE's within the RSTI described by the current record 2261.
- The "*Critical*" 2265 field is used for recording if the RSTI described by the current record 2261 is considered as critical. Its content can take the values "YES" or "NO".
- The "*Header Size*" 2266 field is used for recording the number of RME's constituting the Header part of the RSTI described by the current record 2261.
- The "*Footer Size*" 2267 field is used for recording the number of RME's constituting the Footer part of the RSTI described by the current record 2261.

C11. RSTI Descriptor Table

Referring now to FIG. 17F, the **RSTIDT** Table 2270 corresponds to a logical simple structure made of several records 2271, each of them made of several cells 2272, each of them corresponding to a STI member of the RSTI, according to the preferred embodiment of the present invention. The **RSTIT** table 2270 is mapped to the structure of the associated RSTI with a top header part 2275 (possibly empty) constituted by one or several records 2271, with a middle body part 2274 constituted by one or several records 2271, and with a bottom footer part 2273 (possibly empty) constituted by one or several records 2271. Each record 2271 comprises one or a plurality of individual cells 2272, the number of which 35 corresponding to the number of STI's per RE. Each record 2272 includes seven fields characterizing a STI member of the RSTI:

- The "*container_range*" 2276 field is used for recording the address of the container range hosting the STI described by the record 2272. By referring to the FIG 15A, this field records the address of the container 2014 (intersection of the container row 2012 and of the container column 2005) if the record 2272 describes the STI 2013.
- The "*container_col*" 2277 field is used for recording the number of columns of the container range hosting the STI described by the record 2272. By referring to the FIG 15A, this field records the column number 2028 if the record 2272 describes the STI 2013.
- The "*STI_col*" 2278 field is used for recording the number of columns of the STI described by the record 2272. By referring to the FIG 15A, this field records the column number 2026 if the record 2272 describes the STI 2013.
- The "*STI_row*" 2279 field is used for recording the number of rows of the STI described by the record 2272. By referring to the FIG 15A, this field records the row number 2027 if the record 2272 describes the STI 2013.
- The "*ST_name*" 2280 field is used to record the name of the ST abided by the STI described by the record 2272.

- The “*container_row*” **2281** field is used for recording the number of rows of the container range hosting the STI described by the record **2272**. By referring to the FIG **15A**, this field records the row number **2029** if the record **2272** describes the STI **2013**.
- The “*STIT_rec_ptr*” **2282** field is used for pointing, within the *STIT* table **750**, to the record **751** describing the STI described by the record **2272**.

C12. Relationships Between Tables

Referring now to FIG. **7F**, some previously introduced tables *RSTIT* **2260**, *RSTIDT* **2270**, *RSTT* **2220**, *RSTD* **2250**, *RET* **2210**, *STIT* **750**, *STT* **720**, *STDT* **760**, *EFT* **700** and *EPT* **710** are presented altogether to illustrate the relationships established between these tables and with either a *RSTI* **730** or a *STI* **797**. Within this diagram, a solid bold arrow illustrates a pointer based relationship towards a table or a record, a dashed bold arrow illustrates an address based relationship towards a range of cells, a solid unbold arrow illustrates a name based relationship towards an object, and a dashed unbold arrow illustrates a size based relationship towards an object. In the FIG **7F**, the pointer based, address based and named relationships are identified by an index represented within a circle, according to the following sequence:

- Starting with a *STI* **797** made of the three parts “*STI Header*”, “*STI Body*” and “*STI Footer*”, a first address based relationship ① is established between this *STI* **797** and a record **751** of the *STIT* table **750**.
- A second name based relationship ② is then established between this record **751** and a record **721** of the *STT* table **720**. This record **721** corresponds to the *ST* abided by the *STI* **797**.
- A third pointer based relationship ③ is established between this record **721** and a *STDT* table **760** which describes the structure of the *ST*. Each record of the *STDT* table **760** corresponds to a pair of an element or MEF name and of an element or MEP name.
- A fourth name based relationship ④ is established between the element or MEF name and a record **701** of the *EFT* table **700**.
- A fifth name based relationship ⑤ is established between the element or MEP name and a record **711** of the *EPT* table **710**.
- A sixth pointer based relationship ⑥ is established between the record **701** and an illustrative range of cells **798** specifying the format attributes.
- A seventh pointer based relationship ⑦ is established between the record **711** and an illustrative range of cells **799** specifying the profile content.
- Starting now with a *RSTI* **730** made of the three parts “*RSTI Header*”, “*RSTI Body*” and “*RSTI Footer*”, an eighth address based relationship ⑧ is established between this *RSTI* **730** and a record **2261** of the *RSTIT* table **2260**.
- A ninth pointer based relationship ⑨ is established between this record **2261** and a *RSTIDT* table **2270** which describes the structure of the *RSTI* **730**. Each cell **2272** of the *RSTIDT* table **2270** comprise several fields **2276**, **2277**, **2278**, **2279**, **2280**, **2281** and **2282** related to a given *STI* (like *STI* **797**) member of the *RSTI* **730**.
- A tenth address based relationship ⑩ is thus established between the **2276** field of the cell **2272** of the *RSTIDT* table **2270**, and the container range comprising the *STI* **797**.
- An eleventh pointer based relationship ⑪ is also established between the **2282** field of the cell **2272** of the *RSTIDT* table **2270**, and the record **751** of the *STIT* table **750** corresponding to the *STI* **797**.
- A twelfth name based relationship ⑫ is then established between the record **2261** and a record **2221** of the *RSTT* table **2220**. This record **2221** corresponds to the *RST* abided by the *RSTI* **730**.
- A thirteenth pointer based relationship ⑬ is established between this record **2221** and a *RSTD* table **2250** which describes the structure of the *RST*. Each record of the *RSTD* table **2250** corresponds to a *RE* or *RME*.

- A fourteenth name based relationship ①④ is established between the RE or RME name and a record 2211 of the RET table 2210.
- A fifteenth pointer based relationship ①⑤ is established between the record 2211 and a RE descriptor range of cells 731 containing the names of ST's.
- 5 • A sixteenth name based relationship ①⑥ is established between the RE descriptor range of cells 731 and a record 721 of the STT table 720.
- A similar seventeenth name based relationship ①⑦ is established between the cell 2272 of the RSTIDT table 2270 and a record 721 of the STT table 720.

D. Scenarios

- 10 In contrast to just-described conventional tools, the preferred embodiment of the present invention provides a more powerful, user-friendly and interactive approach for defining and managing ST's, in a form of a collection of methods.

In a preferred embodiment, the present invention is used within a scenario which articulates as a sequence of operations :

- 15 • **1. First Operation : Creation of a STI or of a RSTI**

The first operation occurs when the spreadsheet user decides, based on some criteria not detailed here, to either create a STI abiding by the structure of a ST or to create a RSTI abiding by the structure of a RST. In a preferred embodiment of the present invention, this operation comprises the following steps:

- 20 • **a. RST Manager** : The spreadsheet user invokes first an original specific command called "**RST Manager**" thanks to conventional means available in spreadsheet environment, such as but not limited to the pointing device 105 or the keyboard 104, in order to visualize through a dedicated user interface any existing EF or MEF or EP or MEP or RE or RME or ST or RST. This RST manager offers different alternatives
- 25 for further managing these entities. This can be illustrated with the user interface described with the FIG 2, showing the RST Manager Dialog Box 200, as displayed on the display device 106. Within this RST Manager Dialog Box 200, the user can visualize already defined objects (EF's, MEF's, EP's, MEP's, RE's, RME's, ST's and RST's) in the "list boxes" 213, 214 and 202 where are respectively specified the names of the objects, the types of the objects and their last date of update. If a large number of objects have been defined, then the user can navigate among them by clicking with the pointing device 105 either upwards or downwards on the scroll bar
- 30 203, so that the objects shown within the list boxes 213, 214 and 202 move back and forth between the top object and the bottom object. In a preferred embodiment of the present invention, the objects have been sorted by date of last update, but any other sorting scheme could be also used without departing from the spirit of the invention. Several actions may then be taken by the user. The user can use the pointing device 105 to click on a check box on the left side of the RST Manager Dialog Box 200 like the check box 212, in order to either select or deselect the object whose name is displayed within the list box 213 just on the right of the clicked check box. One or multiple objects can be selected or deselected. List scrolling is of course reflected on the check boxes. Once a selection is performed, the user can use the pointing device 105 to click on the "**Delete**" push-button 207, if he/she intends to remove all the selected objects from the list boxes 213, 214 and 202. If there is no other object (either ST or STI or RE or RME or RST or RSTI) referring to at least one of these objects, then they are immediately deleted, so that they do no longer appear on the list boxes 213, 214 and 202. If there is at least one other ST or STI or RE or RME or RST or RSTI referring to at least one of the selected objects, then a conventional dialog box is displayed on the display device 106 to first alert the user about this situation and second to invite him to either cancel the deletion operation or to confirm it. If the user decision is to cancel the operation, then no action is taken, otherwise the selected objects are immediately deleted, so that they do no longer appear on the list boxes 213, 214 and 202.
- 40
- 45
- 50

Alternatively the user can use the pointing device **105** to click on the "*Edit*" push-button **211** if he/she wants to edit the selected object which is assumed to be unique.

If no object or multiple objects have been previously selected, as shown within the RST Manager Dialog Box **200** by the presence of no or multiple check marks (visible or not) within the check boxes located on the left side, like the check box **212**, then a warning message is displayed on the display device **106** to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention.

If a single object was previously selected, as shown by the presence of a single check mark (visible or not) within a check box located on the left side, like the check box **212**, then the RST Manager Dialog Box **200** is first closed and afterwards the nature of this single selected object is taken into account to determine the new dialog box to be opened.

- If the selected object was an EF or a MEF, then the **EF Editor** command is issued, so that the **EF Editor** method takes control by first displaying on the display device **106** the EF Editor Dialog Box **301**, as illustrated in FIG 3. The following steps of this scenario case are detailed in a subsequent section.
- If the selected object was an EP or a MEP, then the **EP Editor** command is issued, so that the **EP Editor** method takes control by first displaying on the display device **106** the EP Editor Dialog Box **401**, as illustrated in FIG 4. The following steps of this scenario case are detailed in a subsequent section.
- If the selected object was a RE or a RME, then the **RE Editor** command is issued, so that the **RE Editor** method takes control by first displaying on the display device **106** the RE Editor Dialog Box **2321**, as shown in FIG 18B. The following steps of this scenario case are detailed in a subsequent section.
- If the selected object was a ST, then the **ST Editor** command is issued, so that the **ST Editor** method takes control by first displaying on the display device **106** the ST Editor Dialog Box **501**, as illustrated in FIG 5. The following steps of this scenario case are detailed in a subsequent section.
- If the selected object was a RST, then the **RST Editor** command is issued, so that the **RST Editor** method takes control by first displaying on the display device **106** the RST Editor Dialog Box **601**, as illustrated in FIG 6. The following steps of this scenario case are detailed in a subsequent section.

Alternatively the user can use the pointing device **105** to click on the "*Instanciate*" push-button **204** if he/she wants to generate either a STI or a RSTI which abides by the selected object which is assumed to be unique and to be respectively a ST or a RST.

If no object or multiple objects have been previously selected, as shown within the RST Manager Dialog Box **200** by the presence of no or multiple check marks (visible or not) within the check boxes located on the left side, like the check box **212**, then a warning message is displayed on the display device **106** to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention.

If a single object was previously selected, as shown by the presence of a single check mark (visible or not) within a check box located on the left side, like the check box **212**, then the method checks if this object is a ST or a RST.

If it is not the case, then a warning message is displayed on the display device **106** to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention.

If a single ST (respectively RST) object was previously selected, then the RST Manager Dialog Box 200 is first closed and afterwards the *ST Instanciator* (resp. *RST Instanciator*) command is issued, so that the *ST Instanciator* (resp. *RST Instanciator*) method takes control by first displaying on the display device 106 the ST Instanciator Dialog Box 1300 (resp. RST Instanciator Dialog Box 2300), as shown in FIG 13A (resp. 18A). The following steps of this scenario case are detailed in subsequent sections.

Alternatively the user can use the pointing device 105 to click on the "Export" push-button 206 if he/she wants to export a non-empty set of objects from the current spreadsheet file to another spreadsheet file. If the check box "Including child objects (for Export)" 220 is filled with a check mark, then all the child objects of the selected objects will also benefit from the export operation, even if these child objects are not selected through the check boxes located on the left side, like the check box 212.

If no object has been previously selected, as shown within the RST Manager Dialog Box 200 by the absence of any check mark (visible or not) within the check boxes located on the left side, like the check box 212, then a warning message is displayed on the display device 106 to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention.

If one or multiple objects were previously selected, as shown by the presence of at least one check mark (visible or not) within a check box located on the left side, like the check box 212, then the RST Manager Dialog Box 200 is first closed and afterwards a specific *RST Export Manager* command is issued, so that a dedicated method, not described in the present invention, takes control to handle the export operation.

Alternatively the user can use the pointing device 105 to click on the "Import" push-button 205 if he/she wants to import one or several objects from another spreadsheet file to the current spreadsheet file. The RST Manager Dialog Box 200 is first closed and afterwards a specific *RST Import Manager* command is issued, so that a dedicated method, not described in the present invention, takes control to handle the import operation.

Alternatively the user can use the pointing device 105 to click on one of the five option-buttons 217 "Format", 209 "Profile", 216 "Template", 218 "RE", 219 "Recursive Template", on the bottom left side of the RST Manager Dialog Box 200, if he/she wants to specify which type of new object may be created afterwards. As five option-buttons are available on the RST Manager Dialog Box 200, the user has the choice to specify either a EF, or a EP or a RE or a ST or a RST as the type of the new object to be created afterwards.

Alternatively the user can use the pointing device 105 to click on the check-box 208 entitled "From current selection", if he/she wants to specify if the next object to be created afterwards will be derived or not from the range of cells currently selected in the spreadsheet file.

Alternatively the user can use the pointing device 105 to click on the "Create New" push-button 210 if he/she wants to create a new object whose type has been previously specified thanks to the three option-buttons like

- the "Profile" option-button 209, or
- the "Format" option-button 217, or
- the "Template" option-button 216, or
- The "RE" option-button 218, or
- The "Recursive Template" option-button 219.

If none of these five option-buttons shows a previous user choice, as shown within the RST Manager Dialog Box 200 by the absence of a point within one of these five

option-buttons **209**, **216**, **217**, **218** and **219**, then a warning message is displayed on the display device **106** to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention.

If one of these five option-buttons **209**, **216**, **217**, **218** and **219** shows a previous user choice, then the RST Manager Dialog Box **200** is first closed and afterwards the single selected option-button is taken into account to determine the new dialog box to be opened.

- If the "*Format*" option-button **217** shows a selection, then the **EF Editor** command is issued, so that the **EF Editor** method takes control by first displaying on the display device **106** the EF Editor Dialog Box **301**, as shown in FIG 3. The following steps of this scenario case are detailed in a subsequent section.

- If the "*Profile*" option-button **209** shows a selection, then the **EP Editor** command is issued, so that the **EP Editor** method takes control by first displaying on the display device **106** the EP Editor Dialog Box **401**, as shown in FIG 4. The following steps of this scenario case are detailed in a subsequent section.

- If the "*Template*" option-button **216** shows a selection, then the **ST Editor** command is issued, so that the **ST Editor** method takes control by first displaying on the display device **106** the ST Editor Dialog Box **501**, as illustrated in FIG 5. The following steps of this scenario case are detailed in a subsequent section.

- If the "*RE*" option-button **218** shows a selection, then the **RE Editor** command is issued, so that the **RE Editor** method takes control by first displaying on the display device **106** the RE Editor Dialog Box **2321**, as illustrated in FIG 18B. The following steps of this scenario case are detailed in a subsequent section.

- If the "*Recursive Template*" option-button **219** shows a selection, then the **RST Editor** command is issued, so that the **RST Editor** method takes control by first displaying on the display device **106** the RST Editor Dialog Box **601**, as illustrated in FIG 6. The following steps of this scenario case are detailed in a subsequent section.

Finally the user can use the pointing device **105** to click on the "*Done*" push-button **201** or on the closing-window push-button **215** if he/she wants to quit the RST Manager method. The resulting effect is to close the RST Manager Dialog Box **200** on the display device **106**.

- **b. EF Editor** : According to the previous scenario illustrating the **RST Manager** method, the spreadsheet user may then invoke an original specific command called "**EF Editor**" thanks to conventional means available in spreadsheet environment, such as but not limited to the pointing device **105** or the keyboard **104**, in order to either create a new EF; or to create a new MEF; or to update an existing EF; or to update an existing MEF. The corresponding scenario is described in international patent application PCT/EP 02/09483 (IBM's reference FR9 2001 0029) entitled "System and method in an electronic spreadsheet for exporting-importing the content of input cells from a scalable template instance to another" by Aureglia et al.
- **c. EP Editor** : According to the previous scenario illustrating the **RST Manager** method, the spreadsheet user may then invoke an original specific command called "**EP Editor**" thanks to conventional means available in spreadsheet environment, such as but not limited to the pointing device **105** or the keyboard **104**, in order to either create a new EP or to create a new MEP or to update an existing EP or to update an existing MEP. The corresponding scenario is described in international patent application PCT/EP 02/09483 (IBM's reference FR9 2001 0029) entitled "System and method in an electronic spreadsheet for exporting-importing the content of input cells from a scalable template instance to another" by Aureglia et al.

- **d. RE Editor** : According to the previous scenario illustrating the *RST Manager* method, the spreadsheet user may then invoke an original specific command called "**RE Editor**" thanks to conventional means available in spreadsheet environment, such as but not limited to the pointing device **105** or the keyboard **104**, in order to either create a new RE or to create a new RME or to update an existing RE or to update an existing RME. This can be illustrated with the user interface described with the FIG **18B**, showing the RE Editor Dialog Box **2321**, as displayed on the display device **106** within the GUI window of the electronic spreadsheet office application.

When the RE Editor Dialog Box **2321** is displayed on the display device **106**, it contains some pieces of information.

First the nature of the edited object is shown by a pair of option-buttons **2330** and **2331** which specifies if it is either a RE or a RME. The spreadsheet user can click with the pointing device **105** on one of these two option-buttons **2330** and **2331** to swap between a RE definition and a RME definition.

Second the number of fields within the edited object is specified in the text-box **2326**. When a new RE or RME is created (the spreadsheet user having previously clicked with the pointing device **105** on the option-button **218** to put a point on it and on the push-button **210**, all contained within the RST Manager Dialog Box **200**, as illustrated by FIG **2**), the value shown by the text box **2326** corresponds to a default value set to 3 in a preferred embodiment of the present invention. When an existing RE or RME is edited, the value shown by the text box **2326** corresponds to the number of fields previously defined for this object. In all cases, the spreadsheet user can change the value shown in the text box **2326** by clicking with the pointing device **105** on the spin-button **2327**, either on the ascending or on the descending side, so that the value can get increased or decreased (within predefined boundaries).

Third the name of the edited RE or RME is displayed on the label box **2324**. When an existing RE or RME is edited, the name shown by the label box **2324** corresponds to the name previously assigned to this object. When a new RE or RME is created, then the name displayed on the label box **2324** corresponds to a default value which, in a preferred embodiment of the present invention, takes the form "New XX" where XX is a counter ensuring the uniqueness of the assigned name.

Fourth the ST's constituting the edited RE or RME are jointly specified by the text boxes **2335** and **2334**. The text box **2335** specifies a field rank, which by convention takes the value 1 for the leftmost field of the edited RE or RME, and takes the same value as the one displayed in the text box **2326** for the rightmost field of the edited RE or RME. The text box **2334** specifies the name of the ST for the field whose rank is specified by the text box **2335**.

The RE Editor Dialog Box **2321** contains several graphical objects which allow the spreadsheet user to take some actions.

First the spreadsheet user can assign a new name to the currently edited RE or RME. For this purpose he/she will first use conventional means such as the keyboard **104** to specify within the text box **2325** the new name to be given to the edited RE or RME. Then he/she will use the pointing device **105** to click on the "Save As" push-button **2332**. If the specified name entered within the text box **2325** was already assigned to an existing object or was not a valid name, then a warning message is displayed on the display device **106** to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention. This warning message informs the spreadsheet user about this situation and then prompts him for acknowledgment. Then the text box **2325** is cleared without further action. If the specified name entered within the text box **2325** was not yet assigned to an existing object and was a valid name, then the text box

2325 is cleared and the edited object is saved on the spreadsheet file under the new name which is in turn displayed within the label box 2324.

Second the spreadsheet user can save on the spreadsheet file the current definition of the edited object by clicking with the pointing device 105 on the "Save" push-button 2333. This event results in checking if the updated RE or RME is already referenced by an existing RST. If it is not the case, then the updated definition of the RE or RME is saved on the spreadsheet file. If it is the case, then a warning message is displayed on the display device 106 to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention. This warning message informs the spreadsheet user about this situation and then prompts him for either canceling the operation or for pursuing it. In the first case the updated RE or RME definition is not saved while it is saved on the spreadsheet file in the second case.

Third the spreadsheet user can change the definition of the ST's constituting the edited RE or RME. For this purpose he/she will first navigate within the fields of the edited object by clicking with the pointing device 105 on the spin-button 2329 to either decrement or increment the rank of the field, as displayed in the text box 2335, and whose ST name is displayed in the text box 2334. The value taken by the field rank is kept within an interval lower bounded by the value 1 (one) and upper bounded by the value of the text box 2326. Then the spreadsheet user can update the name of the ST for the field whose rank is displayed in the text box 2335 by clicking with the pointing device 105 on the spin-button 2328 to select an available ST name.

Finally the user can use the pointing device 105 to click on the "Done" push-button 2323 or on the closing-window push-button 2322 if he/she wants to quit the RE Editor method. The resulting effect is to close the RE Editor Dialog Box 2321 on the display device 106.

- **e. ST Editor** : According to the previous scenario illustrating the *RST Manager* method, the spreadsheet user may then invoke an original specific command called "**ST Editor**" thanks to conventional means available in spreadsheet environment, such as but not limited to the pointing device 105 or the keyboard 104, in order to either create a new ST or to update an existing ST. The corresponding scenario is described in international patent application PCT/EP 02/09483 (IBM's reference FR9 2001 0029) entitled "System and method in an electronic spreadsheet for exporting-importing the content of input cells from a scalable template instance to another" by Aureglia et al.
- **f. RST Editor** : According to the previous scenario illustrating the *RST Manager* method, the spreadsheet user may then invoke an original specific command called "**RST Editor**" thanks to conventional means available in spreadsheet environment, such as but not limited to the pointing device 105 or the keyboard 104, in order to either create a new RST or to update an existing RST. This can be illustrated with the user interface described with the FIG 6, showing the RST Editor Dialog Box 601, as displayed on the display device 106 within the GUI window 611 of the electronic spreadsheet office application. When the RST Editor Dialog Box 601 is displayed on the display device 106, the current sheet becomes a dedicated sheet entitled "**Editor Space**" 615 in a preferred embodiment of the present invention. Within the "**Editor Space**" 615 sheet, the RST to be edited appears as a range of cells 614 in the top left angle, with the top left cell at address B2. Although the edited RST corresponds to a regular range of cells 614 within a sheet, conventional tools available in electronic spreadsheet environments cannot be used to update this range of cells 614. The spreadsheet user will only be able to navigate within the range of cells 614 illustrating the RST, and to either insert or delete rows within the range of cells 614

illustrating the RST, by using dedicated means which are part of the RST Editor Dialog Box 601. Row insertion or deletion in the "Editor Space" sheet 615 will be disabled. Moreover the "Editor Space" sheet 615 is write-protected to prevent the user to inadvertently modify the settings of the RE's or RME's defined as part of the RST illustrated by the range of cells 614.

When the RST Editor Dialog Box 601 is displayed on the display device 106, it contains some pieces of information which either relate to the whole RST, as illustrated by the range of cells 614, or which relate to the RE or RME pointed by the cell currently selected within this same range of cells 614.

First the RE or RME pointed by the cell currently selected is shown by the "RE" combo box 610. By clicking with the pointing device 105 on the arrow located on the right side of this "RE" combo box 610, the spreadsheet user can display and navigate within the list of defined RE's and RME's, then select a RE or RME of his/her choice and his/her choice appearing on the row where is located the currently selected cell within the range of cells 614. If the spreadsheet user changes the selected row within the range of cells 614, by clicking with the pointing device 105 on the "Up" push-button 619, or on the "Down" push-button 616, then the name displayed within the combo box 610 is updated to specify the name of the RE or RME corresponding to the new selected row. If the spreadsheet user wishes to insert a new RME either in the header or in the footer part of the RST, he/she has just to click with the pointing device 105 on the "Add" push-button 617 to insert a new row within the range of cells 614, at the desired place above the last position of the currently selected cell. Then the range of cells 614 is updated with a new row being displayed on the window 611. Then the RST Editor Dialog Box 601 is updated by showing within the combo boxes 610 the name assigned by default to the introduced RME. If the spreadsheet user wishes to remove a RME either from the header part or from the footer part of the RST, he/she has just to click with the pointing device 105 on the "Delete" push-button 618 to remove the corresponding row within the range of cells 614, at the desired place. Then the currently selected cell within the range of cells 614 becomes the one belonging to the row representing the unique RE defined within the RST, and the RST Editor Dialog Box 601 is updated by showing within the combo box 610 the name of the unique RE defined within the RST.

Second the minimum number of RE's allowed within a RSTI abiding by the edited RST is specified in the "MIN" text-box 606. Similarly the maximum number of RE's allowed within a RSTI abiding by the edited RST is specified in the "MAX" text-box 609. When a new RST is created (the spreadsheet user having previously clicked with the pointing device 105 on the option-button 219 to put a point on it and on the push-button 210, all contained within the RST Manager Dialog Box 200, as illustrated by FIG 2), the value shown by the "MIN" text box 606 corresponds to a default value set to 1 in a preferred embodiment of the present invention, and the value shown by the "MAX" text box 609 corresponds to a default value set to 16 in a preferred embodiment of the present invention. When an existing RST is edited, the values shown by the text boxes 606 and 609 correspond respectively to the minimum and maximum number of RE's allowed in any RSTI abiding by the currently edited RST, as previously defined by the spreadsheet user. In all cases, the spreadsheet user can change the values shown in the text box "MIN" 606 or in the text box "MAX" 609 by clicking with the pointing device 105 respectively on the spin-button 607 or on the spin-button 608, either on the ascending or on the descending side, so that the values can get increased or decreased (within predefined boundaries), while ensuring that the value specified in the "MIN" text box 606 remains less than or equal to the value specified in the "MAX" text box 609. Should any existing RSTI abiding by the updated RST have a number of elements

falling outside the new "*MIN*"-"*MAX*" interval, then this RSTI will not be impacted by the RST update, but any future addition or removal of RE's will be done according to the new definition of the "*MIN*"-"*MAX*" interval.

Third the name of the edited RST is displayed on the label box 604. When an existing RST is edited, the name shown by the label box 604 corresponds to the name previously assigned to this object. When a new RST is created, then the name displayed on the label box 604 corresponds to a default value which, in a preferred embodiment of the present invention, takes the form "New XX" where XX is a counter ensuring the uniqueness of the assigned name.

The RST Editor Dialog Box 601 comprises several graphical objects which allow the spreadsheet user to take some actions.

First the spreadsheet user can assign a new name to the currently edited RST, if this RST is currently constituted by RE's and RME's having all the same number of fields. Indeed in this case the "Save As" push-button 612 is enabled, so that any click on it with the pointing device 105 is recognized as a valid event. The spreadsheet user will first use conventional means such as the keyboard 104 to specify within the text box 605 the new name to be given to the edited RST. Then he/she will use the pointing device 105 to click on the "Save As" push-button 612. If the specified name entered within the text box 605 was already assigned to an existing object or is not a valid name, then a warning message is displayed on the display device 106 to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention. This warning message informs the spreadsheet user about this situation and then prompts her/him for acknowledgment. Then the text box 605 is cleared without further action. If the specified name entered within the text box 605 was not yet assigned to an existing object and is a valid name, then the text box 605 is cleared and the edited RST is saved on the spreadsheet file under the new name which is in turn displayed within the label box 604.

Second the spreadsheet user can save on the spreadsheet file the current definition of the edited RST, if this RST is currently constituted by RE's and RME's having all the same number of fields. Indeed in this case the "Save" push-button 613 is enabled, so that any click on it with the pointing device 105 is recognized as a valid event. This event results in checking if the updated RST is already referenced by an existing RSTI. If it is not the case, then the updated definition of the RST is saved on the spreadsheet file. If it is the case, then a warning message is displayed on the display device 106 to the user through conventional means such as pop-up windows, status bar messages, or any other similar conventional means which can be used instead without departing from the spirit of the invention. This warning message informs the spreadsheet user about this situation and then prompts him for either canceling the operation or for pursuing it. In the first case the updated RST definition is not saved while it is saved on the spreadsheet file in the second case.

Finally the user can use the pointing device 105 to click on the "Done" push-button 603 or on the closing-window push-button 602 if he/she wants to quit the RST Editor method. The resulting effect is to close the RST Editor Dialog Box 601 on the display device 106 and to revert to the sheet which was active when the **RST Editor** command was first invoked.

- **g. ST Instanciator** : According to the previous scenario illustrating the **RST Manager** method, the spreadsheet user may then invoke an original specific command called "**ST Instanciator**" thanks to conventional means available in spreadsheet environment, such as but not limited to the pointing device 105 or the keyboard 104, in order to create a STI abiding by a selected ST and located according to the currently selected cell. The corresponding scenario is described in

international patent application PCT/EP 02/09483 (IBM's reference FR9 2001 0029) entitled "System and method in an electronic spreadsheet for exporting-importing the content of input cells from a scalable template instance to another" by Aureglia et al.

- **h. RST Instanciator** : According to the previous scenario illustrating the **RST Manager** method, the spreadsheet user may then invoke an original specific command called "**RST Instanciator**" thanks to conventional means available in spreadsheet environment, such as but not limited to the pointing device **105** or the keyboard **104**, in order to create a RSTI abiding by a selected RST and located according to the currently selected cell. This can be illustrated with the user interface described with the FIG **18A**, showing the RST Instanciator Dialog Box **2300**, as displayed on the display device **106**. When the RST Instanciator Dialog Box **2300** is displayed on the display device **106**, the current sheet remains still active, so that the spreadsheet user can visualise the data present on it. The RST Instanciator Dialog Box **2300** contains some pieces of information which relate to the instantiation operation.

First the name of the RST that abides by the RSTI to be created, is displayed in a label box **2302**.

Second the number of RE's to be present at RSTI creation time is shown in a text box **2311**. This number takes a default value equal to the minimum number of RE's, as specified in the definition of the RST that abides by the RSTI to be created. If the spreadsheet user wished to create a RSTI with another number of RE's, then he/she will have to click with the pointing device **105** on the upper or lower side of the spin-button **2303** to either increase or decrease the number of RE's. This number of RE's will vary within a range delimited by the minimum and maximum number of RE's, as specified within the definition of the RST (fields "**Min Element #**" **2225** and "**Max Element #**" **2226** within a record **2221** of the RSTT table **2220** whose "**Name**" field **2222** matches the name displayed in the label box **2302**) and is displayed, after possible update, in the text box **2311**.

Third the push-button "**Cancel**" **2308** or the closing-window push-button **2301** allow to close the RST Instanciation Dialog Box **2300** without further action. By clicking with the pointing device **105** on one of these two push-buttons **2301** and **2308**, the RST Instanciation Dialog Box **2300** is closed and the RST instanciation operation is aborted.

Fourth the push-button "**Create Instance**" **2310**, when first enabled and second clicked with the pointing device **105** by the spreadsheet user, is the trigger launching the operation of RST instanciation. This push-button "**Create Instance**" **2310** is enabled (meaning that the method recognises the click event with the pointing device **105** on this push-button "**Create Instance**" **2310**) when the instanciation operation is possible. The fact that this RST instanciation is possible or not depends on different factors: the position of the currently selected cell within the current sheet of the electronic spreadsheet, the size of the RSTI to be created, the presence of any existing STI belonging to the same sheet as the currently selected cell. The possibility to create or not a new RSTI with the size specified in the text box **2303**, abiding by a RST whose name is specified by the label box **2302**, with the top left corner located on the currently selected cell, is reflected by several label boxes, taking the values "YES" or "NO", which are part of the RST Instanciation Dialog Box **2300**: the label box **2304** which reflects if the new RSTI is or not too wide, the label box **2305** which reflects if the new RSTI is or not too high, the label box **2306** which reflects if any existing STI is already defined on the sheet comprising the currently selected cell, and the label box **2307** which reflects if the creation of the new RSTI may lead to loose any existing data present in one or several spreadsheet cells. As soon as the value "YES" is taken by the label box **2304**, or by the label box **2305**, or by the label box **2306**, then the RSTI creation is considered as impossible, so that

the "Create Instance" push-button 2310 get disabled. If the value "No" is displayed in these three label boxes, then the instantiation operation is possible, so that the "Create Instance" push-button 2310 get enabled. When clicked with the pointing device 105 by the spreadsheet user, the instantiation operation is performed, and then the RST Instanciation Dialog Box 2300 is closed.

Fifth the push-button "Create instance in a new sheet" 2309, when first enabled and second clicked with the pointing device 105 by the spreadsheet user, is an alternative trigger launching the operation of RST instantiation, but in a sheet which is created as part of this instantiation operation. In a preferred embodiment of the present invention, the new sheet is created after the sheet comprising the currently selected cell. Any other sheet position could be used instead, without departing from the spirit of the current invention. This push-button "Create instance in a new sheet" 2309 is enabled (meaning that the method recognises the click event with the pointing device 105 on this push-button "Create instance in a new sheet" 2309) when the instantiation operation is possible in a new sheet. The fact that this RST instantiation is possible or not in a new sheet depends on the size of the RSTI to be created. The possibility to create or not a new RSTI in a new sheet with the size specified in the text box 2303, abiding by a RST whose name is specified by the label box 2302, is reflected by several label boxes, taking the values "YES" or "NO", which are part of the RST Instanciation Dialog Box 2300: the label box 2304 which reflects if the new RSTI is or not too wide, and the label box 2305 which reflects if the new RSTI is or not too high. As soon as the value "YES" is taken by the label box 2304, or by the label box 2305, then the RSTI creation is considered as impossible in a new sheet, so that the "Create instance in a new sheet" push-button 2309 get disabled. If the value "No" is displayed in these two label boxes, then the instantiation operation is possible in a new sheet, so that the "Create instance in a new sheet" push-button 2309 get enabled. When clicked with the pointing device 105 by the spreadsheet user, the instantiation operation is performed in a new sheet, and then the RST Instanciation Dialog Box 2300 is closed.

• 2. Second Operation : Introduction of New Elements Within a Defined STI

The second operation occurs when the spreadsheet user decides, based on his or her own criteria not detailed here, to introduce new elements within a defined STI. The corresponding scenario is described in international patent application PCT/EP 02/09483 (IBM's reference FR9 2001 0029) entitled "System and method in an electronic spreadsheet for exporting-importing the content of input cells from a scalable template instance to another" by Aureglia et al.

• 3. Third Operation : Removal of Elements from a Defined STI

The fourth operation occurs when the spreadsheet user decides, based on his or her own criteria not detailed here, either to remove some elements from a defined STI, or to clear the content of some elements within a defined STI, or to delete a whole defined STI, or even to delete some spreadsheet cells or columns or rows from the current sheet. The corresponding scenario is described in international patent application PCT/EP 02/09483 (IBM's reference FR9 2001 0029) entitled "System and method in an electronic spreadsheet for exporting-importing the content of input cells from a scalable template instance to another" by Aureglia et al.

E.METHODS

E1. RST Manager method

The method for managing EF's, MEF's, EP's, MEP's, ST's, RE's and RST's used in the preferred embodiment of the present invention is summarized in flowchart 800 of FIG 8.

- At step 801, the method is in its default state, waiting for an event to initiate the process.

- At step 802, the **RST Manager** command is detected, as a result of a user action. This action can be for instance:

- a specific combination of key on the keyboard 104, or
- the click of the pointing device 105 on a specific button, or
- any other similar means not further specified here.

- At step 803, some local variables are initialized:

- the local variable *RSTM_select* is set to the value 0 (zero),
- the local variable *RSTM_new* is set to the value "NONE",
- the local variable *RSTM_range* is set to the value "NO", and
- the local variable *RSTM_index* is set to the value 1 (one), and
- The local variable *RSTM_child* is set to the value "NO".

- At step 804, the five tables EFT 700, EPT 710, STT 720, RET 2210 and RSTT 2220 are parsed to derive the table RSTMT 2230. For each respective record 701, or 711, or 721, or 2211, or 2221 found in one of these five tables, is created a new record 2231 within the RSTMT table 2230.

Referring now to FIG 7A, 7B, 7C, 17A, 17B and 17C, this construction is done by copying in sequence all the fields defined in the record 701 ("Name" field 702, "Last Change Date" field 703, "Description Ptr" field 704, "Row #" field 705, "Column #" field 706 and "Type" field 707), or in the record 711 ("Name" field 712, "Last Change Date" field 713, "Description Ptr" field 714, "Row #" field 715, "Column #" field 716 and "Type" field 717), or in the record 721 ("Name" field 722, "Last Change Date" field 723, "Description Ptr" field 724, "Min Element #" field 725, "Max Element #" field 726 and "Type" field 727), or in the record 2211 ("Name" field 2212, "Last Change Date" field 2213, "Description Ptr" field 2214, "Row #" field 2215, "Column #" field 2216 and "Type" field 2217), or in the record 2221 ("Name" field 2222, "Last Change Date" field 2223, "Description Ptr" field 2224, "Min Element #" field 2225, "Max Element #" field 2226 and "Type" field 2227) onto the corresponding fields of the record 2231 ("Name" field 2232, "Last Change Date" field 2233, "Description Ptr" field 2234, "Info Field 1" field 2235, "Info Field 2" field 2236 and "Type" field 2237), then by initialising in the "Type" field 2237 the "SELECTED" attribute 2242 to "NO" and the "NATURE" attribute 2241 to the values "FORMAT", or "PROFILE" or "TEMPLATE" or "RECELEMENT" or "RECTEMPLATE" if the record 2231 has been respectively copied from a record 701, or 711, or 721, or 2211, or 2221 and then by initializing the last field "Index" 2238 with the value of a counter which increments for each new record and which starts with the value 1 (one).

- At step 805, the RST Manager Dialog Box 200 is displayed on the display device 106.

- The "Name" information appearing on the top of the list box 213 corresponds to the "Name" field 2232 of the record 2231 in the RSTMT table 2230 whose "Index" field 2238 is equal to the local variable *RSTM_index*. Underneath "Name" information's within this list box 213 correspond to the "Name" field 2232 of the following records 2231 of the RSTMT table 2230.

- The "Type" information appearing on the top of the list box 214 is derived from the "Type" field 2237 (attributes "NATURE" 2241 and "META" 2239) of the record 2231 in the RSTMT table 2230 whose "Index" field 2238 is equal to the local variable *RSTM_index*. Underneath "Type" information's within this list box 213 are derived from the "Type" field 2237 (attributes "NATURE" 2241 and "META" 2239) of the following records 2231 of the RSTMT table 2230.

- The "Modified" information appearing on the top of the list box 202 corresponds to the "Last Change Date" field 2233 of the record 2231 in the RSTMT table 2230 whose "Index" field 2238 is equal to the local variable *RSTM_index*. Underneath "Modified" information's within this list box 213 correspond to the "Last Change Date" field 2233 of the following records 2231 of the RSTMT table 2230.

- The check box 212 is filled with a check mark if the "Type" field 2237 of the record 2231 in the RSTMT table 2230 whose "Index" field 2238 is equal to the local variable

RSTM_index has the "SELECTED" attribute **2242** equal to "YES". Underneath check boxes on the left of the list box **213** are also derived from the "Type" field **2237** ("SELECTED" attribute **2242**) of the following records **2231** of the RSTMT table **2230**.

- The option button "Format" **217** displays a black point if and only if the local variable *RSTM_new* is equal to "FORMAT". The option button "Profile" **209** displays a black point if and only if the local variable *RSTM_new* is equal to "PROFILE". The option button "Template" **216** displays a black point if and only if the local variable *RSTM_new* is equal to "TEMPLATE". The option button "RE" **218** displays a black point if and only if the local variable *RSTM_new* is equal to "RECELEMENT". The option button "Recursive Template" **219** displays a black point if and only if the local variable *RSTM_new* is equal to "RECTEMPLATE".
- The check box "From current selection" **208** displays a check mark if and only if the local variable *RSTM_range* is equal to "YES".
- The check box "Including child objects (for Export)" **220** displays a check mark if and only if the local variable *RSTM_child* is equal to "YES".
- At step **806**, the method is waiting for any user action on the RST Manager Dialog Box **200**. Such user action is typically resulting from a click with the pointing device **105**, but take other similar forms such as, but not limited to a specific combination of key on the keyboard **104**, or any other similar means not further specified here.
- At step **807**, a user action on the RST Manager Dialog Box **200** is detected.
 - If the user action is a click on the push-button "Delete" **207**, then control is given to step **808**;
 - if the user action is a click on the push-button "Import" **205**, then control is given to step **810**;
 - if the user action is a click on the push-button "Done" **201** or on the closing-window push-button **215**, then control is given to step **834**;
 - if the user action is a click on the push-button "Export" **206**, then control is given to step **811**;
 - if the user action is a click on the scrolling bar **203**, either on the up direction or on the down direction, then control is given to step **814**;
 - if the user action is a click on the option buttons "Format" **217**, or "Profile" **209**, or "Template" **216**, or "RE" **218**, or "Recursive Template" **219**, then control is given to step **815**;
 - if the user action is a click on the check box "From current selection" **208**, then control is given to step **816**;
 - if the user action is a click on the check box "Including child objects (for Export)" **220**, then control is given to step **841**;
 - if the user action is a click on a top check box like the check box **212**, then control is given to step **817**;
 - if the user action is a click on the push-button "Instanciate" **204**, then control is given to step **830**;
 - if the user action is a click on the push-button "Edit" **211**, then control is given to step **824** and;
 - if the user action is a click on the push-button "Create New" **210**, then control is given to step **818**.
- At step **808**, a test is performed on each of the records **2231** of the RSTMT table **2230** whose "Type" field **2237** has the "SELECTED" attribute **2242** with the subfield "REFERENCED OBJECT" (RO) **2240d** equal to "YES" or with the subfield "INSTANCE REFERENCE" (IR) **2240c** larger than 1 (one) (this test determines if there exist some objects referring to one of the selected objects, or if there exist some instance abiding by one of the selected objects).

- If it is the case, then control is given to step 835 (meaning that at least one record 2231 of the RSTMT table 2230 previously selected was referenced by a ST, or by a STI, or by a RE, or by a RST, or by a RSTI);
 - otherwise control is given to step 809.
- 5 • At step 809, each respective record 701, 711, 721, 2211 and 2221 is removed from the EFT table 700, EPT table 710, STT table 720, RET table 2210, and RSTT table 2220, if the corresponding respective "Name" field 702, 712, 722, 2212, and 2222 matches the "Name" field 2232 of a record 2231 of the RSTMT table 2230 whose "Type" field 2237
- 10 has the "SELECTED" attribute 2242 equal to "YES", as resulting from the step 817. Then the local variable *RSTM_select* is reset to the value 0 (zero). Then control is given to the step 804 for rebuilding the RSTMT table 2230.
- At step 810, the **RST Import Manager** command is issued and then control is given to step 834.
 - At step 811, a test is performed to determine if the local variable *RSTM_select* is equal
- 15 to 0 (zero).
- If it is the case, then control is given to step 813;
 - otherwise control is given to step 812.
- At step 812, the **RST Export Manager** command is issued and then control is given to step 834.
- 20 • At step 813, a warning message notification is issued for informing the user that at least one object must be selected prior clicking on the "Export" push-button 206. This can typically be done by displaying on the display device 106 a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this
- 25 notification message through conventional means such as clicking with the pointing device 105 on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step 805.
- At step 814, the local variable *RSTM_index* is either incremented or decremented by 1 (one) according to the direction (up or down) specified by the pointing device 105 on the scrolling bar 203, and as long as its value remains positive and less than or equal to the number of records 2231 defined within the RSTMT table 2230. Then control is given to step 805.
- 30 • At step 815, the local variable *RSTM_new* is updated to reflect the option button hit by the user with the pointing device 105.
- If the user has clicked on the "Format" option button 217, then the local variable *RSTM_new* takes the value "FORMAT".
 - If the user has clicked on the "Profile" option button 209, then the local variable *RSTM_new* takes the value "PROFILE".
- 40 • If the user has clicked on the "Template" option button 216, then the local variable *RSTM_new* takes the value "TEMPLATE".
- If the user has clicked on the "RE" option button 218, then the local variable *RSTM_new* takes the value "RECELEMENT".
 - If the user has clicked on the "Recursive Template" option button 219, then the local
- 45 variable *RSTM_new* takes the value "RECTEMPLATE".
- Then control is given to step 805.
- At step 816, the local variable *RSTM_range* is updated, so that its value swaps between "YES" and "NO". In addition, a check mark is respectively added within or removed from the check box 206 if it was previously absent or present in this same check box 206.
- 50 Then control is given to step 805.
- At step 817, the method updates the value of the "Type" field 2237 of the record 2231 within the RSTMT table 2230, whose "Name" field 2232 is found equal to the character

string located within the list box **213** immediately on the right of the check box on which the user has just clicked.

If the previous value of this "Type" field **2237** had the "SELECTED" attribute **2242** equal to "YES", then the value update consists in turning this "SELECTED" attribute **2242** to "NO" ; reversibly if the previous value of the "SELECTED" attribute **2242** was equal to "NO", then the value update consists in turning this "SELECTED" attribute **2242** to "YES".

In the first case the local variable *RSTM_select* is decremented by 1, and in the second case the local variable *RSTM_select* is incremented by 1.

Furthermore in the first case the check mark previously present in the check box on which the user has just clicked is removed from this check box and in the second case a check mark is displayed in the check box on which the user has just clicked. Then control is given to step **805**.

- At step **818**, a test is performed to determine if the local variable *RSTM_new* is equal to "NONE". If it is the case, then control is given to step **819**; otherwise control is given to step **820**.
- At step **819**, a warning message notification is issued for informing the user that at least one option ("Format" option button **217**, or "Profile" option button **209**, or "Template" option button **216**, or "RE" option button **218**, or "Recursive Template" option button **219**) must be selected prior clicking on the "Create New" push-button **210**. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device **105** on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **805**.
- At step **820**, a test is performed to determine the value taken by the local variable *RSTM_new*.
 - If found equal to "FORMAT", then control is given to step **821**;
 - If found equal to "PROFILE", then control is given to step **822**;
 - If found equal to "TEMPLATE", then control is given to step **823**.
 - If found equal to "RECELEMENT", then control is given to step **836**.
 - If found equal to "RECTEMPLATE", then control is given to step **837**.
- At step **821**, the **EF Editor** command is issued with passing two parameters ("NEW" ; *RSTM_range*) and then control is given to step **834**.
- At step **822**, the **EP Editor** command is issued with passing two parameters ("NEW" ; *RSTM_range*) and then control is given to step **834**.
- At step **823**, the **ST Editor** command is issued with passing one parameter ("NEW") and then control is given to step **834**.
- At step **824**, a test is performed to determine if the local variable *RSTM_select* is equal to 1 (one). If it is the case, then control is given to step **825**; otherwise control is given to step **829**.
- At step **825**, a test is performed to determine the nature of the selected object, as specified by the "Type" field **2237** "NATURE" attribute **2241** of the corresponding record **2231** of the RSTMT table **2230**.
 - If found equal to "FORMAT", then control is given to step **826**;
 - if found equal to "PROFILE", then control is given to step **827**;
 - if found equal to "TEMPLATE", then control is given to step **828**.
 - if found equal to "RECELEMENT", then control is given to step **838**.
 - if found equal to "RECTEMPLATE", then control is given to step **839**.
- At step **826**, the **EP Editor** command is issued with passing one parameter equal to the "Name" field **2232** of the unique record **2231** of the RSTMT table **2230** whose "Type"

field 2237 has the "SELECTED" attribute 2242 equal to "YES", and then control is given to step 834.

- At step 827, the **EF Editor** command is issued with passing one parameter equal to the "Name" field 2232 of the unique record 2231 of the RSTMT table 2230 whose "Type" field 2237 has the "SELECTED" attribute 2242 equal to "YES", and then control is given to step 834.
- At step 828, the **ST Editor** command is issued with passing one parameter equal to the "Name" field 2232 of the unique record 2231 of the RSTMT table 2230 whose "Type" field 2237 has the "SELECTED" attribute 2242 equal to "YES", and then control is given to step 834.
- At step 829, a warning message notification is issued for informing the user that a single object must be selected within the ST Manager Dialog Box (thanks to check boxes like 212) prior clicking on the "Edit" push-button 211 or on the "Instanciate" push-button 204. This can typically be done by displaying on the display device 106 a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device 105 on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step 805.
- At step 830, a test is performed to determine if the local variable *RSTM_select* is equal to 1 (one). If it is the case, then control is given to step 831; otherwise control is given to step 829.
- At step 831, a test is performed to determine the nature of the selected object, as specified by the "Type" field 2237 "NATURE" attribute 2241 of the corresponding record 2231 of the RSTMT table 2230.
 - If found equal to "TEMPLATE", then control is given to step 832;
 - If found equal to "RECTEMPLATE", then control is given to step 840;
 - otherwise control is given to step 833.
- At step 832, the **ST Instanciator** command is issued with passing one parameter equal to the "Name" field 2232 of the unique record 2231 of the RSTMT table 2230 whose "Type" field 2237 has the "SELECTED" attribute 2242 equal to "YES", and then control is given to step 834.
- At step 833, a warning message notification is issued for informing the user that a single ST object or a single RST object must be selected within the RST Manager Dialog Box (thanks to check boxes like 212) prior clicking on the "Instanciate" push-button 204. This can typically be done by displaying on the display device 106 a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device 105 on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step 805.
- At step 834, the RST Manager Dialog Box 200 is closed so that it disappears from the display device 106 and then control is given back to the initial step 801 for processing any future **RST Manager** command.
- At step 835, a warning message notification is issued for informing the user that at least one selected object to be deleted is referenced by another object. This can typically be done by displaying on the display device 106 a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Then the user is prompted to either cancel the current "Delete" operation, or to pursue it. This can typically be done by displaying on the display device 106 a prompting message in a pop-up window, but any other similar

means could be used instead, without departing from the spirit of the invention. Once the user has made his choice through conventional means such as clicking with the pointing device 105 on an "Cancel" or "Continue" push-button present within a prompting message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step 805 if the spreadsheet user decision is to cancel the "Delete" operation, or to step 809 if the spreadsheet user decision is to continue the "Delete" operation.

- 5 • At step 836, the **RE Editor** command is issued with passing one parameter ("NEW") and then control is given to step 834.
- 10 • At step 837, the **RST Editor** command is issued with passing one parameter ("NEW") and then control is given to step 834.
- At step 838, the **RE Editor** command is issued with passing one parameter equal to the "Name" field 2232 of the unique record 2231 of the RSTMT table 2230 whose "Type" field 2237 has the "SELECTED" attribute 2242 equal to "YES", and then control is given to step 834.
- 15 • At step 839, the **RST Editor** command is issued with passing one parameter equal to the "Name" field 2232 of the unique record 2231 of the RSTMT table 2230 whose "Type" field 2237 has the "SELECTED" attribute 2242 equal to "YES", and then control is given to step 834.
- 20 • At step 840, the **RST Instanciator** command is issued with passing one parameter equal to the "Name" field 2232 of the unique record 2231 of the RSTMT table 2230 whose "Type" field 2237 has the "SELECTED" attribute 2242 equal to "YES", and then control is given to step 834.
- At step 841, the value of the local variable *RSTM_child* is updated by swapping the values "YES" and "NO". Then control is given to step 805.

E2. EF Editor method

The method for creating or updating EF's or MEF's used in the preferred embodiment of the present invention is summarised in flowchart 900 of FIG 9. This method can be seen as the processing of the **EF Editor** command.

- 30 • At step 901, the method is in its default state, waiting for an event to initiate the process.
- At step 902, the **EF Editor** command is detected, as a result of an user action. This action can be for instance:
 - 35 • a specific combination of key on the keyboard 104, or
 - the click of the pointing device 105 on a specific button, or
 - any other similar means not further specified here.
- At step 903, the parameters of the command are retrieved. They correspond to:
 - 40 • a first mandatory parameter *EFE_name* which can either take a reserved value "NEW" or another value corresponding to a character string name, as found in the "Name" field 2232 of a record 2231 within the RSTMT table 2230; and
 - a second optional parameter *EFE_range* which can take only two predefined values "YES" and "NO". This second optional parameter must be present when the first mandatory parameter value differs from the "NEW".
- These two parameters are recorded as local variables.
- 45 • At step 904, some local variables are initialized: the local variable *EFE_meta* is set to the value "no", the local variable *EFE_size* is set to the value 8 (eight).
- At step 905, a test is performed to determine the value taken by the local variable *EFE_name*. If found equal to "NEW", then control is given to step 909; otherwise control is given to step 906.
- 50 • At step 906, the EFT table 700 is looked up to locate a record 701 whose "Name" field 702 is found equal to the value taken by the local variable *EFE_name*. If such a record is found, then control is given to step 908; otherwise control is given to step 907.

- At step 907, an exception handler is invoked to treat this "should not occur" condition. Such operation is implementation dependent and can take different forms such as the display on the display device 106 of an error message pop-up window. Then control is given to step 925.
- 5 • At step 908,
 - the local variable *EFE_meta* is set to the value "YES" or "NO" according to the value of the "META" attribute 708 within the "Type" field 707 of the record 701 found at step 906,
 - the local variable *EFE_size* is set to the value found in the "Column #" field 706 of the record 701 found at step 906, and
 - 10 • the memory location pointed by the "Description Ptr" field 704 of the record 701 found at step 906 is copied onto the clipboard.
 Then control is given to step 912.
- 15 • At step 909, a new name for the newly created EF or MEF is determined, according to a name string taking in a preferred embodiment of the present invention the form "New XX" where XX corresponds to a counter value ensuring the name uniqueness with respect to all the names previously defined and recorded in the "Name" fields 702, 712, 722, 2212 and 2222 found in the respective records 701, 711, 721, 2211 and 2221 of the respective tables EFT 700, EPT 710, STT 720, RET 2210 and RSST 2220. Any other similar conventional means could be used instead without departing from the spirit of the invention, as long as the uniqueness of the newly created name is ensured. Then the new name is recorded in the local variable *EFE_name*. Then memory space is allocated within the main memory 102 to later record the illustrative range of cells for the EF or MEF. This allocated memory is part of the memory space corresponding to the currently opened electronic spreadsheet file. Then a new record 701 is created in the EFT table 700, and this new record 701 is initialized as follows:
 - the "Name" field 702 is set to the value of the local variable *EFE_name* ;
 - the "Last Change Date" field 703 is set to the system time reference, as known by the central processor 101 ;
 - 30 • the "Description Ptr" field 704 is set to the memory location which has just been allocated ;
 - the "Row #" field 705 is set to the value 1 (as in the preferred embodiment of the present invention the ST's are managed in a 2D environment; this field would carry the number of defined rows for the created EF or MEF in a 3D environment) ;
 - 35 • the "Column #" field 706 is set to the value of the local variable *EFE_size* ; and
 - the "Type" field 707 is set as follows: the attribute "META" 708 is set equal to the value of the local variable *EFE_meta*, and the attribute "REFERENCED" 709 is initialized as follows:
 - The "OWN REFERENCE" (OR) subfield 709a is initialized with a prime number not yet assigned to any other OR subfield 709a, or 719a, or 729a, or 780a, or 2219a, or 2229a, or 2240a. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
 - The "FILIALION REFERENCE" (FR) subfield 709b is initialized with the value 1 (one).
 - The "INSTANCE REFERENCE" (IR) subfield 709c is initialized with the value 1 (one).
 - 45 • The "REFERENCED OBJECT" (RO) subfield 709d is initialized with the following formula, where the \mathcal{P} set corresponds to the set of ST's:

$$\text{RO} = \text{"YES"} \text{ if } \text{LCM}(\{\text{FR}_i\}_{i \in \mathcal{P}}) \bmod \text{OR} = 0;$$

$$\text{RO} = \text{"NO"} \text{ otherwise.}$$
 - 40 • The "SELECTED CHILDREN" (SC) subfield 709e is initialized with the following formula, where the \mathcal{S} set corresponds to the set of selected objects (having the "SELECTED" attribute 2242 equal to the value "YES" in the RSTMT table 2230):

$$\text{SC} = \text{"YES"} \text{ if } \text{LCM}(\{\text{FR}_i\}_{i \in \mathcal{S}}) \bmod \text{OR} = 0 \#_{\text{OR}} \# \text{EFE_name} \in \mathcal{S};$$

$$\text{SC} = \text{"NO"} \text{ otherwise.}$$
 - 50

Then control is given to step 910.

- At step 910, a test is performed to determine the value taken by the local variable *EFE_range*. If found equal to "YES", then control is given to step 911; otherwise control is given to step 912.
- 5 • At step 911, the currently selected range of cells is copied onto the clipboard and the local variable *EFE_size* is set equal to the number of columns of the selected range.
- At step 912, the "Editor Space" sheet 315 is made the current sheet and the content of the clipboard is pasted on this blank sheet at a fixed cell address 314 (address B2 in a preferred embodiment of the present invention, as shown on FIG 3), so that the user can visualize on the display device 106 an illustration of the EF or MEF.
- 10 • At step 913, the EF Editor Dialog Box 301 is displayed on the display device 106.
 - The label box 304 is initialized with the value of the local variable *EFE_name*.
 - The top (respectively bottom) option button 310 is filled with a black point if the local variable *EFE_meta* is found equal to "No" (respectively "YES").
 - 15 • The text box 306 is filled with the value of the local variable *EFE_size*.
 - The push-buttons "Save" 312 and "Save & Refresh" 308 are enabled if the local variable *EFE_size* is found equal to the "Column #" field 706 of the current record 701, or if the attribute "REFERENCED" 709 within the "Type" field 707 of this same record 701 is found with the subfield "REFERENCED OBJECT" 709d (RO) equal to "No", so that any future click with the pointing device 105 on one of these two push-buttons "Save" 312 and "Save & Refresh" 308 will be recognized as a valid event.
 - 20 • The push-buttons "Save" 312 and "Save & Refresh" 308 are disabled otherwise (local variable *EFE_size* is not found equal to the "Column #" field 706 of the current record 701, and the attribute "REFERENCED" 709 within the "Type" field 707 of this same record 701 is found with the subfield "REFERENCED OBJECT" 709d (RO) equal to "YES"), so that any future click with the pointing device 105 on one of these two push-buttons "Save" 312 and "Save & Refresh" 308 will not be recognized as an event.
- 25 • At step 914, the method is waiting for any user action on the EF Editor Dialog Box 301. Such user action is typically resulting from a click with the pointing device 105, but take other similar forms such as, but not limited to a specific combination of key on the keyboard 104, or any other similar means not further specified here.
- 30 • At step 915, a user action on the EF Editor Dialog Box 301 is detected.
 - If the user action is a click on the push-button "Save & Refresh" 308, then control is given to step 916;
 - 35 • if the user action is a click on the push-button "Save" 312, then control is given to step 917;
 - if the user action is a click on the push-button "Save As" 311, then control is given to step 918;
 - 40 • if the user action is a click on the push-button "Clear" 309, then control is given to step 919;
 - if the user action is a click on the spin button 307, then control is given to step 920;
 - if the user action is a click on one of the two option buttons 310, then control is given to step 921;
 - 45 • if the user action is a click on the push-button "Done" 303, or on the closing-window push-button 302, then control is given to step 925.
- At step 916, the EFT table 700 is updated and saved as part of the electronic spreadsheet file by refreshing the record 701 whose "Name" field 702 is equal to the local variable *EFE_name*. For this purpose,
 - 50 • the "Last Change Date" field 703 is set to the system time reference, as known by the central processor 101 ;
 - the "Column #" field 706 is set to the value of the local variable *EFE_size* ; and

- the "Type" field 707 is set as follows: the attribute "META" 708 is set equal to the value of the local variable *EFE_meta*.

In addition the range of cells 314 illustrating on the "Editor Space" sheet 315 the current definition of the EF or MEF is copied onto the memory location pointed by the "Description Ptr" field 704. Then control is given to step 922.

- At step 917, the EFT table 700 is updated and saved as part of the electronic spreadsheet file by refreshing the record 701 whose "Name" field 702 is equal to the local variable *EFE_name*. For this purpose,
 - the "Last Change Date" field 703 is set to the system time reference, as known by the central processor 101 ;
 - the "Column #" field 706 is set to the value of the local variable *EFE_size* ; and
 - the "Type" field 707 is set as follows: the attribute "META" 708 is set equal to the value of the local variable *EFE_meta*.

In addition the range of cells 314 illustrating on the "Editor Space" sheet 315 the current definition of the EF or MEF is copied onto the memory location pointed by the "Description Ptr" field 704. Then control is given to step 913.

- At step 918, a test is performed on the value found in the text box 305 to determine if it corresponds to a valid new name. The corresponding criteria are implementation dependent and may take different forms without departing from the spirit of the invention, as long as the new proposed name is a unique character string against all the already defined names recorded in the "Name" fields 702, 712, 722, 2212 and 2222. If validity and uniqueness are proven, then control is given to step 923; otherwise control is given to step 924.
- At step 919, the default attributes currently defined in the spreadsheet environment are applied to the "Editor Space" sheet 315, so that the displayed illustration of the EF or MEF receives these same default attributes. Then control is given to the step 913.
- At step 920, the local variable *EFE_size* is either incremented or decremented by 1 (one) according to the direction (up or down) specified by the pointing device 105 on the spin button 307, and as long as its value remains positive and less than or equal to an upper limit set equal to 254 in a preferred embodiment of the present invention. Then control is given to step 913.
- At step 921, the local variable *EFE_meta* is updated, so that its value becomes "YES" (respectively "NO") if the bottom (respectively top) option button 310 has been clicked on. Then control is given to step 913.
- At step 922, the **ST Refresh Manager** command is issued with the following parameters: *EFE_name*, "FORMAT" and then control is given to step 913.
- At step 923, memory space is allocated within the main memory 102 to later record the illustrative range of cells for the EF or MEF. This allocated memory is part of the memory space corresponding to the currently opened electronic spreadsheet file. Then a new record 701 is created in the EFT table 700 which is saved as part of the electronic spreadsheet file, and this new record 701 is initialized as follows:
 - the "Name" field 702 is set to the value found in the text box 305 and validated at step 918; this field 702 becoming then the new value of the *EFE_name* local variable;
 - the "Last Change Date" field 703 is set to the system time reference, as known by the central processor 101 ;
 - the "Description Ptr" field 704 is set to the memory location which has just been allocated ;
 - the "Row #" field 705 is set to the value 1 (as in the preferred embodiment of the present invention the ST's are managed in a 2D environment; this field would carry the number of defined rows for the created EF or MEF in a 3D environment) ;
 - the "Column #" field 706 is set to the value of the local variable *EFE_size* ; and

- the "Type" field **707** is set as follows: the attribute "META" **708** is set equal to the value of the local variable *EFE_meta*, and the attribute "REFERENCED" **709** is initialized as follows:

- The "OWN REFERENCE" (OR) subfield **709a** is initialized with a prime number not yet assigned to any other OR subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.

- The "FILATION REFERENCE" (FR) subfield **709b** is initialized with the value 1 (one).

- The "INSTANCE REFERENCE" (IR) subfield **709c** is initialized with the value 1 (one).

- The "REFERENCED OBJECT" (RO) subfield **709d** is initialized with the following formula, where the \mathcal{P} set corresponds to the set of ST's:

$$RO = \text{"YES"} \text{ if } \text{LCM}(\{FR_i\}_{i \in \mathcal{P}}) \bmod OR = 0;$$

$$RO = \text{"NO"} \text{ otherwise.}$$

- The "SELECTED CHILDREN" (SC) subfield **709e** is initialized with the following formula, where the \mathcal{S} set corresponds to the set of selected objects (having the "SELECTED" attribute **2242** equal to the value "YES" in the RSTMT table **2230**):

$$SC = \text{"YES"} \text{ if } \text{LCM}(\{FR_i\}_{i \in \mathcal{S}}) \bmod OR = 0 \text{ or } \# EFE_name \in \mathcal{S};$$

$$SC = \text{"NO"} \text{ otherwise.}$$

Then control is given to step **913**.

- At step **924**, a warning message notification is issued for informing the user that a valid and unique name must be specified in the text box **305** prior to clicking on the "Save As" push-button **311**. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device **105** on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **913**.
- At step **925**, the EF Editor Dialog Box **501** is closed so that it disappears from the display device **106**, then the "Editor Space" sheet **515** is removed from the displayed window so that it is replaced by the original sheet present at *EF Editor* invocation time. Finally control is given back to the initial step **901** for processing any future *EF Editor* command.

E3. EP Editor method

The method for creating or updating EP's or MEP's used in the preferred embodiment of the present invention is summarized in flowchart **1000** of FIG **10**. This method can be seen as the processing of the *EP Editor* command.

- At step **1001**, the method is in its default state, waiting for an event to initiate the process.

- At step **1002**, the *EP Editor* command is detected, as a result of an user action. This action can be for instance:

- a specific combination of key on the keyboard **104**, or
- the click of the pointing device **105** on a specific button, or
- any other similar means not further specified here.

- At step **1003**, the parameters of the command are retrieved. They correspond to:

- a first mandatory parameter *EPE_name* which can either take a reserved value "NEW" or another value corresponding to a character string name, as found in the "Name" field **2232** of a record **2231** within the RSTMT table **2230**; and
- a second optional parameter *EPE_range* which can take only two predefined values "YES" and "NO". This second optional parameter must be present when the first mandatory parameter value differs from the "NEW".

These two parameters are recorded as local variables.

- At step **1004**, some local variables are initialized: the local variable *EPE_meta* is set to the value "NO", the local variable *EPE_size* is set to the value 8 (eight).
- At step **1005**, a test is performed to determine the value taken by the local variable *EPE_name*. If found equal to "NEW", then control is given to step **1009**; otherwise control is given to step **1006**.
- At step **1006**, the EPT table **710** is looked up to locate a record **711** whose "Name" field **712** is found equal to the value taken by the local variable *EPE_name*. If such a record is found, then control is given to step **1008**; otherwise control is given to step **1007**.
- At step **1007**, an exception handler is invoked to treat this "should not occur" condition. Such operation is implementation dependent and can take different forms such as the display on the display device **106** of an error message pop-up window. Then control is given to step **1025**.
- At step **1008**,
 - the local variable *EPE_meta* is set to the value "YES" or "NO" according to the value of the "META" attribute **718** within the "Type" field **717** of the record **711** found at step **1006**,
 - the local variable *EPE_size* is set to the value found in the "Column #" field **716** of the record **711** found at step **1006**, and
 - the memory location pointed by the "Description Ptr" field **714** of the record **711** found at step **1006** is copied onto the clipboard and within the local variable *EPE_Desc*.
 Then control is given to step **1012**.
- At step **1009**, a new name for the newly created EP or MEP is determined, according to a name string taking in a preferred embodiment of the present invention the form "New XX" where XX corresponds to a counter value ensuring the name uniqueness with respect to all the names previously defined and recorded in the "Name" fields **702**, **712**, **722**, **2212** and **2222** found in the respective records **701**, **711**, **721**, **2211** and **2221** of the respective tables EFT **700**, EPT **710**, STT **720**, RET **2210** and RSST **2220**. Any other similar conventional means could be used instead without departing from the spirit of the invention, as long as the uniqueness of the newly created name is ensured. Then the new name is recorded in the local variable *EPE_name*. Then memory space is allocated within the main memory **102** to later record the illustrative range of cells for the EP or MEP. This allocated memory is part of the memory space corresponding to the currently opened electronic spreadsheet file. Then a new record **711** is created in the EPT table **710**, and this new record **711** is initialized as follows:
 - the "Name" field **712** is set to the value of the local variable *EPE_name* ;
 - the "Last Change Date" field **713** is set to the system time reference, as known by the central processor **101** ;
 - the "Description Ptr" field **714** is set to the memory location which has just been allocated ;
 - the "Row #" field **715** is set to the value 1 (as in the preferred embodiment of the present invention the ST's are managed in a 2D environment; this field would carry the number of defined rows for the created EP or MEP in a 3D environment) ;
 - the "Column #" field **716** is set to the value of the local variable *EPE_size* ; and
 - the "Type" field **717** is set as follows: the attribute "META" **718** is set equal to the value of the local variable *EPE_meta*, and the attribute "REFERENCED" **719** is initialized as follows:
 - The "OWN REFERENCE" (OR) subfield **719a** is initialized with a prime number not yet assigned to any other OR subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
 - The "FILIALION REFERENCE" (FR) subfield **719b** is initialized with the value 1 (one).
 - The "INSTANCE REFERENCE" (IR) subfield **719c** is initialized with the value 1 (one).

- The "REFERENCED OBJECT" (RO) subfield **719d** is initialized with the following formula, where the \mathcal{P} set corresponds to the set of ST's:

$$\text{RO} = \text{"YES"} \text{ if } \text{LCM}(\{\text{FR}_i\})_{i \in \mathcal{P}} \text{ Mod OR} = 0;$$

$$\text{RO} = \text{"No"} \text{ otherwise.}$$

- 5 • The "SELECTED CHILDREN" (SC) subfield **719e** is initialized with the following formula, where the \mathcal{S} set corresponds to the set of selected objects (having the "SELECTED" attribute **2242** equal to the value "YES" in the RSTMT table **2230**):

$$\text{SC} = \text{"YES"} \text{ if } \text{LCM}(\{\text{FR}_i\})_{i \in \mathcal{S}} \text{ Mod OR} = 0 \text{ \#OR\# } \text{EPE_name} \in \mathcal{S};$$

$$\text{SC} = \text{"No"} \text{ otherwise.}$$

10 Then control is given to step **1010**.

- At step **1010**, a test is performed to determine the value taken by the local variable *EPE_range*. If found equal to "YES", then control is given to step **1011**; otherwise control is given to step **1012**.
- 15 • At step **1011**, the currently selected range of cells is copied onto the clipboard and the local variable *EPE_size* is set equal to the number of columns of the selected range.
- At step **1012**, the "Editor Space" sheet **315** is made the current sheet and the content of the clipboard is pasted on this blank sheet at a fixed cell address **314** (address B2 in a preferred embodiment of the present invention, as shown on FIG 3), so that the user can visualize on the display device **106** an illustration of the EP or MEP.
- 20 • At step **1013**, the EP Editor Dialog Box **401** is displayed on the display device **106**.
 - The label box **404** is initialized with the value of the local variable *EPE_name*. The top (respectively bottom) option button **410** is filled with a black point if the local variable *EPE_meta* is found equal to "No" (respectively "YES").
 - The text box **406** is filled with the value of the local variable *EPE_size*.
 - 25 • The push-buttons "Save" **412** and "Save & Refresh" **408** are enabled if the local variable *EPE_size* is found equal to the "Column #" field **716** of the current record **711**, or if the attribute "REFERENCED" **719** within the "Type" field **717** of this same record **711** is found with the subfield "REFERENCED OBJECT" **719d** (RO) equal to "No", so that any future click with the pointing device **105** on one of these two push-buttons "Save" **412** and "Save & Refresh" **408** will be recognized as a valid event.
 - 30 • The push-buttons "Save" **412** and "Save & Refresh" **408** are disabled otherwise (local variable *EPE_size* is not found equal to the "Column #" field **716** of the current record **711**, and the attribute "REFERENCED" **719** within the "Type" field **717** of this same record **711** is found with the subfield "REFERENCED OBJECT" **719d** (RO) equal to "YES"), so that any future click with the pointing device **105** on one of these two push-buttons "Save" **412** and "Save & Refresh" **408** will not be recognized as an event.
 - 35 • At step **1014**, the method is waiting for any user action on the EP Editor Dialog Box **401**. Such user action is typically resulting from a click with the pointing device **105**, but take other similar forms such as, but not limited to a specific combination of key on the keyboard **104**, or any other similar means not further specified here.
 - 40 • At step **1015**, a user action on the EP Editor Dialog Box **401** is detected.
 - If the user action is a click on the push-button "Save & Refresh" **408**, then control is given to step **1016**;
 - 45 • if the user action is a click on the push-button "Save" **412**, then control is given to step **1017**;
 - if the user action is a click on the push-button "Save As" **411**, then control is given to step **1018**;
 - if the user action is a click on the push-button "Clear" **409**, then control is given to
 - 50 step **1019**;
 - if the user action is a click on the spin button **407**, then control is given to step **1020**;

- if the user action is a click on one of the two option buttons **410**, then control is given to step **1021**;
- if the user action is a click on the push-button "Done" **403**, or on the closing-window push-button **402**, then control is given to step **1025**.

- 5 • At step **1016**, the EPT table **710** is updated and saved as part of the electronic spreadsheet file by refreshing the record **711** whose "Name" field **712** is equal to the local variable *EPE_name*. For this purpose,
- the "Last Change Date" field **713** is set to the system time reference, as known by the central processor **101** ;
 - 10 ◦ the "Column #" field **716** is set to the value of the local variable *EPE_size* ; and
 - the "Type" field **717** is set as follows: the attribute "META" **718** is set equal to the value of the local variable *EPE_meta*.

In addition the range of cells **414** illustrating on the "Editor Space" sheet **415** the current definition of the EP or MEP is copied onto the memory location pointed by the "Description Ptr" field **714**. Then control is given to step **1022**.

- 15 • At step **1017**, the EPT table **710** is updated and saved as part of the electronic spreadsheet file by refreshing the record **711** whose "Name" field **712** is equal to the local variable *EPE_name*. For this purpose,
- the "Last Change Date" field **713** is set to the system time reference, as known by the central processor **101** ;
 - 20 • the "Column #" field **716** is set to the value of the local variable *EPE_size* ; and
 - the "Type" field **717** is set as follows: the attribute "META" **718** is set equal to the value of the local variable *EPE_meta*.

25 In addition the range of cells **414** illustrating on the "Editor Space" sheet **415** the current definition of the EP or MEP is copied onto the memory location pointed by the "Description Ptr" field **714**.

Then the local variable *EPE_desc* is updated with the current EP or MEP description, as recorded in the memory location pointed by the "Description Ptr" field **714**, and control is given to step **1013**.

- 30 • At step **1018**, a test is performed on the value found in the text box **405** to determine if this value corresponds to a valid new name. The corresponding criteria are implementation dependent and may take different forms without departing from the spirit of the invention, as long as the new proposed name is a unique character string against all the already defined names recorded in the "Name" fields **702**, **712**, **722**, **2212** and **2222**. If validity and uniqueness are proven, then control is given to step **1023**; otherwise control is given to step **1024**.

- At step **1019**, the default attributes currently defined in the spreadsheet environment are applied to the "Editor Space" sheet **415**, so that the displayed illustration of the EP or MEP receives these same default attributes. Then control is given to the step **1013**.

- 40 • At step **1020**, the local variable *EPE_size* is either incremented or decremented by 1 (one) according to the direction (up or down) specified by the pointing device **105** on the spin button **407**, and as long as its value remains positive and less than or equal to an upper limit set equal to 254 in a preferred embodiment of the present invention. Then control is given to step **1013**.

- 45 • At step **1021**, the local variable *EPE_meta* is updated, so that its value becomes "yes" (respectively "no") if the bottom (respectively top) option button **410** has been clicked on. Then control is given to step **1013**.

- At step **1022**, the **ST Refresh Manager** command is issued with the following parameters: *EPE_name*, "PROFILE", and *EPE_desc*. Then the local variable *EPE_desc* is updated with the current EP or MEP description, as recorded in the memory location pointed by the "Description Ptr" field **714** and then control is given to step **1013**.

- 50 • At step **1023**, memory space is allocated within the main memory **102** to later record the illustrative range of cells for the EP or MEP. This allocated memory is part of the

memory space corresponding to the currently opened electronic spreadsheet file. Then a new record **711** is created in the EPT table **710** which is saved as part of the electronic spreadsheet file, and this new record **711** is initialized as follows:

- the "*Name*" field **712** is set to the value found in the text box **405** and validated at step **1018**; this field **712** becoming then the new value of the *EPE_name* local variable;
- the "*Last Change Date*" field **713** is set to the system time reference, as known by the central processor **101**;
- the "*Description Ptr*" field **714** is set to the memory location which has just been allocated;
- the "*Row #*" field **715** is set to the value 1 (as in the preferred embodiment of the present invention the ST's are managed in a 2D environment; this field would carry the number of defined rows for the created EP or MEP in a 3D environment);
- the "*Column #*" field **716** is set to the value of the local variable *EPE_size*;
- the "*Type*" field **717** is set as follows: the attribute "*META*" **718** is set equal to the value of the local variable *EPE_meta*, and the attribute "*REFERENCED*" **719** is initialized as follows:
 - The "*OWN REFERENCE*" (OR) subfield **719a** is initialized with a prime number not yet assigned to any other OR subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
 - The "*FILIATION REFERENCE*" (FR) subfield **719b** is initialized with the value 1 (one).
 - The "*INSTANCE REFERENCE*" (IR) subfield **719c** is initialized with the value 1 (one).
 - The "*REFERENCED OBJECT*" (RO) subfield **719d** is initialized with the following formula, where the *P* set corresponds to the set of ST's:

$$\text{RO} = \text{"YES"} \text{ if } \text{LCM}(\{\text{FR}_i\})_{i \in P} \text{ Mod OR} = 0;$$

$$\text{RO} = \text{"NO"} \text{ otherwise.}$$
 - The "*SELECTED CHILDREN*" (SC) subfield **719e** is initialized with the following formula, where the *S* set corresponds to the set of selected objects (having the "*SELECTED*" attribute **2242** equal to the value "*YES*" in the RSTMT table **2230**):

$$\text{SC} = \text{"YES"} \text{ if } \text{LCM}(\{\text{FR}_i\})_{i \in S} \text{ Mod OR} = 0 \text{ \#OR\# } \text{EPE_name} \in S;$$

$$\text{SC} = \text{"NO"} \text{ otherwise.}$$

Then control is given to step **1013**.

- At step **1024**, a warning message notification is issued for informing the user that a valid and unique name must be specified in the text box **405** prior to clicking on the "Save As" push-button **411**. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device **105** on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **1013**.
- At step **1025**, the EP Editor Dialog Box **401** is closed so that it disappears from the display device **106**, then the "Editor Space" sheet **415** is removed from the display window so that it is replaced by the original sheet present at *EP Editor* invocation time. Finally control is given back to the initial step **1001** for processing any future *EP Editor* command.

E4. ST Editor method

The method for creating or updating ST's used in the preferred embodiment of the present invention is summarized in flowchart **1100** of FIG **11**. This method can be seen as the processing of the *ST Editor* command.

- At step **1101**, the method is in its default state, waiting for an event to initiate the process.

- At step 1102, the **ST Editor** command is detected, as a result of an user action. This action can be for instance:
 - a specific combination of key on the keyboard 104, or
 - the click of the pointing device 105 on a specific button, or
 - any other similar means not further specified here.
 - At step 1103, the parameter of the command is retrieved. It corresponds to a mandatory parameter *STE_name* which can either take a reserved value "NEW" or another value corresponding to a character string name, as found in the "Name" field 2232 of a record 2231 within the RSTMT table 2230. This parameter is recorded as a local variable.
 - At step 1104, some local variables are initialized: the local variable *STE_min* is set to the default value 1 (one), the local variable *STE_max* is set to the default value 255.
 - At step 1105, a test is performed to determine the value taken by the local variable *STE_name*. If found equal to "NEW", then control is given to step 1109; otherwise control is given to step 1106.
 - At step 1106, the STT table 720 is looked up to locate a record 721 whose "Name" field 722 is found equal to the value taken by the local variable *STE_name*. If such a record is found, then control is given to step 1108; otherwise control is given to step 1107.
 - At step 1107, an exception handler is invoked to treat this "should not occur" condition. Such operation is implementation dependent and can take different forms such as the display on the display device 106 of an error message pop-up window. Then control is given to step 1128.
 - At step 1108,
 - the local variable *STE_min* is set to the value found in the "Min Element #" field 725 of the record 721 found at step 1106,
 - the local variable *STE_max* is set to the value found in the "Max Element #" field 726 of the record 721 found at step 1106.
- Then the memory location pointed by the "Description Ptr" field 724 of the record 721 found at step 1106 (where is recorded the description of the ST according to the STDT table 760 illustrated in FIG 7D) is copied in a working buffer which in turns follows the same STDT table 760. This structure is then used to build on the clipboard within the main memory 102 a spreadsheet range of cells illustrating the ST definition copied in the working buffer. This construction is achieved by loading in the clipboard within the main memory 102 an ordered sequence of ranges of cells, each of them successively abiding by the EF (column 765) and the EP (column 764) definition corresponding to each pair of EF and EP names, starting with the first pair 761 up to the last one 763. Then control is given to step 1110.
- At step 1109, a new name for the newly created ST is determined, according to a name string taking in a preferred embodiment of the present invention the form "New XX" where XX corresponds to a counter value ensuring the name uniqueness with respect to all the names previously defined and recorded in the "Name" fields 702, 712, 722, 2212 and 2222 found in the respective records 701, 711, 721, 2211 and 2221 of the respective tables EFT 700, EPT 710, STT 720, RET 2210 and RSST 2220. Any other similar conventional means could be used instead without departing from the spirit of the invention, as long as the uniqueness of the newly created name is ensured. Then the new name is recorded in the local variable *STE_name*. Then memory space is allocated within the main memory 102 to later record the illustrative range of cells for the new ST. This allocated memory is part of the memory space corresponding to the currently opened electronic spreadsheet file and follows the STDT table 760 illustrated in FIG 7D. Then a new record 721 is created in the STT table 720, and this new record 721 is initialized as follows:
 - the "Name" field 722 is set to the value of the local variable *STE_name* ;
 - the "Last Change Date" field 723 is set to the system time reference, as known by the central processor 101 ;

- the "Description Ptr" field **724** is set to the memory location which has just been allocated ;
- the "Min Element #" field **725** is set to the value of the local variable *STE_min*;
- the "Max Element #" field **726** is set to the value of the local variable *STE_max*; and
- the "Type" field **727** is set as follows: the attribute "META" **728** is set equal to "NO", and the attribute "REFERENCED" **729** is initialized as follows:
 - The "OWN REFERENCE" (OR) subfield **729a** is initialized with a prime number not yet assigned to any other OR subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
 - The "FILIALION REFERENCE" (FR) subfield **729b** is initialized according to the following formula, where the \mathcal{F} set corresponds to the set of EF's, MEF's, EP's and MEP's constituting the new ST, according to the structure recorded in the "Description Ptr" field **724**:

$$FR = \prod_{i \in \mathcal{F}} OR_i \times LCM(\{FR_i\})_{i \in \mathcal{F}}$$

- The "INSTANCE REFERENCE" (IR) subfield **729c** is initialized with the value 1 (one).
- The "REFERENCED OBJECT" (RO) subfield **729d** is initialized with the following formula, where the \mathcal{P} set corresponds to the set of RE's and RME's:

$$RO = \text{"YES"} \text{ if } LCM(\{FR_i\})_{i \in \mathcal{F}} \bmod OR = 0;$$

$$RO = \text{"NO"} \text{ otherwise.}$$

- The "SELECTED CHILDREN" (SC) subfield **729e** is initialized with the following formula, where the \mathcal{S} set corresponds to the set of selected objects (having the "SELECTED" attribute **2242** equal to the value "YES" in the RSTMT table **2230**):

$$SC = \text{"YES"} \text{ if } LCM(\{FR_i\})_{i \in \mathcal{S}} \bmod OR = 0 \text{ \#OR\# } STE_name \in \mathcal{S};$$

$$SC = \text{"NO"} \text{ otherwise.}$$

Then a working buffer is allocated in main memory **102** and initialized with a default ST description which corresponds to a single pair **762** of default EF and default EP. This default ST description is then used to build on the clipboard within the main memory **102** a spreadsheet range of cells illustrating the new ST. This construction is achieved as explained at the end of the step **1108**. Then control is given to step **1110**.

- At step **1110**, the "Editor Space" sheet **515** is made the current sheet and this sheet is turned to write-protect mode while regular row insertion and deletion are disabled. Then the top left cell of the range of cells **514** is selected. Then the local variable *STE_format* is filled with the name of the EF or of the MEF corresponding to the row where is located the currently selected cell within the range of cells **514**. Finally the local variable *STE_profile* is filled with the name of the EP or of the MEP corresponding to the row where is located the currently selected cell within the range of cells **514**.
- At step **1111**, the ST Editor Dialog Box **501** is displayed on the display device **106**.
 - The label box **504** is initialized with the value of the local variable *STE_name*.
 - The text box **506** is filled with the value of the local variable *STE_min*.
 - The text box **509** is filled with the value of the local variable *STE_max*.
 - The combo box **511** is filled with the value of the local variable *STE_format*.
 - The combo box **510** is filled with the value of the local variable *STE_profile*.

Then the range of cells **514** is updated according to the description recorded in the memory clipboard: the content of the clipboard is pasted on this blank sheet at a fixed cell address **514** (address B2 in a preferred embodiment of the present invention, as shown on FIG 5), so that the user can visualize on the display device **106**, within the window **500** an illustration of the ST. Then a test is performed to check if all the EF's, EP's, MEF's and MEP's contributing to the ST definition illustrated by the range of cells **514**, have the same number of fields. If it is the case, then the two push-buttons "Save" **513** and "Save As" **512** are enabled, so that the click with the pointing device **105** on one of these two push-buttons is recognized as a valid event. Otherwise the two

push-buttons "Save" 513 and "Save As" 512 are disabled, so that the click with the pointing device 105 on one of these two push-buttons is not recognized as a valid event.

- At step 1112, the method is waiting for any user action on the ST Editor Dialog Box 501. Such user action is typically resulting from a click with the pointing device 105, but take other similar forms such as, but not limited to a specific combination of key on the keyboard 104, or any other similar means not further specified here.
- At step 1113, a user action on the ST Editor Dialog Box 501 is detected.
 - If the user action is a click on the push-button "Save" 513, then control is given to step 1116;
 - if the user action is a click on the push-button "Save As" 512, then control is given to step 1119;
 - if the user action is a click on the push-button "Add" 517, then control is given to step 1124;
 - if the user action is a click on the push-button "Delete" 518, then control is given to step 1125;
 - if the user action is a click on the push-button "Up" 519 or on the push-button "Down" 520, then control is given to step 1126;
 - if the user action is an update of the combo box 511, then control is given to step 1114;
 - if the user action is an update of the combo box 510, then control is given to step 1115;
 - if the user action is a click on the spin button 507, then control is given to step 1122;
 - if the user action is a click on the spin button 508, then control is given to step 1123;
 - if the user action is a click on the push-button "Done" 503, or on the closing-window push-button 502, then control is given to step 1128.
- At step 1114, the ST description is updated in the working buffer by replacing by the EF or MEF name found in the text box 511 the previous EF or MEF specification corresponding to the element or meta-element illustrated by the currently selected cell within the range of cells 514. Then the local variable *STE_format* is also set equal to the name found in the text box 511. Then control is given to step 1111.
- At step 1115, the ST description is updated in the working buffer by replacing by the EP or MEP name found in the text box 510 the previous EP or MEP specification corresponding to the element or meta-element illustrated by the currently selected cell within the range of cells 514. Then the local variable *STE_profile* is also set equal to the name found in the text box 510. Then control is given to step 1111.
- At step 1116, a test is performed to check if the currently edited ST is already referenced by an existing RE or RME or is already instantiated as a STI. For this purpose is considered the "REFERENCED" attribute 729 within the "Type" field 727 of the record 721 within the STT table 720 whose "Name" field 722 is equal to the local variable *STE_name*. If the value of the "REFERENCED OBJECT" (RO) subfield 729d is equal to "NO" and if the value of the "INSTANCE REFERENCE" (IR) subfield 729c is equal to 1 (one), then control is given to step 1117; otherwise control is given to step 1118.
- At step 1117, the STT table 720 is updated by refreshing the record 721 whose "Name" field 722 is equal to the local variable *STE_name*. For this purpose,
 - the "Last Change Date" field 723 is set to the system time reference, as known by the central processor 101 ;
 - the "Min Element #" field 725 is set to the value of the local variable *STE_min*;
 - the "Max Element #" field 726 is set to the value of the local variable *STE_max*.
- The current description of the ST, as illustrated by the range of cells 514, as recorded in the working buffer, and following the STDt table 760 is copied onto the memory location pointed by the "Description Ptr" field 724.
- The "Type" field 727 is updated as the "FILIAION REFERENCE" (FR) subfield 729b of the "REFERENCED" attribute 729 is automatically updated thanks to its definition formula

depending on the set of EF's, MEF's, EP's and MEP's belonging to the STDT table **760** pointed by the "*Description Ptr*" field **724**.

- For each EF name or MEF name found in the column **765** of this STDT table **760**, the EFT table **700** is automatically updated within the corresponding records **701** whose "*Name*" field **702** matches this element or MEF name, as the subfield "REFERENCED OBJECT" (RO) **709d** (within the "REFERENCED" attribute **709**) is recalculated according to its definition formula.
- For each EP name or MEP name found in the column **764** of this STDT table **760**, the EPT table **710** is automatically updated within the corresponding records **711** whose "*Name*" field **712** matches this element or MEP name, as the subfield "REFERENCED OBJECT" (RO) **719d** (within the "REFERENCED" attribute **719**) is recalculated according to its definition formula.

Then control is given to step **1111**.

- At step **1118**, a warning message notification is issued for informing the user that the edited ST is already referenced by a RE or RME or is already instanciated as an existing STI. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Then the user is prompted to either cancel the current "Save" operation, or to pursue it. This can typically be done by displaying on the display device **106** a prompting message in a pop-up window, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has made his choice through conventional means such as clicking with the pointing device **105** on an "Cancel" or "Continue" push-button present within a prompting message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **1111** if the spreadsheet user decision is to cancel the operation, or to step **1117** if the spreadsheet user decision is to continue the operation.
- At step **1119**, a test is performed on the value found in the text box **505** to determine if it corresponds to a valid new name. The corresponding criteria are implementation dependent and may take different forms without departing from the spirit of the invention, as long as the new proposed name is a unique character string against all the already defined names recorded in the "*Name*" fields **702**, **712**, **722**, **2212** and **2222**. If validity and uniqueness are proven, then control is given to step **1120**; otherwise control is given to step **1121**.
- At step **1120**, memory space is allocated within the main memory **102** to later record the descriptor of the ST. This allocated memory is part of the memory space corresponding to the currently opened electronic spreadsheet file. Then a new record **721** is created in the STT table **720**, and this new record **721** is initialized as follows:
 - the "*Name*" field **722** is set to the value found in the text box **505** and validated at step **1119**; this field **722** becoming then the new value of the *STE_name* local variable;
 - the "*Last Change Date*" field **723** is set to the system time reference, as known by the central processor **101** ;
 - the "*Description Ptr*" field **724** is set to the memory location which has just been allocated ;
 - the "*Min Element #*" field **725** is set to the value of the local variable *STE_min*;
 - the "*Max Element #*" field **726** is set to the value of the local variable *STE_max* ;
 - the current description of the ST, as illustrated by the range of cells **514**, as recorded in the working buffer, and following the STDT table **760** is copied onto the memory location pointed by the "*Description Ptr*" field **724**.
 - the "*Type*" field **727** is set as follows: the attribute "META" **728** is set equal to "No", and the attribute "REFERENCED" **729** is initialized as follows:

- The "OWN REFERENCE" (OR) subfield **729a** is initialized with a prime number not yet assigned to any other OR subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
- 5 • The "FILIALION REFERENCE" (FR) subfield **729b** is initialized according to the following formula, where the \mathcal{F} set corresponds to the set of EF's, MEF's, EP's and MEP's constituting the new ST, according to the structure recorded in the "Description Ptr" field **724**:

$$FR = \prod_{i \in \mathcal{F}} OR_i \times LCM(\{FR_i\})_{i \in \mathcal{F}}$$
- 10 • The "INSTANCE REFERENCE" (IR) subfield **729c** is initialized with the value 1 (one).
- The "REFERENCED OBJECT" (RO) subfield **729d** is initialized with the following formula, where the \mathcal{P} set corresponds to the set of RE's and RME's:

$$RO = \text{"YES"} \text{ if } LCM(\{FR_i\})_{i \in \mathcal{P}} \bmod OR = 0;$$

$$RO = \text{"NO"} \text{ otherwise.}$$
- 15 • The "SELECTED CHILDREN" (SC) subfield **729e** is initialized with the following formula, where the \mathcal{S} set corresponds to the set of selected objects (having the "SELECTED" attribute **2242** equal to the value "YES" in the RSTMT table **2230**):

$$SC = \text{"YES"} \text{ if } LCM(\{FR_i\})_{i \in \mathcal{S}} \bmod OR = 0 \#OR\# STE_name \in \mathcal{S};$$

$$SC = \text{"NO"} \text{ otherwise.}$$
- 20 • For each EF name or MEF name found in the column **765** of this STDT table **760**, the EFT table **700** is automatically updated within the corresponding records **701** whose "Name" field **702** matches this element or MEF name, as the subfield "REFERENCED OBJECT" (RO) **709d** (within the "REFERENCED" attribute **709**) is recalculated according to its definition formula.
- 25 • For each EP name or MEP name found in the column **764** of this STDT table **760**, the EPT table **710** is automatically updated within the corresponding records **711** whose "Name" field **712** matches this element or MEP name, as the subfield "REFERENCED OBJECT" (RO) **719d** (within the "REFERENCED" attribute **719**) is recalculated according to its definition formula.
- 30 Then control is given to step **1111**.
- At step **1121**, a warning message notification is issued for informing the user that a valid and unique name must be specified in the text box **505** prior to clicking on the "Save As" push-button **512**. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device **105** on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **1111**.
- 35 • At step **1122**, the local variable STE_min is either incremented or decremented by 1 (one) according to the direction (up or down) specified by the pointing device **105** on the spin button **507**, and as long as its value remains positive and less than or equal to both an upper limit set equal to 254 in a preferred embodiment of the present invention and to the value shown in the text box **509**. Then control is given to step **1111**.
- 40 • At step **1123**, the local variable STE_max is either incremented or decremented by 1 (one) according to the direction (up or down) specified by the pointing device **105** on the spin button **508**, and as long as its value remains positive, greater than the value shown in the text box **506** and less than or equal to an upper limit set equal to 254 in a preferred embodiment of the present invention. Then control is given to step **1111**.
- 45 • At step **1124**, a new row is inserted in the range of cells **514** illustrating the edited ST, above the row where the last selected cell was previously located.
- 50 • Then the left most cell located on the new row within the range of cells **514** is selected. Then the ST definition is updated in the working buffer by introducing a new

meta-element which is described, like the other ones, by a couple (MEF 765, MEP 764) which defaults to a couple of default MEF and default MEP, which are also respectively assigned to the local variable *STE_format* and *STE_profile*. In addition the current description of the ST, as illustrated by the range of cells 514, as recorded in the working buffer, and following the STDT table 760 is copied onto the memory location pointed by the "Description Ptr" field 724. Then control is given to step 1111.

- 5
 - At step 1125, the row containing the selected cell is removed from the range of cells 514. Then the left most cell located within the range of cells 514 on the row representing the element defined within the edited ST is selected. Then the ST definition is updated by removing the deleted meta-element which was described by a couple (MEF, MEP). In addition the current description of the ST, as illustrated by the range of cells 514, as recorded in the working buffer, and following the STDT table 760 is copied onto the memory location pointed by the "Description Ptr" field 724. Then control is given to step 1127.
- 10
 - At step 1126, the current cell within the "Editor Space" sheet 515 is respectively moved up or down if the spreadsheet user has clicked with the pointing device 105 on the "Up" push-button 519, or on the "Down" push-button 520, and also if this movement does not move the current cell away from the range of cells 514 illustrating the ST.
- 15
 - At step 1127, the local variables *STE_format* and *STE_profile* are respectively set equal to the name of the EF or MEF and to the name of the EP or MEP corresponding to the element or the meta-element illustrated by the currently selected cell within the range of cells 514. Then control is given to step 1111.
- 20
 - At step 1128, the ST Editor Dialog Box 501 is closed so that it disappears from the display device 106, then the "Editor Space" sheet 515 is removed from the display window so that it is replaced by the original sheet present at *EP Editor* invocation time. All the means which were temporarily disabled while the "Editor Space" sheet 515 was displayed are now enabled again. Finally control is given back to the initial step 1101 for processing any future *ST Editor* command.

E5. RST Editor method

- 30 The method for creating or updating RST's used in the preferred embodiment of the present invention is summarized in flowchart 1230 of FIG 12. This method can be seen as the processing of the *RST Editor* command.
 - At step 1231, the method is in its default state, waiting for an event to initiate the process.
 - 35
 - At step 1232, the *RST Editor* command is detected, as a result of an user action. This action can be for instance:
 - a specific combination of key on the keyboard 104, or
 - the click of the pointing device 105 on a specific button, or
 - any other similar means not further specified here.
 - 40
 - At step 1233, the parameter of the command is retrieved. It corresponds to a mandatory parameter *RSTE_name* which can either take a reserved value "NEW" or another value corresponding to a character string name, as found in the "Name" field 2232 of a record 2231 within the RSTMT table 2230. This parameter is recorded as a local variable.
 - 45
 - At step 1234, some local variables are initialized: the local variable *RSTE_min* is set to the default value 1 (one), the local variable *RSTE_max* is set to the default value 16.
 - At step 1235, a test is performed to determine the value taken by the local variable *RSTE_name*. If found equal to "NEW", then control is given to step 1239; otherwise control is given to step 1236.
 - 50
 - At step 1236, the RSTT table 2220 is looked up to locate a record 2221 whose "Name" field 2222 is found equal to the value taken by the local variable *RSTE_name*. If such a record is found, then control is given to step 1238; otherwise control is given to step 1237.

- At step **1237**, an exception handler is invoked to treat this “should not occur” condition. Such operation is implementation dependent and can take different forms such as the display on the display device **106** of an error message pop-up window. Then control is given to the initial step **1231** for processing any future **RST Editor** command.
- 5 • At step **1238**,
 - the local variable *RSTE_min* is set to the value found in the “*Min Element #*” field **2225** of the record **2221** found at step **1236**,
 - the local variable *RSTE_max* is set to the value found in the “*Max Element #*” field **2226** of the record **2221** found at step **1236**.
- 10 Then the memory location pointed by the “*Description Ptr*” field **2224** of the record **2221** found at step **1236** (where is recorded the description of the RST according to the RSTDT table **2250** illustrated in FIG **17D**) is copied in a working buffer which in turns follows the same RSTDT table **2250**. This structure is then used to build on the clipboard within the main memory **102** a spreadsheet range of cells illustrating the RST definition
- 15 copied in the working buffer, each cell successively corresponding to RE or RME names, starting with the first name **2251** up to the last one **2253**. Then control is given to step **1240**.
- At step **1239**, a new name for the newly created RST is determined, according to a name string taking in a preferred embodiment of the present invention the form “New XX” where XX corresponds to a counter value ensuring the name uniqueness with respect to all the names previously defined and recorded in the “*Name*” fields **702**, **712**, **722**, **2212** and **2222** found in the respective records **701**, **711**, **721**, **2211** and **2221** of the respective tables EFT **700**, EPT **710**, STT **720**, RET **2210** and RSST **2220**. Any other similar conventional means could be used instead without departing from the spirit of the invention, as long as the uniqueness of the newly created name is ensured. Then the new name is recorded in the local variable *RSTE_name*. Then memory space is allocated within the main memory **102** to later record the illustrative range of cells for the new RST. This allocated memory is part of the memory space corresponding to the currently opened electronic spreadsheet file and follows the RSTDT table **2250** illustrated in FIG **17D**. Then a new record **2221** is created in the RSTT table **2220**, and this new record **2221** is initialized as follows:
 - the “*Name*” field **2222** is set to the value of the local variable *RSTE_name* ;
 - the “*Last Change Date*” field **2223** is set to the system time reference, as known by the central processor **101** ;
 - 35 • the “*Description Ptr*” field **2224** is set to the memory location which has just been allocated ;
 - the “*Min Element #*” field **2225** is set to the value of the local variable *RSTE_min*;
 - the “*Max Element #*” field **2226** is set to the value of the local variable *RSTE_max* ;
 - 40 • the “*Type*” field **2227** is set as follows: the attribute “*META*” **2228** is set equal to “No”, and the attribute “*REFERENCED*” **2229** is initialized as follows:
 - The “*OWN REFERENCE*” (OR) subfield **2229a** is initialized with a prime number not yet assigned to any other OR subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
 - 45 • The “*FILIATION REFERENCE*” (FR) subfield **2229b** is initialized according to the following formula, where the \mathcal{F} set corresponds to the set of RE's and RME constituting the new RST, according to the structure recorded in the “*Description Ptr*” field **2224**:

$$FR = \prod_{i \in \mathcal{F}} OR_i \times LCM(\{FR_i\})_{i \in \mathcal{F}}$$
 - 50 • The “*INSTANCE REFERENCE*” (IR) subfield **2229c** is initialized with the value 1 (one).
 - The “*REFERENCED OBJECT*” (RO) subfield **2229d** is initialized with the value “No”.

- The "SELECTED CHILDREN" (SC) subfield **2229e** is initialized with the following formula, where the S set corresponds to the set of selected objects (having the "SELECTED" attribute **2242** equal to the value "YES" in the RSTMT table **2230**):

$SC = \text{"YES"} \text{ if } LCM(\{FR_i\})_{i \in S} \bmod OR = 0 \text{ \#OR\# } RSTE_name \in S,$

$SC = \text{"NO"} \text{ otherwise.}$

Then a working buffer is allocated in main memory **102** and initialized with a default RST description which corresponds to a RE **2252**. This default RST description is then used to build on the clipboard within the main memory **102** a spreadsheet range of cells illustrating the new RST. This construction is achieved as explained at the end of the step **1238**. Then control is given to step **1240**.

- At step **1240**, the "Editor Space" sheet **615** is made the current sheet and this sheet is turned to write-protect mode while regular row insertion and deletion are disabled. Then the top left cell of the range of cells **614** is selected. Then the local variable RE_name is filled with the name of the RE corresponding to the row where is located the currently selected cell within the range of cells **614**.

- At step **1241**, the RST Editor Dialog Box **601** is displayed on the display device **106**.

- The label box **604** is initialized with the value of the local variable $RSTE_name$.
- The text box **606** is filled with the value of the local variable $RSTE_min$.
- The text box **609** is filled with the value of the local variable $RSTE_max$.

- The combo box **610** is filled with the value of the local variable RE_name .

Then the range of cells **614** is updated according to the description recorded in the memory clipboard: the content of the clipboard is pasted on this blank sheet at a fixed cell address **614** (address B2 in a preferred embodiment of the present invention, as shown on FIG 6), so that the user can visualize on the display device **106**, within the window **611** an illustration of the ST. Then a test is performed to check if all the RE's and RME's contributing to the RST definition illustrated by the range of cells **614**, have the same number of fields. If it is the case, then the two push-buttons "Save" **613** and "Save As" **612** are enabled, so that the click with the pointing device **105** on one of these two push-buttons is recognized as a valid event. Otherwise the two push-buttons "Save" **613** and "Save As" **612** are disabled, so that the click with the pointing device **105** on one of these two push-buttons is not recognized as a valid event.

- At step **1242**, the method is waiting for any user action on the RST Editor Dialog Box **601**. Such user action is typically resulting from a click with the pointing device **105**, but take other similar forms such as, but not limited to a specific combination of key on the keyboard **104**, or any other similar means not further specified here.

- At step **1243**, a user action on the RST Editor Dialog Box **601** is detected.

- If the user action is a click on the push-button "Save" **613**, then control is given to step **1246**;

- if the user action is a click on the push-button "Save As" **612**, then control is given to step **1249**;

- if the user action is a click on the push-button "Add" **617**, then control is given to step **1254**;

- if the user action is a click on the push-button "Delete" **618**, then control is given to step **1255**;

- if the user action is a click on the push-button "Up" **619** or on the push-button "Down" **616**, then control is given to step **1256**;

- if the user action is an update of the combo box **610**, then control is given to step **1244**;

- if the user action is a click on the spin button **607**, then control is given to step **1252**;

- if the user action is a click on the spin button **608**, then control is given to step **1253**;

- if the user action is a click on the push-button "Done" **603**, or on the closing-window push-button **602**, then control is given to step **1258**.

- At step **1244**, the ST description is updated in the working buffer by replacing by the RE or RME name found in the combo box **610** the previous RE or RME name corresponding to the RE or RME illustrated by the currently selected cell within the range of cells **614**. Then the local variable *RE_name* is also set equal to the name found in the combo box **610**. Then control is given to step **1241**.
- At step **1246**, a test is performed to check if the currently edited RST is already referenced by an existing RSTI. For this purpose is considered the value of the "REFERENCED" attribute **2229** within the "Type" field **2227** of the record **2221** within the RSTT table **2220** whose "Name" field **2222** is equal to the local variable *RSTE_name*. If the value of the "INSTANCE REFERENCE" (IR) subfield **2229c** is equal to 1 (one), then control is given to step **1247**; otherwise control is given to step **1248**.
- At step **1247**, the RSTT table **2220** is updated by refreshing the record **2221** whose "Name" field **2222** is equal to the local variable *RSTE_name*. For this purpose,
 - the "Last Change Date" field **2223** is set to the system time reference, as known by the central processor **101** ;
 - the "Min Element #" field **2225** is set to the value of the local variable *RSTE_min*;
 - the "Max Element #" field **2226** is set to the value of the local variable *RSTE_max*.
 - The current description of the RST, as illustrated by the range of cells **614**, as recorded in the working buffer, and following the RSTDT table **2250** is copied onto the memory location pointed by the "Description Ptr" field **2224**.
 - The "Type" field **2227** is updated as the "FILATION REFERENCE" (FR) subfield **2229b** of the "REFERENCED" attribute **2229** is automatically updated thanks to its definition formula depending on the set of RE's, and RME's belonging to the RSTDT table **2250** pointed by the "Description Ptr" field **2224**.
 - For each RE name or RME name found in the column **2254** of this RSTDT table **2250**, the RET table **2210** is automatically updated within the corresponding record **2211** whose "Name" field **2212** matches this RE or RME name, as the subfield "REFERENCED OBJECT" (RO) **2219d** (within the "REFERENCED" attribute **2219**) is recalculated according to its definition formula.
- At step **1248**, a warning message notification is issued for informing the user that the edited RST is already instanciated as a RSTI. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Then the user is prompted to either cancel the current "Save" operation, or to pursue it. This can typically be done by displaying on the display device **106** a prompting message in a pop-up window, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has made his choice through conventional means such as clicking with the pointing device **105** on an "Cancel" or "Continue" push-button present within a prompting message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **1241** if the spreadsheet user decision is to cancel the operation, or to step **1247** if the spreadsheet user decision is to continue the operation.
- At step **1249**, a test is performed on the value found in the text box **605** to determine if it corresponds to a valid new name. The corresponding criteria are implementation dependent and may take different forms without departing from the spirit of the invention, as long as the new proposed name is a unique character string against all the already defined names recorded in the "Name" fields **702**, **712**, **722**, **2212** and **2222**. If validity and uniqueness are proven, then control is given to step **1250**; otherwise control is given to step **1251**.
- At step **1250**, memory space is allocated within the main memory **102** to later record the descriptor of the RST. This allocated memory is part of the memory space corresponding to the currently opened electronic spreadsheet file. Then a new record

2221 is created in the RSTT table **2220**, and this new record **2221** is initialized as follows:

- the “Name” field **2222** is set to the value found in the text box **605** and validated at step **1249**; this field **2222** becoming then the new value of the *RSTE_name* local variable;
- the “Last Change Date” field **2223** is set to the system time reference, as known by the central processor **101** ;
- the “Description Ptr” field **2224** is set to the memory location which has just been allocated ;
- the “Min Element #” field **2225** is set to the value of the local variable *RSTE_min*;
- the “Max Element #” field **2226** is set to the value of the local variable *RSTE_max* ; and
- the “Type” field **2227** is set as follows: the attribute “META” **2228** is set equal to “No”, and the attribute “REFERENCED” **2229** is initialized as follows:

- The “OWN REFERENCE” (OR) subfield **2229a** is initialized with a prime number not yet assigned to any other OR subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
- The “FILIALION REFERENCE” (FR) subfield **2229b** is initialized according to the following formula, where the \mathcal{F} set corresponds to the set of RE's and RME constituting the new RST, according to the structure recorded in the “Description Ptr” field **2224**:

$$FR = \prod_{i \in \mathcal{F}} OR_i \times LCM(\{FR_i\})_{i \in \mathcal{F}}$$

- The “INSTANCE REFERENCE” (IR) subfield **2229c** is initialized with the value 1 (one).
- The “REFERENCED OBJECT” (RO) subfield **2229d** is initialized with the value “No”.
- The “SELECTED CHILDREN” (SC) subfield **2229e** is initialized with the following formula, where the \mathcal{S} set corresponds to the set of selected objects (having the “SELECTED” attribute **2242** equal to the value “YES” in the RSTMT table **2230**):

$$SC = \text{“YES” if } LCM(\{FR_i\})_{i \in \mathcal{S}} \bmod OR = 0 \text{ \#OR\# } RSTE_name \in \mathcal{S},$$

$$SC = \text{“No” otherwise.}$$

- The current description of the RST, as illustrated by the range of cells **614**, as recorded in the working buffer, and following the RSTDT table **2250** is copied onto the memory location pointed by the “Description Ptr” field **2224**.
- For each RE name or RME name found in the column **2254** of this RSTDT table **2250**, the RET table **2210** is automatically updated within the corresponding record **2211** whose “Name” field **2212** matches this RE or RME name, as the subfield “REFERENCED OBJECT” (RO) **2229d** (within the “REFERENCED” attribute **2219**) is recalculated according to its definition formula.
- At step **1251**, a warning message notification is issued for informing the user that a valid and unique name must be specified in the text box **605** prior to clicking on the “Save As” push-button **612**. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device **105** on an “OK” push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **1241**.
- At step **1252**, the local variable *RSTE_min* is either incremented or decremented by 1 (one) according to the direction (up or down) specified by the pointing device **105** on the spin button **607**, and as long as its value remains positive and less than or equal to both an upper limit set equal to 254 in a preferred embodiment of the present invention and to the value shown in the text box **609**. Then control is given to step **1241**.

- At step **1253**, the local variable *RSTE_max* is either incremented or decremented by 1 (one) according to the direction (up or down) specified by the pointing device **105** on the spin button **608**, and as long as its value remains positive, greater than the value shown in the text box **606** and less than or equal to an upper limit set equal to 254 in a preferred embodiment of the present invention. Then control is given to step **1241**.
- At step **1254**, a new row is inserted in the range of cells **614** illustrating the edited RST, above the row where the last selected cell was previously located. Then the left most cell located on the new row within the range of cells **614** is selected. Then the RST definition is updated in the working buffer by introducing a new RME which is identified, like the other ones, by a name, which is also assigned to the local variable *RE_name*. In addition the current description of the RST, as illustrated by the range of cells **614**, as recorded in the working buffer, and following the RSTDT table **2250** is copied onto the memory location pointed by the "Description Ptr" field **2224**. Then control is given to step **1241**.
- At step **1255**, the row containing the selected cell is removed from the range of cells **614**, so that the next RE or meta-element gets selected. Then the RST definition is updated by removing the deleted RME which was identified by its name. In addition the current description of the RST, as illustrated by the range of cells **614**, as recorded in the working buffer, and following the RSTDT table **2250** is copied onto the memory location pointed by the "Description Ptr" field **2224**. Then control is given to step **1257**.
- At step **1256**, the current cell within the "Editor Space" sheet **615** is respectively moved up or down if the spreadsheet user has clicked with the pointing device **105** on the "Up" push-button **619**, or on the "Down" push-button **616**, and also if this movement does not move the current cell away from the range of cells **614** illustrating the RST.
- At step **1257**, the local variable *RE_name* is set equal to the name of the RE or RME corresponding to either the RE or the RME identified by the currently selected cell within the range of cells **614**. Then control is given to step **1241**.
- At step **1258**, the RST Editor Dialog Box **601** is closed so that it disappears from the display device **106**, then the "Editor Space" sheet **615** is removed from the display window so that it is replaced by the original sheet present at **RST Editor** invocation time. All the means which were temporarily disabled while the "Editor Space" sheet **615** was displayed are now enabled again. Finally control is given back to the initial step **1231** for processing any future **RST Editor** command.

E6. ST Instanciator method

The method for creating a STI abiding by a defined ST used in the preferred embodiment of the present invention is summarized in flowchart **1400** of FIG **14A** and FIG **14B**, where the later corresponds to the **CreateSTI** routine. This method can be seen as the processing of the **ST Instanciator** command.

- At step **1401**, the method is in its default state, waiting for an event to initiate the process.
- At step **1402**, the **ST Instanciator** command is detected, as a result of a user action. This action can be for instance a specific combination of key on the keyboard **104**, or the click of the pointing device **105** on a specific button, or any other similar means not further specified here.
- At step **1403**, a test is performed to check if the currently selected cell is contained within a sheet where a RSTI is present. This test can be done by parsing the RSTIT table **2260** to identify any record **2261** whose *Address* field **2262** corresponds to the same sheet as the currently selected cell. If it is the case, then control is given to step **1404** ; otherwise control is given to step **1405**.

- At step **1404**, a warning message notification is issued for informing the user that a STI cannot be individually created on a sheet where a RSTI already exists. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device **105** on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **1401**.
- At step **1405**, the command parameter *ST_name* is first retrieved: it corresponds to the name of the ST that the STI to be created will abide by. This parameter *ST_name* is used to parse the STT table **720** in order to find the record **721** whose "Name" field **722** matches the parameter *ST_name*. Once this record **721** is found, its fields "Min Element #" **725** and "Max Element #" **726** are respectively memorized as local variables *STI_min* and *STI_max*. Then its field "Description Ptr" **724** is used to determine, according to the referenced STD table **760**, the number of meta-elements defined within the ST, and the number of cells defined within each element or meta-element member of the ST. The first number is memorized in a local variable *STI_meta*, and the second number is memorized in a local variable *STI_width* **1325** (representing the number of columns of the future STI).
 Then another local variable *STI_element* is initialized with the value taken by *STI_min*.
 Then another local variable *STI_critical* is initialized with the default value "YES".
 Then another local variable *STI_sheet_width* **1321** is initialized with the total number of columns in the current sheet **1320**.
- Then another local variable *STI_sheet_height* **1322** is initialized with the total number of rows in the current sheet **1320**.
 Then another local variable *STI_mode* is initialized with the value OVERLAY.
- At step **1406**, some other local variables are first built or updated. The position of the currently selected cell **1327** is first represented by the local variables *STI_offset_width* **1323** and *STI_offset_height* **1324** corresponding respectively to the number of columns and of rows between the top left cell of the current sheet **1320** and the currently selected cell **1327**. Then the number of rows of the future STI is represented by the local variable *STI_height* **1326**, computed as the sum of the local variables *STI_meta* and *STI_element*. Second some working ranges of cells are determined through the evaluation of their addresses. The range of cells *STI_range* **1328** corresponding to the future STI is first determined as the range of cells with the currently selected cell **1327** as the top left cell, and with a number of rows and columns respectively equal to *STI_height* **1326** and *STI_width* **1325**.
 Then the range of cells *STI_horizontal_flushed_range* **1330** is determined as the range of cells sharing the same rows as *STI_range* **1328**, and occupying the *STI_width* **1325** rightmost columns of the current sheet **1320**.
 Then the range of cells *STI_horizontal_kept_range* **1329** is determined as the range of cells sharing the same rows as *STI_range* **1328**, and occupying the columns located between those of *STI_range* **1328** and *STI_horizontal_flushed_range* **1330**.
 Then the range of cells *STI_vertical_flushed_range* **1332** is determined as the range of cells sharing the same columns as *STI_range* **1328**, and occupying the *STI_height* **1326** bottom columns of the current sheet **1320**.
 Then the range of cells *STI_vertical_kept_range* **1331** is determined as the range of cells sharing the same columns as *STI_range* **1328**, and occupying the rows located between those of *STI_range* **1328** and *STI_vertical_flushed_range* **1332**.
- At step **1407**, two sums are performed to check if the future STI will fit within the boundaries of the current sheet **1320**.

- If the sum of the local variables *STI_offset_width* 1323 and *STI_width* 1325 is found greater than the local variable *STI_sheet_width* 1321, then a local variable *STI_too_wide* is set to "YES"; otherwise it is set to "NO".
- If the sum of the local variables *STI_offset_height* 1324 and *STI_height* 1326 is found greater than the local variable *STI_sheet_height* 1322, then a local variable *STI_too_high* is set to "YES"; otherwise it is set to "NO".

At step 1408, several tests are performed to evaluate the potential impact of the creation of the future STI, according to the five possible instantiation modes, on any already existing STI or data. These tests require to parse the STIT table 750, and to visit each record 751 to learn the address ("Address" field 752) and the importance ("Critical" field 755) of every already defined STI. These tests evaluate either if two given ranges of cells partially overlap (meaning that there exist in the first range of cells at least one cell belonging to the second range of cells and at least one cell not belonging to the second range of cells) or if a first given range of cells is included within a second given range of cells (meaning that every cell belonging to the first range of cells belongs too to the second range of cells). Different conventional range comparison techniques can be used for evaluating either range partial overlapping or range inclusion, without departing from the spirit of the present invention; they will not be described in the preferred embodiment of the present invention.

First the OVERLAY mode of instantiation is investigated.

- If there exists at least one existing STI whose "Critical" field 755 takes the value "YES" and which partially overlaps the range of cells *STI_range* 1328, then the local test variable *STI_overlay_critical* takes the value "YES"; otherwise the local test variable *STI_overlay_critical* takes the value "NO".
- If there exists at least one existing STI whose "Critical" field 755 takes the value "NO" and which partially overlaps the range of cells *STI_range* 1328, then the local test variable *STI_overlay_other* takes the value "YES"; otherwise the local test variable *STI_overlay_other* takes the value "NO".
- If all the cells within the range of cells *STI_range* 1328 are empty (containing none data), then the local test variable *STI_overlay_data* takes the value "NO"; otherwise the local test variable *STI_overlay_data* takes the value "YES".

Second the HORIZONTAL_INSERT mode of instantiation is investigated.

- If there exists at least one existing STI whose "Critical" field 755 takes the value "YES" and which partially overlaps the range of cells made of the entire row where is located the currently selected cell 1327, or which partially overlaps the range of cells constituted by the last bottom *STI_height* 1326 rows, or which is included in the range of cells constituted by the last bottom *STI_height* 1326 rows, then the local test variable *STI_horizontal_critical* takes the value "YES"; otherwise the local test variable *STI_horizontal_critical* takes the value "NO".
- If there exists at least one existing STI whose "Critical" field 755 takes the value "NO" and which partially overlaps the range of cells made of the entire row where is located the currently selected cell 1327, or which partially overlaps the range of cells constituted by the last bottom *STI_height* 1326 rows, or which is included in the range of cells constituted by the last bottom *STI_height* 1326 rows, then the local test variable *STI_horizontal_other* takes the value "YES"; otherwise the local test variable *STI_horizontal_other* takes the value "NO".
- If all the cells within the range of cells constituted by the last bottom *STI_height* 1326 rows are empty (containing none data), then the local test variable *STI_horizontal_data* takes the value "NO"; otherwise the local test variable *STI_horizontal_data* takes the value "YES".

Third the HORIZONTAL_INSERT_BY_RANGE mode of instantiation is investigated.

- If there exists at least one existing STI whose "Critical" field 755 takes the value "YES" and which partially overlaps the range of cells constituted by the concatenation of the

two ranges of cells *STI_range* 1328 and *STI_vertical_kept_range* 1331, or which partially overlaps the range of cells *STI_vertical_flushed_range* 1332, or which is included in the range of cells *STI_vertical_flushed_range* 1332, then the local test variable *STI_horizontal_range_critical* takes the value "YES"; otherwise the local test variable *STI_horizontal_range_critical* takes the value "NO".

- If there exists at least one existing STI whose "Critical" field 755 takes the value "NO" and which partially overlaps the range of cells constituted by the concatenation of the two ranges of cells *STI_range* 1328 and *STI_vertical_kept_range* 1331, or which partially overlaps the range of cells *STI_vertical_flushed_range* 1332, or which is included in the range of cells *STI_vertical_flushed_range* 1332, then the local test variable *STI_horizontal_range_other* takes the value "YES"; otherwise the local test variable *STI_horizontal_range_other* takes the value "NO".
- If all the cells within the range of cells *STI_vertical_flushed_range* 1332 are empty (containing none data), then the local test variable *STI_horizontal_range_data* takes the value "NO"; otherwise the local test variable *STI_horizontal_range_data* takes the value "YES".

Fourth the VERTICAL_INSERT mode of instantiation is investigated.

- If there exists at least one existing STI whose "Critical" field 755 takes the value "YES" and which partially overlaps the range of cells made of the entire column where is located the currently selected cell 1327, or which partially overlaps the range of cells constituted by the last right *STI_width* 1325 columns, or which is included in the range of cells constituted by the last right *STI_width* 1325 columns, then the local test variable *STI_vertical_critical* takes the value "YES"; otherwise the local test variable *STI_vertical_critical* takes the value "NO".
- If there exists at least one existing STI whose "Critical" field 755 takes the value "NO" and which partially overlaps the range of cells made of the entire column where is located the currently selected cell 1327, or which partially overlaps the range of cells constituted by the last right *STI_width* 1325 columns, or which is included in the range of cells constituted by the last right *STI_width* 1325 columns, then the local test variable *STI_vertical_other* takes the value "YES"; otherwise the local test variable *STI_vertical_other* takes the value "NO".
- If all the cells within the range of cells constituted by the last right *STI_width* 1325 columns are empty (containing no data), then the local test variable *STI_vertical_data* takes the value "NO"; otherwise the local test variable *STI_vertical_data* takes the value "YES".

Fifth the VERTICAL_INSERT_BY_RANGE mode of instantiation is investigated.

- If there exists at least one existing STI whose "Critical" field 755 takes the value "YES" and which partially overlaps the range of cells constituted by the concatenation of the two ranges of cells *STI_range* 1328 and *STI_horizontal_kept_range* 1329, or which partially overlaps the range of cells *STI_horizontal_flushed_range* 1330, or which is included in the range of cells *STI_horizontal_flushed_range* 1330, then the local test variable *STI_vertical_range_critical* takes the value "YES"; otherwise the local test variable *STI_vertical_range_critical* takes the value "NO".
- If there exists at least one existing STI whose "Critical" field 755 takes the value "NO" and which partially overlaps the range of cells constituted by the concatenation of the two ranges of cells *STI_range* 1328 and *STI_horizontal_kept_range* 1329, or which partially overlaps the range of cells *STI_horizontal_flushed_range* 1330, or which is included in the range of cells *STI_horizontal_flushed_range* 1330, then the local test variable *STI_vertical_range_other* takes the value "YES"; otherwise the local test variable *STI_vertical_range_other* takes the value "NO".
- If all the cells within the range of cells *STI_horizontal_flushed_range* 1330 are empty (containing none data), then the local test variable *STI_vertical_range_data* takes the

value "No"; otherwise the local test variable *STI_vertical_range_data* takes the value "YES".

- 5 • At step **1409**, the ST Instanciator Dialog Box **1300** is displayed on the display device **106**. The "*Critical*" check box **1314** displays a check mark if the local variable *STI_critical* takes the value "YES"; otherwise (value "No"), the "*Critical*" check box **1314** is kept with a blank empty display. The label box **1315** is initialized with the value of the local variable *ST_name*. The text box **1312** is filled with the value of the local variable *STI_element*. The label box **1311** is filled with the value of the local variable *STI_too_wide* and the label box **1310** is filled with the value of the local variable *STI_too_high*. The 15 label boxes **1304** are filled row after row, starting with the top row, from the left to the right, with the values of the following local variables in the following order: *STI_overlay_critical*, *STI_overlay_other*, *STI_overlay_data*, *STI_horizontal_critical*, *STI_horizontal_other*, *STI_horizontal_data*, *STI_horizontal_range_critical*, *STI_horizontal_range_other*, *STI_horizontal_range_data*, *STI_vertical_critical*, *STI_vertical_other*, *STI_vertical_data*, *STI_vertical_range_critical*, *STI_vertical_range_other*, *STI_vertical_range_data*. Then if the local variable *STI_mode* takes the respective value OVERLAY, or HORIZONTAL_INSERT, or HORIZONTAL_INSERT_BY_RANGE, or VERTICAL_INSERT, or VERTICAL_INSERT_BY_RANGE, then the option button "*Overlay*" **1309**, or "*Horizontal Insert*" **1308**, or "*Horizontal Insert by Range*" **1307**, or "*Vertical Insert*" **1306**, or "*Vertical Insert by Range*" **1305** displays alone a black point. Finally the "*Create*" push-button **1303** is disabled as soon as one of the following local variables takes the value "YES": *STI_too_wide*, *STI_too_high*, *STI_overlay_critical* (only taken into account if the local variable *STI_mode* is equal to OVERLAY), *STI_horizontal_critical* (only taken into account if the local variable *STI_mode* is equal to HORIZONTAL_INSERT), *STI_vertical_critical* (only taken into account if the local variable *STI_mode* is equal to VERTICAL_INSERT), *STI_horizontal_range_critical* (only taken into account if the local variable *STI_mode* is equal to HORIZONTAL_INSERT_BY_RANGE), *STI_vertical_range_critical* (only taken into account if the local variable *STI_mode* is equal to VERTICAL_INSERT_BY_RANGE); otherwise the "*Create*" push-button **1303** is enabled.
- 30 • At step **1410**, the method is waiting for any user action on the ST Instanciator Dialog Box **1300**, or on any change of the currently selected cell. Such user action is typically resulting from a click with the pointing device **105**, but take other similar forms such as, but not limited to a specific combination of key on the keyboard **104**, or any other similar means not further specified here.
- 35 • At step **1411**, a user action on the ST Instanciator Dialog Box **1300**, or a change of the currently selected cell is detected.

 - 40 • If the user action is a click on the "*Create*" push-button **1303**, then control is given to step **1416**;
 - if the user action is a click on the upper part of the spin button **1313**, then control is given to step **1415**;
 - if the user action is a click on the lower part of the spin button **1313**, then control is given to step **1414**;
 - if the user action is a click on the "*Critical*" check box **1314**, then control is given to step **1413**;
 - 45 • if the user action is a click on one of the option buttons **1309**, or **1308**, or **1307**, or **1306**, or **1305**, then control is given to step **1412**;
 - if the user action is a click on the "*Cancel*" push-button **1302**, or on the closing-window push-button **1301**, then control is given to step **1418**;
 - 50 • finally if the user action is a change in the position of the currently selected cell, then control is given to step **1406**.
- At step **1412**, the local variable *STI_mode* takes the value OVERLAY, or HORIZONTAL_INSERT, or HORIZONTAL_INSERT_BY_RANGE, or VERTICAL_INSERT, or VERTICAL_INSERT_BY_RANGE if the

spreadsheet user has respectively clicked with the pointing device **105** on the option button **1309**, or **1308**, or **1307**, or **1306**, or **1305**. Then control is given to step **1406**.

- At step **1413**, the local variable *STI_critical* is updated in order to swap between the values "YES" and "NO". Then control is given to step **1406**.
- 5 ◦ At step **1414**, the local variable *STI_element* is decremented by 1 (one), as long as its value remains greater than or equal to the value of the local variable *STI_min*. Then control is given to step **1406**.
- At step **1415**, the local variable *STI_element* is incremented by 1 (one), as long as its value remains less than or equal to the value of the local variable *STI_max*. Then control is given to step **1406**.
- 10 • At step **1416**, the STIT table **750** is visited to remove from it every record **751** corresponding to a STI corrupted by the introduction of the new instance, as identified during the step **1408** for the insertion mode represented by the local variable *STI_mode*.
- 15 Then the STT table **720** is updated to reflect the removal of each STI. For each removed STI, the INSTANCE REFERENCE (IR) field **729c** of the "REFERENCED" attribute **729** of the record **721** whose "Name" field **722** is equal to the "ST" field **753** of the record **751** of the STIT table **750** corresponding to the removed STI, is divided by 2 (two).
- At step **1417**, the routine CreateSTI is called.
- 20 • At step **1418**, the ST Instanciator Dialog Box **1300** is closed so that it disappears from the display device **106**. Finally control is given back to the initial step **1401** for processing any future *ST Instanciator* command.

The following steps, all part of FIG **14B**, correspond to the execution of the *CreateSTI* routine, as used in the preferred embodiment of the present invention

- 25 • At step **1419**, a new record **751** is introduced in the STIT table **750**. Within this record **751**, the "Address" field **752** is initialized with the address of the range of cells *STI_range* **1328**, the "ST" field **753** is initialized with the value of the local variable *ST_name*, the "Element #" field **754** is initialized with the value of the local variable *STI_element*, the "Critical" field **755** is initialized with the value of the local variable *STI_critical*, the
- 30 "Header Size" field **756** is initialized with the number of meta-elements constituting the header part of the new STI (this number being equal to the number of pairs in the header part **767** of the STDT table **760** associated to the ST that the new STI will abide by), and the "Footer Size" field **757** is initialized with the number of meta-elements constituting the footer part of the new STI (this number being equal to the number of
- 35 pairs in the footer part **766** of the STDT table **760** associated to the ST abided by the new STI). Then the STT table **720** is scanned to identify the record **721** whose "Name" field is found equal to the local variable *ST_name*. Once found, the "REFERENCED" attribute **729** within the "Type" field **727** of this record **721** is updated by multiplying the "INSTANCE REFERENCE" subfield **729c** by 2 (two).
- 40 • At step **1420** a test is performed to check the value of the local variable *STI_mode*.
 - If this value is found equal to OVERLAY then control is given to step **1425**,
 - If this value is found equal to HORIZONTAL_INSERT then control is given to step **1424**,
 - If this value is found equal to HORIZONTAL_INSERT_BY_RANGE then control is given to step **1422**,
 - 45 • If this value is found equal to VERTICAL_INSERT then control is given to step **1423**,
 - If this value is found equal to VERTICAL_INSERT_BY_RANGE then control is given to step **1421**.
- At step **1421**, the range of cells *STI_range* **1328** is selected to become the currently selected range of cells, with the currently selected cell being kept in its former position
- 50 **1327** and then a regular operation of "column insertion within selected range" is performed. Then control is given to step **1425**.
- At step **1422**, the range of cells *STI_range* **1328** is selected to become the currently selected range of cells, with the currently selected cell being kept in its former position

1327 and then a regular operation of "row insertion within selected range" is performed. Then control is given to step 1425.

- At step 1423, the range of cells *STI_range* 1328 is selected to become the currently selected range of cells, with the currently selected cell being kept in its former position 1327 and then a regular operation of "column insertion" is performed. Then control is given to step 1425.
- At step 1424, the range of cells *STI_range* 1328 is selected to become the currently selected range of cells, with the currently selected cell being kept in its former position 1327 and then a regular operation of "row insertion" is performed. Then control is given to step 1425.
- At step 1425, a local variable *STI_index* is initialized to the value taken by the local variable *STI_element*. Then the STT table 720 is parsed to identify the record 721 whose "Name" field 722 matches the value of the local variable *ST_name*. Within this record 721 is retrieved the "Description Ptr" field 724 allowing to locate in memory the STDT table 760 associated to the ST that the new STI to be created will abide by. Then the first pair 761 of element or MEF name and element or MEP name found within this STDT table 760 is set as the current pair of names: (EF or MEF name, EP or MEP name).
- At step 1426, the EPT table 710 is parsed to find the record 711 whose "Name" field 712 is found equal to the EP or MEP name within the current pair. Once this record 711 is found, its "Description Ptr" field 714 is retrieved to locate in memory the range of cells illustrating the EP or MEP. This description of the EP or MEP is copy-pasted by value only onto the currently selected cell, so that the corresponding row within the *STI_range* receives the EP or MEP initial values. Then the EFT table 700 is parsed to find the record 701 whose "Name" field 702 is found equal to the EF or MEF name within the current pair. Once this record 701 is found, its "Description Ptr" field 704 is retrieved to locate in memory the range of cells illustrating the EF or MEF. This description of the EF or MEF is copy-pasted by attribute only onto the currently selected cell, so that the corresponding row within the *STI_range* receives the EF or MEF attributes.
- At step 1427 a test is performed to check if the current pair (EF or MEF name, EP or MEP name) corresponds to an element or to a meta-element. In the first case, control is given to step 1428, and in the second case control is given to step 1429.
- At step 1428, the local variable *STI_index* is decremented by 1 (one). Then control is given to step 1430.
- At step 1429, a test is performed to check if the current pair (EF or MEF name, EP or MEP name) is the last one 763 within the STDT table 760. If it is the case, the execution of the **CreateSTI** routine completes by returning control to the routine caller, otherwise control is given to step 1431.
- At step 1430, a test is performed to check if the local variable *STI_index* is equal to 0 (zero). If it is the case, then control is given to step 1429, otherwise control is given to step 1432.
- At step 1431, the pair of names (EF or MEF name, EP or MEP name) following the current one in the STDT table 760 becomes the current pair of names.
- At step 1432, the currently selected cell is moved downwards by one row. Then control is given to step 1426.

E7. RST Instanciator method

The method for instanciating a RST used in the preferred embodiment of the present invention is summarized in flowchart 2100 of FIG 16A and 16B. This method can be seen as the processing of the **ST Instanciator** command.

- At step 2101, the method is in its default state, waiting for an event to initiate the process.
- At step 2102, the **RST Instanciator** command is detected, as a result of a user action. This action can be for instance a specific combination of keys on the keyboard 104, or

the click of the pointing device **105** on a specific button, or any other similar means no further specified here.

- At step **2103**, the command parameter is retrieved and some local variables are initialized:
 - 5 ◦ The command parameter is recorded in the *RST_Name* variable.
 - The local variable *Element#* is initialized with the value 0 (zero).
 - The local variable *too_wide* is initialized with the default value FALSE.
 - The local variable *too_high* is initialized with the default value FALSE.
 - 10 ◦ The local variable *Max_col* is initialized with the maximum number of available columns on a sheet.
 - If the local variable *Max_row* is initialized with the maximum number of available rows on a sheet.
 - The local variable *STI_present* is initialized with the default value FALSE.
 - The local variable *RSTI_busy* is initialized with the default value FALSE.
 - 15 • The local variable *RSTI_top_left_cell* is initialized as being the currently selected cell.
- At step **2104**, the RSTT table **2220** is parsed to identify the record **2221** (identified by the local variable *Curr_RSTT_rec*) whose "Name" field **2222** is equal to the command parameter *RST_Name*. Then the local variable *RSTI_E#* is set equal to the value of the "Min Element#" field **2225** of this record *Curr_RSTT_rec* **2221**.
- 20 • At step **2105**, the local variable *Curr_RSTDT* is set equal to the RSTDT table **2250** pointed by the "Description Ptr" field **2224** of the record *Curr_RSTT_rec* **2221**. Then the local variable *Curr_RSTDT_rec* is set equal to the first single-cell record **2251** of the *Curr_RSTDT* table **2250**. Then the local variable *Curr_RET_rec* is set equal to the record **2211** of the RET table **2210**, with a "Name" field **2212** equal to the local variable *Curr_RSTDT_rec*. Then the local variable *Curr_RED_RoC* is set equal to the range of cells pointed by the "Description Ptr" field **2214** of the record *Curr_RET_rec* **2211**.
- 25 • At step **2106**, a RSTIDT table **2270** is loaded in memory and named through the local variable *Curr_RSTIDT*. This table has a number of rows equal to the numbers of rows of the *Curr_RSTDT* table **2250**, incremented by the value of the local variable *RSTI_E#* and decremented by 1 (one). This table has a number of columns equal to the number of columns of the *Curr_RED_RoC* range of cells. Then the local variable *Curr_RSTIDT_rec* is initialized as the first record **2271** of the *Curr_RSTIDT* table **2270**.
- 30 • At step **2107**, the local variable *Curr_RSTIDT_cell* is initialized as the first cell **2280** of the *Curr_RSTIDT_rec* **2271**. Then the local variable *Curr_REC_RoC_cell* is initialized as the first cell of the *Curr_REC_RoC* range of cells.
- 35 • At step **2108**, the "STI_col" field **2278** of the *Curr_RSTIDT_cell* **2280** is set equal to the value returned by the function *STI_col* when called with the unique parameter equal to the value of the local variable *Curr_RET_RoC_cell*. Then the "STI_row" field **2279** of the *Curr_RSTIDT_cell* **2280** is set equal to the value returned by the function *STI_row* when called with the two parameters respectively equal to the value of the local variable *Curr_RET_RoC_cell* and to 0 (zero). Then the "ST_name" field **2280** of the *Curr_RSTIDT_cell* **2280** is set equal to the value of the local variable *Curr_RET_RoC_cell*.
- 40 • At step **2109**, a test is performed to check if the cell represented by the local variable *Curr_RSTIDT_cell* **2280** is the last cell of the record represented by the local variable *Curr_RSTIDT_rec* **2271**. If it is the case, then control is given to step **2111**; otherwise control is given to step **2110**.
- 45 • At step **2110**, the cell located on the right of the cell represented by the local variable *Curr_RSTIDT_cell* **2280** becomes the new *Curr_RSTIDT_cell* **2280**. Then the cell located on the right of the cell represented by the local variable *Curr_RET_RoC_cell* becomes the new *Curr_RET_RoC_cell*. Then control is given to step **2108**.
- 50 • At step **2111**, a test is performed to check if the record represented by the local variable *Curr_RET_rec* **2211** describes a RE. This can be determined if the "META" attribute **2218**

of the "Type" field **2217** of the *Curr_RET_rec* record **2211** is equal to the value "No". If it is the case, then control is given to step **2112**; otherwise control is given to step **2114**.

- At step **2112**, the local variable *Element#* is incremented by 1 (one).
- 5 • At step **2113**, a test is performed to determine if the local variable *Element#* is equal to the local variable *RSTI_E#*. If it is the case, then control is given to step **2114**; otherwise control is given to step **2115**.
- At step **2114**, a test is performed to check if the cell represented by the local variable *Curr_RSTIDT_cell* **2280** is the last cell of the record represented by the local variable *Curr_RSTIDT_rec* **2271**. If it is the case, then control is given to step **2116**; otherwise control is given to step **2117**.
- 10 • At step **2115**, the record following the *Curr_RSTIDT_rec* record **2271** in the *Curr_RSTIDT* table **2270** becomes the new *Curr_RSTIDT_rec* record **2271**. Then control is given to step **2107**.
- At step **2116**, the record following the *Curr_RSTDT_rec* record in the *Curr_RSTDT* table **2250** becomes the new *Curr_RSTDT_rec*. Then control is given to step **2115**.
- 15 • At step **2117**, for each cell *Curr_RSTIDT_cell* **2280** belonging to the *Curr_RSTIDT* table **2270**, the "container_row" attribute **2281** is set equal to the maximum value of the "STI_row" attribute **2279** of the cells *Same_row_cell* located within the *Curr_RSTIDT* table **2270** on the same row as *Curr_RSTIDT_cell*. Then for each cell *Curr_RSTIDT_cell* **2280** belonging to the *Curr_RSTIDT* table **2270**, the "container_col" attribute **2277** is set equal to the maximum value of the "STI_col" attribute **2278** of the cells *Same_col_cell* located within the *Curr_RSTIDT* table **2270** on the same column as *Curr_RSTIDT_cell*.
- 20 • At step **2118**, the local variable *RSTI_col* is set equal to the sum of the "container_col" attributes **2277** of the cells belonging to the first row of the *Curr_RSTIDT* table **2270**. Then the local variable *RSTI_row* is set equal to the sum of the "container_row" attributes **2281** of the cells belonging to the first column of the *Curr_RSTIDT* table **2270**.
- 25 • At step **2119**, a test is performed to determine if the sum of the local variable *RSTI_col* and of the column index of the individual cell *RSTI_top_left_cell* decremented by 1 (one) is strictly greater than the local variable *Max_col*. If it is the case, then control is given to step **2120**; otherwise control is given to step **2121**.
- 30 • At step **2120**, the local variable *too_wide* is set equal to the value TRUE.
- At step **2121**, a test is performed to determine if the sum of the local variable *RSTI_row* and of the row index of the individual cell *RSTI_top_left_cell* decremented by 1 (one) is strictly greater than the local variable *Max_row*. If it is the case, then control is given to step **2122**; otherwise control is given to step **2123**.
- 35 • At step **2122**, the local variable *too_high* is set equal to the value TRUE.
- At step **2123**, a test is performed to determine if there is any existing STI present on the same sheet as the individual cell *RSTI_top_left_cell*. This test can simply be done by parsing the STIT table **750** for identifying any record **751** with an "Address" field **752** pointing to the same sheet as the individual cell *RSTI_top_left_cell*. If it is the case, then control is given to step **2124**; otherwise control is given to step **2125**.
- 40 • At step **2124**, the local variable *STI_present* is set equal to the value TRUE.
- At step **2125**, the local variable *RSTI_range* is initialized as being the range of cells with *RSTI_top_left_cell* as the top left cell, with a number of rows equal to the value of the local variable *RSTI_row*, and with a number of columns equal to the value of the local variable *RSTI_col*.
- 45 ◦ At step **2126**, a test is performed to check if there is any data present within the range of cells *RSTI_range*. If it is the case, then control is given to step **2127**; otherwise control is given to step **2128**.
- 50 ◦ At step **2127**, the local variable *RSTI_busy* is set equal to the value TRUE.
- At step **2128**, the RST Instanciator dialog box **2300** is displayed on the display device **106**. Within this dialog box **2300**, the text field **2302** is filled with the value of the local variable *RST_name*, the text field **2311** is filled with the value of the local variable

RSTI_E#, the text field **2304** is filled with the value of the local variable *too_wide*, the text field **2305** is filled with the value of the local variable *too_high*, the text field **2306** is filled with the value of the local variable *STI_present*, the text field **2307** is filled with the value of the local variable *RSTI_busy*. The "Create Instance" push-button **2310** is enabled if and only if the three local variables *too_wide*, *too_high* and *STI_present* take the same value FALSE. The "Create instance in a new sheet" push-button **2309** is enabled if and only if the two local variables *too_wide* and *too_high* take the same value FALSE.

- 5 • At step **2129**, the method is waiting for any user action on the RST Instanciator dialog box **2300**. Such user action is typically resulting from a click with the pointing device **105**, but take other similar forms such as, but not limited to a specific combination of keys on the keyboard **104**, or any other similar means not further specified here.
- 10 • At step **2130**, a user action on the RST Instanciator dialog box **2300** is detected.
 - 15 • If the user action is a click with the pointing device **105** on one "Up" arrow of the spin-button **2303**, then control is given to step **2133**.
 - 20 • If the user action is a click with the pointing device **105** on one "Down" arrow of the spin-button **2303**, then control is given to step **2134**.
 - 25 • If the user action is a click with the pointing device **105** on the "Create instance" push-button **2310**, then control is given to step **2138**.
 - 30 • If the user action is a click with the pointing device **105** on the "Create instance in a new sheet" push-button **2309**, then control is given to step **2136**.
 - 35 • If the user action is a click with the pointing device **105** on the "Cancel" push button **2308**, or on the closing-window push-button **2301**, then control is given to step **2131**.
- At step **2131**, the range of cells *Curr_RSTIDT* is released from memory.
- At step **2132**, the RST Instanciator dialog box **2300** is closed on the display device **106** and then control is given back to the initial step **2101** for processing any future *RST Instanciator* command.
- At step **2133**, the local variable *RSTI_E#* is incremented by 1 (one).
- At step **2134**, the local variable *RSTI_E#* is decremented by 1 (one).
- At step **2135**, the range of cells *Curr_RSTIDT* is released from memory, and then control is given to the step **2105**.
- At step **2136**, a new sheet is created and named *curr_sheet*.
- At step **2137**, the top left cell of the sheet *curr_sheet* becomes the new individual cell *RSTI_top_left_cell*.
- At step **2138**, the local variable *STI_mode* is initialized with the value OVERLAY. Then the local variable *STI_critical* is initialized with the value YES. Then the local variable *Curr_RSTIDT_rec* is initialized as being the first record **2271** of the *Curr_RSTIDT* table **2270**. Then the local variable *Curr_RSTIDT_cell* is initialized as being the first cell **2280** of the record *Curr_RSTIDT_rec* **2271**. Then the local variable *Curr_cell* is initialized as being equal to *RSTI_top_left_cell*.
- 40 • At step **2139**, the "container_range" attribute **2276** of the *Curr_RSTIDT_cell* **2280** is initialized as the range of cell having as the top left cell the individual cell *Curr_cell*, having a number of rows equal to the value of the "container_row" attribute **2281**, and having a number of columns equal to the value of the "container_col" attribute **2277**.
- 45 • At step **2140**, the local variable *STI_range* is set equal to the "container_range" attribute **2276** of the *Curr_RSTIDT_cell* **2280**. Then the local variable *ST_name* is set equal to the "ST_name" attribute **2280** of the *Curr_RSTIDT_cell* **2280**. Then the local variable *STI_element* is set equal to the "Min Element#" field **2225** of the record **721** of the STT table **720** with a "Name" field **722** equal to *ST_Name*.
- 50 • At step **2141**, the *CreateSTI* command is invoked (as a sub-routine). When this command completes and returns control to the current process, the control is given to the next step **2142**.

- At step 2142, the "STIT_rec_ptr" attribute 2282 of the *Curr_RSTIDT_cell* 2280 is set as pointing to the STIT record 751 that has just been created during the previous step 2141.
- 5 • At step 2143, a test is performed to check if the cell represented by the local variable *Curr_RSTIDT_cell* 2280 is the last cell of the record represented by the local variable *Curr_RSTIDT_rec* 2271. If it is the case, then control is given to step 2143; otherwise control is given to step 2144.
- 10 • At step 2144, the individual cell *curr_cell* is moved to the right by a number of columns equal to the value of the "container_col" attribute 2277 of *Curr_RSTIDT_cell* 2280. Then the cell located on the right of the individual cell *Curr_RSTIDT_cell* 2280 becomes the new *Curr_RSTIDT_cell* 2280.
- 15 • At step 2145, a test is performed to check if the record represented by the local variable *Curr_RSTIDT_rec* 2271 is the last record of the RSTIDT table represented by the local variable *Curr_RSTIDT* 2270. If it is the case, then control is given to step 2147; otherwise control is given to step 2146.
- 20 • At step 2146, the individual cell *RSTI_top_left_cell* is moved down by a number of rows equal to the value of the "container_row" attribute 2281 of the *Curr_RSTIDT_cell* 2280. Then the individual cell *curr_cell* is set equal to the individual cell *RSTI_top_left_cell*. Then the record 2271 following *Curr_RSTIDT_rec* in *Curr_RSTIDT* 2270 becomes the new record *Curr_RSTIDT_rec* 2271. Then the first cell of *Curr_RSTIDT_rec* 2271 becomes the new individual cell *Curr_RSTIDT_cell* 2280.
- 25 • At step 2147, a new record 2261 is created in the RSTIT table 2260 for describing the RSTI that has just been created. The "Address" field 2262 is filled with the address of the *rir* range of cell 2001. The "RST" field 2263 is filled with the local variable *RST_Name*. The "Element #" field 2264 is filled with the local variable *Element#*. The "RSTIDT Ptr" field 2265 is filled with the local variable *Curr_RSTIDT*. The "Header Size" field 2266 is filled with the number of rows of the container rows constituting the RSTI header 2002. The "Footer Size" field 2267 is filled with the number of rows of the container rows constituting the RSTI footer 2004. Then the RSTT table 2220 is scanned to identify the record 2221 whose "Name" field 2222 is found equal to the local variable *RST_name*. Once found, the "REFERENCED" attribute 2229 within the "Type" field 2227 of this record 2221 is updated by multiplying the "INSTANCE REFERENCE" subfield 2229c by 2 (two). Then control is given to step 2132.

E8. RE Editor method

- 35 The method for creating or updating RE's or meta-elements used in the preferred embodiment of the present invention is summarized in flowchart 2340 of FIG 18C. This method can be seen as the processing of the **RE Editor** command.
- At step 2341, the method is in its default state, waiting for an event to initiate the process.
 - 40 • At step 2342, the **RE Editor** command is detected, as a result of an user action. This action can be for instance:
 - a specific combination of key on the keyboard 104, or
 - the click of the pointing device 105 on a specific button, or
 - any other similar means not further specified here.
 - 45 • At step 2343, the parameter of the command is retrieved. It corresponds to a mandatory parameter *RE_name* which can either take a reserved value "NEW" or another value corresponding to a character string name, as found in the "Name" field 2232 of a record 2231 within the RSTMT table 2230. This parameter is recorded as a local variable.
 - 50 • At step 2344, some local variables are initialized: the local variable *RE_meta* is set to the value "NO", the local variable *RE_size* is set to the value 3 (three), and the local variable *RE_rank* is set to the value 1 (one).

- At step **2345**, a test is performed to determine the value taken by the local variable *RE_name*. If found equal to "NEW", then control is given to step **2349**; otherwise control is given to step **2346**.
- 5 • At step **2346**, the RET table **2210** is looked up to locate a record **2211** whose "Name" field **2212** is found equal to the value taken by the local variable *RE_name*. If such a record is found, then control is given to step **2348**; otherwise control is given to step **2347**.
- 10 • At step **2347**, an exception handler is invoked to treat this "should not occur" condition. Such operation is implementation dependent and can take different forms such as the display on the display device **106** of an error message pop-up window. Then control is given to step **2341**.
- 15 • At step **2348**,
 - the local variable *RE_meta* is set to the value "YES" or "NO" according to the value of the "META" attribute **2218** within the "Type" field **2217** of the record **2211** found at step **2346**,
 - the local variable *RE_size* is set to the value found in the "Column #" field **2216** of the record **2211** found at step **2346**, and
 - the memory location pointed by the "Description Ptr" field **2214** of the record **2211** found at step **2346** is copied onto a temporary buffer recorded as the local variable *RE_buffer*.
- 20 Then control is given to step **2350**.
- 25 • At step **2349**, a new name for the newly created RE is determined, according to a name string taking in a preferred embodiment of the present invention the form "New XX" where XX corresponds to a counter value ensuring the name uniqueness with respect to all the names previously defined and recorded in the "Name" fields **702**, **712**, **722**, **2212** and **2222** found in the respective records **701**, **711**, **721**, **2211** and **2221** of the respective tables EFT **700**, EPT **710**, STT **720**, RET **2210** and RSST **2220**. Any other similar conventional means could be used instead without departing from the spirit of the invention, as long as the uniqueness of the newly created name is ensured.
- 30 Then the new name is recorded in the local variable *RE_name*. Then memory space is allocated within the main memory **102** to later record the illustrative range of cells for the RE or RME. This allocated memory, recorded as the local variable *RE_buffer* is part of the memory space corresponding to the currently opened electronic spreadsheet file. Then a new record **2211** is created in the RET table **2210**, and this new record **2211** is initialized as follows:
 - 35 • the "Name" field **2212** is set to the value of the local variable *RE_name* ;
 - the "Last Change Date" field **2213** is set to the system time reference, as known by the central processor **101** ;
 - 40 • the "Description Ptr" field **2214** is set to the memory location *RE_buffer* which has just been allocated ;
 - the "Row #" field **2215** is set to the value 1 (as in the preferred embodiment of the present invention the RST's are managed in a 2D environment; this field would carry the number of defined rows for the created RE in a 3D environment) ;
 - 45 • the "Column #" field **2216** is set to the value of the local variable *RE_size* ;
 - the "Type" field **2217** is set as follows: the attribute "META" **2218** is set equal to the value of the local variable *RE_meta*, and the attribute "REFERENCED" **2219** is initialized as follows:
 - 50 • The "OWN REFERENCE" (OR) subfield **2219a** is initialized with a prime number not yet assigned to any other OR subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
 - The "FILIALION REFERENCE" (FR) subfield **2219b** is initialized according to the following formula, where the \mathcal{F} set corresponds to the set of ST's constituting the

new RE or meta-element, according to the structure recorded in the "Description Ptr" field **2214**:

$$FR = \prod_{i \in \mathcal{F}} OR_i \times LCM(\{FR_i\})_{i \in \mathcal{F}}$$

- The "INSTANCE REFERENCE" (IR) subfield **2219c** is initialized with the value 1 (one).
- The "REFERENCED OBJECT" (RO) subfield **2219d** is initialized with the following formula, where the \mathcal{P} set corresponds to the set of RST's:

$$RO = \text{"YES"} \text{ if } LCM(\{FR_i\})_{i \in \mathcal{P}} \bmod OR = 0;$$

$$RO = \text{"NO"} \text{ otherwise.}$$

- The "SELECTED CHILDREN" (SC) subfield **2219e** is initialized with the following formula, where the \mathcal{S} set corresponds to the set of selected objects (having the "SELECTED" attribute **2242** equal to the value "YES" in the RSTMT table **2230**):

$$SC = \text{"YES"} \text{ if } LCM(\{FR_i\})_{i \in \mathcal{S}} \bmod OR = 0 \#OR\# RSTE_name \in \mathcal{S},$$

$$SC = \text{"NO"} \text{ otherwise.}$$

Then control is given to step **2350**.

- At step **2350**, the RE Editor Dialog Box **2321** is displayed on the display device **106**.
 - The label box **2324** is initialized with the value of the local variable *RE_name*.
 - The top option button **2331** (respectively bottom option button **2330**) is filled with a black point if the local variable *RE_meta* is found equal to "NO" (respectively "YES").
 - The text box **2326** is filled with the value of the local variable *RE_size*.
 - The push-button "Save" **2333** is enabled if the local variable *RE_size* is found equal to the "Column #" field **2216** of the current record **2211**, or if the attribute "REFERENCED" **2219** within the "Type" field **2217** of this same record **2211** is found with the subfield "REFERENCED OBJECT" **2219d** (RO) equal to "NO", so that any future click with the pointing device **105** on this push-button "Save" **2333** will be recognized as a valid event.
 - The push-button "Save" **2333** is disabled otherwise (local variable *RE_size* is not found equal to the "Column #" field **2216** of the current record **2211**, and the attribute "REFERENCED" **2219** within the "Type" field **2217** of this same record **2211** is found with the subfield "REFERENCED OBJECT" **2219d** (RO) equal to "YES"), so that any future click with the pointing device **105** on this push-button "Save" **2333** will not be recognized as an event.
 - The text box **2335** is initialized with the value of the local variable *RE_rank*.
 - The list box **2334** is initialized with the content of the cell belonging to *RE_buffer* and whose offset is equal to *RE_rank*. The list of names available within this list box **2334** (by clicking on the spin button **2328**) is constituted by the names of the ST's recorded in the STT table **720**.
- At step **2351**, the method is waiting for any user action on the RE Editor Dialog Box **2321**. Such user action is typically resulting from a click with the pointing device **105**, but take other similar forms such as, but not limited to a specific combination of key on the keyboard **104**, or any other similar means not further specified here.
- At step **2352**, a user action on the RE Editor Dialog Box **2321** is detected.
 - If the user action is a click on the spin button **2328**, to select a ST name, then control is given to step **2353**;
 - if the user action is a click on the push-button "Save" **2333**, then control is given to step **2354**;
 - if the user action is a click on the push-button "Save As" **2332**, then control is given to step **2355**;
 - if the user action is a click on the spin button **2329**, then control is given to step **2358**;
 - if the user action is a click on the spin button **2327**, then control is given to step **2359**;
 - if the user action is a click on one of the two option buttons **2330** or **2331**, then control is given to step **2360**;

- if the user action is a click on the push-button "Done" **2323**, or on the closing-window push-button **2322**, then control is given to step **2361**.
 - At step **2353**, the local variable *RE_buffer* is updated by setting equal to the content of the list box **2334** the content of the cell with offset equal to the value of the local variable *RE_rank*. Then control is given to step **2350**.
 - At step **2354**, the RET table **2210** is updated and saved as part of the electronic spreadsheet file by refreshing the record **2211** whose "Name" field **2212** is equal to the local variable *RE_name*. For this purpose,
 - the "Last Change Date" field **2213** is set to the system time reference, as known by the central processor **101** ;
 - the "Column #" field **2216** is set to the value of the local variable *RE_size* ;
 - the "Type" field **2217** is set as follows: the attribute "META" **2218** is set equal to the value of the local variable *RE_meta*.
- In addition the range of cells *RE_buffer* illustrating the current definition of the RE or meta-element is copied onto the memory location pointed by the "Description Ptr" field **2214**. Then control is given to step **2350**.
- At step **2355**, a test is performed on the value found in the text box **2325** to determine if it corresponds to a valid new name. The corresponding criteria are implementation dependent and may take different forms without departing from the spirit of the invention, as long as the new proposed name is a unique character string against all the already defined names recorded in the "Name" fields **702**, **712**, **722**, **2212** and **2222**. If validity and uniqueness are proven, then control is given to step **2356**; otherwise control is given to step **2357**.
 - At step **2356**, memory space is allocated within the main memory **102** to later record the illustrative range of cells for the EF or MEF. This allocated memory is part of the memory space corresponding to the currently opened electronic spreadsheet file. Then a new record **2211** is created in the RET table **2210** which is saved as part of the electronic spreadsheet file, and this new record **2211** is initialized as follows:
 - the "Name" field **2212** is set to the value found in the text box **2325** and validated at step **2355**;
 - the "Last Change Date" field **2213** is set to the system time reference, as known by the central processor **101** ;
 - the "Description Ptr" field **2214** is set to the memory location *RE_buffer* which has just been allocated ;
 - the "Row #" field **2215** is set to the value 1 (as in the preferred embodiment of the present invention the RST's are managed in a 2D environment; this field would carry the number of defined rows for the created RE in a 3D environment) ;
 - the "Column #" field **2216** is set to the value of the local variable *RE_size* ;
 - the "Type" field **2217** is set as follows: the attribute "META" **2218** is set equal to the value of the local variable *RE_meta*, and the attribute "REFERENCED" **2219** is initialized as follows:
 - The "OWN REFERENCE" (OR) subfield **2219a** is initialized with a prime number not yet assigned to any other subfield **709a**, or **719a**, or **729a**, or **780a**, or **2219a**, or **2229a**, or **2240a**. Various conventional techniques can be used for identifying a prime number, and are not further detailed here.
 - The "FILATION REFERENCE" (FR) subfield **2219b** is initialized according to the following formula, where the \mathcal{F} set corresponds to the set of ST's constituting the new RE or meta-element, according to the structure recorded in the "Description Ptr" field **2214**:

$$FR = \prod_{i \in \mathcal{F}} OR_i \times LCM(\{FR_i\})_{i \in \mathcal{F}}$$
 - The "INSTANCE REFERENCE" (IR) subfield **2219c** is initialized with the value 1 (one).
 - The "REFERENCED OBJECT" (RO) subfield **2219d** is initialized with the following formula, where the \mathcal{P} set corresponds to the set of RST's:

RO = "YES" if $\text{LCM}(\{FR_i\})_{i \in S} \text{ Mod } OR = 0$;
 RO = "NO" otherwise.

- The "SELECTED CHILDREN" (SC) subfield **2219e** is initialized with the following formula, where the *S* set corresponds to the set of selected objects (having the "SELECTED" attribute **2242** equal to the value "YES" in the RSTMT table **2230**):

SC = "YES" if $\text{LCM}(\{FR_i\})_{i \in S} \text{ Mod } OR = 0 \text{ \#OR\# } RSTE_name \in S$;
 SC = "NO" otherwise.

Then control is given to step **2350**.

- At step **2357**, a warning message notification is issued for informing the user that a valid and unique name must be specified in the text box **2325** prior to clicking on the "Save As" push-button **2332**. This can typically be done by displaying on the display device **106** a warning message in a pop-up window, or in a status bar area, but any other similar means could be used instead, without departing from the spirit of the invention. Once the user has acknowledged this notification message through conventional means such as clicking with the pointing device **105** on an "OK" push-button present within a warning message pop-up window, or any other similar means without departing from the spirit of the invention, control is given to step **2350**.
- At step **2358**, the local variable *RE_rank* is decremented by 1 (one) as long as it remains strictly positive if the user has clicked with the pointing device **106** on the down side of the spin button **2329**, and the local variable *RE_rank* is incremented by 1 (one) as long as it remains lower than or equal to the value of the local variable *RE_size*, if the user has clicked with the pointing device **106** on the up side of the spin button **2329**. Then control is given to step **2350**.
- At step **2359**, the local variable *RE_size* is either incremented or decremented by 1 (one) according to the direction (up or down) specified by the pointing device **105** on the spin button **2327**, and as long as its value remains positive and less than or equal to an upper limit set equal to 254 in a preferred embodiment of the present invention. Then control is given to step **2350**.
- At step **2360**, the local variable *RE_meta* is updated, so that its value becomes "YES" (respectively "NO") if the bottom option button **2330** (respectively the top option button **2331**) has been clicked on. Then control is given to step **2350**.
- At step **2361**, the RE Editor Dialog Box **2321** is closed so that it disappears from the display device **106**. Finally control is given back to the initial step **2341** for processing any future *RE Editor* command.

E9. STI Column/Row counter method

The method for counting the number of columns or rows within a STI used in the preferred embodiment of the present invention is summarized in flowcharts **2400** and **2420** of FIG **19A** and **19B**. These methods can be seen as the processing of the *STI_Row* and *STI_col* functions.

- At step **2401**, the first method is in its default state, waiting for a call to the *STI_Row* function.
- At step **2402**, the *STI_Row* function call is detected, as a result of a user action. The function is called with two parameters named *ST_Name* and *STI_Element*.
- At step **2403**, the first record **721** of the STT table **720** is set as *Curr_Record*.
- At step **2404**, the fields Name **722**, Min Element# **725**, and Max Element# **726** of the record *Curr_Record* **721** are respectively set as the local variables *Curr_Name*, *Curr_Min* and *Curr_Max*.
- At step **2405**, a test is performed to check if the local variable *Curr_Name* is equal to the function parameter *ST_Name*. If it is the case, then control is given to step **2409**; otherwise control is given to step **2406**.
- At step **2406**, a test is performed to check if the record **721** *Curr_Record* is the last record of the STT table **720**. If it is the case, then control is given to step **2408**; otherwise control is given to step **2407**.

- At step **2407**, the record following *Curr_Record* in the STT table **720** becomes the new record **721** *Curr_Record*. Then control is given to step **2404**.
- At step **2408**, the local variable *STI_Row* is set equal to the value 0 (zero). Then control is given to step **2412**.
- 5 • At step **2409**, the range of cells pointed by the description Ptr field **724** of the record **721** *Curr_Record* is set as *STDT_address*.
 - At step **2410**, the local variable *Element_Nbr* is set equal to the input parameter *STI_Element*, upper bounded by the local variable *Curr_Max*, and minored by the local variable *Curr_Min*.
- 10 • At step **2411**, the local variable *STI_row* is set equal to the number of rows of the range of cells *STDT_adress*, incremented by the value of the local variable *STI_Element*, and decremented by 1 (one).
 - At step **2412**, the execution of the *STI_row* function completes as control is returned to the function caller.
- 15 • At step **2421**, the second method is in its default state, waiting for a call to the *STI_Col* function.
 - At step **2422**, the *STI_Col* function call is detected, as a result of a user action. The function is called with one parameter named *ST_Name*.
 - At step **2423**, the first record **721** of the STT table **720** is set as *Curr_Record*.
- 20 • At step **2424**, the field Name **722** of the record *Curr_Record* **721** is set as the local variables *Curr_Name*.
 - At step **2425**, a test is performed to check if the local variable *Curr_Name* is equal to the function parameter *ST_Name*. If it is the case, then control is given to step **2429**; otherwise control is given to step **2426**.
- 25 • At step **2426**, a test is performed to check if the record **721** *Curr_Record* is the last record of the STT table **720**. If it is the case, then control is given to step **2428**; otherwise control is given to step **2427**.
 - At step **2427**, the record following *Curr_Record* in the STT table **720** becomes the new record **721** *Curr_Record*. Then control is given to step **2424**.
- 30 • At step **2428**, the local variable *STI_Row* is set equal to the value 0 (zero). Then control is given to step **2431**.
 - At step **2429**, the range of cells pointed by the description Ptr field **724** of the record **721** *Curr_Record* is set as *STDT_address*.
 - At step **2430**, the local variable *STI_col* is set equal to the number of columns of the range of cells *STDT_adress*.
- 35 • At step **2431**, the execution of the *STI_col* function completes as control is returned to the function caller.

ALTERNATE EMBODIMENTS

- The methods and systems according to the present invention may be used advantageously in those environments where elements of information are organized as vertically structured two dimensions tables. The methods and systems according to the present invention may be used advantageously in those environments where elements of information are organized as multidimensional tables having more than two dimensions. While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood that various changes in form and detail may be made therein without departing from the spirit, and scope of the invention.